


**GENERAL**

**TYPE:** Test adaptor LUXCIS ML - LUXCIS ML  
LUXCIS : LuxCis ML contact, mono key  
Zirconia alignment sleeve

**CHARACTERISTICS (Depending on fiber or cable construction)**

**ENVIRONMENTAL:** - Storage temperature -40[°C] to +85[°C]  
- Operating temperature -40[°C] to +70[°C]

DIMENSIONS: mm (inch) -



This information is given as an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged necessary.

4112\_9311

CREATION				
PEN:				
NAME: MANNEVY A.				
DATE: Feb. 15, 2007				
APPR.: MARIE A.				
Issue	Revisions	Name	Approved	

**RADIALL®**  
101, rue P. Hoffmann  
93116 ROSNY / BOIS  
France  
Tel (33) 01 49 35 35 35  
Fax (33) 01 48 54 63 63

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Fibre Optic Connectors](#) category:*

*Click to view products by [Radiall](#) manufacturer:*

Other Similar products are found below :

[0004700001](#) [6100-R](#) [6313](#) [F709034706](#) [F709722200](#) [F709730000](#) [F718183204](#) [F727403500](#) [F727752800](#) [8119](#) [9440F20-27S-190](#) [944-120-6001](#) [9441F10SL-3S](#) [9444W28-21S](#) [9444W36-10S](#) [9446F10SL-4S](#) [9446W20-16S](#) [953-101-5310-P](#) [954-101-57202B](#) [A0270169](#) [12-9122](#) [12-5702](#) [AX101713](#) [AX102420](#) [AX103923](#) [AX104024](#) [AX104193](#) [AX104230](#) [AX104498](#) [AX104562](#) [AX105203-B25](#) [AX105205-S1](#) [EHSC2M](#) [181-011-126](#) [181-011-S](#) [181-057-126](#) [HRFC-R2\(40\)](#) [NKSOPBUY](#) [20500002116](#) [2064996-1](#) [20800001065](#) [2170](#) [9132](#) [2612](#) [2620](#) [9291](#) [9440F16-10S](#) [9440F20-18S](#) [9442W14S-10P](#) [9446F16-10S-190](#)