

FEMALE-FEMALE BULKHEAD ADAPTOR


INSULATED BULKHEAD


R141.723.161

Series: BNC-COM









BRASS

BRASS

BRASS

POLYAMID 6/6 (NYLON)

All dimensions are in mm.


BODY

GASKET OTHERS PARTS

COMPONENTS

CENTER CONTACT

OUTER CONTACT INSULATOR



PLATINGS (μm)
NICKEL 2 GOLD 0.2 OVER NICKEL 2
NICKEL 2

Issue: 0417 B

In the effort to improve our products, we reserve the right to make changes judged to be necessary.

MATERIALS



FEMALE-FEMALE BULKHEAD ADAPTOR

INSULATED BULKHEAD

R141.723.161

Series: BNC-COM

PACKAGING

Standard	Unit	Other
100	'W' option	Contact us

SPECIFICATION

ELECTRICAL CHARACTERISTICS

 $\begin{array}{ccc} \text{Impedance} & & \textbf{50} \;\; \Omega \\ \text{Frequency} & & \textbf{0-1.5} \;\; \text{GHz} \end{array}$

VSWR $NA + 0.000 \times F(GHz) Maxi$ Insertion loss $NA \sqrt{F(GHz)} dB Maxi$

Insertion loss $NA \ \sqrt{F(GHz)} \ dB \ Maxi$ RF leakage - ($NA \ -F(GHz)) \ dB \ Maxi$

 $\begin{array}{ccc} \mbox{Voltage rating} & & \mbox{500 Veff Maxi} \\ \mbox{Dielectric withstanding voltage} & \mbox{1000 Veff mini} \\ \mbox{Insulation resistance} & \mbox{5000 } \mbox{M} \mbox{\Omega} \mbox{mini} \end{array}$

ENVIRONMENTAL

Operating temperature -35/+70 ° C
Hermetic seal NA Atm.cm3/s

Panel leakage NA

OTHERS CHARACTERISTICS

Assembly instruction NA

Others:

MECHANICAL CHARACTERISTICS

Center contact retention

Axial force – Mating end
Axial force – Opposite end
Torque

15 N mini
NA N.cm mini

Recommended torque

Mating NA N.cm Panel nut 370 N.cm

Mating life 100 Cycles mini

Weight **10.420** g

Issue: 0417 B

In the effort to improve our products, we reserve the right to make changes judged to be



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Radiall manufacturer:

Other Similar products are found below:

5916-1103-603 5919-1503-000 651A505 82-5552 9030-9523-502 PN2C A0407000 R114703000W R125771001 R141710000W

R141723161 R141730000 R143730700 R143770000 R161703000W R161753000W R161791530W R201705000 R222705200

R222M40010W R223703180 R316754000 R405006000 R443162000 AD78TL HRM-513S 1996352-2 2157155-1 252169-75 AD158

2101130-1 252186 R114704000W R114720000W R125705001 R125705701 R125771000 R125771001W R127704001 R127.870.001

R127872001 R141717000 R142710000 R142723000 R143703000 R143704000 R143705700 R161715000W R161771000W R176754000