

TECHNICAL DATA SHEET 2/2			
MALE PROTECTION CAP			R185.812.007
WITH CORD		Series : 7-16	
PACKAGINGStandardUnit20-Contact us		SPECIFICATION	
ELECTRICAL CHARACTERISTICS		<u>ENVIRONMENTAL</u>	
VSWR NA + 0,0000 Insertion loss NA RF leakage - (NA	Ω GHz x F(GHz) Maxi √F(GHz) dB Maxi - F(GHz)) dB Maxi Veff Maxi	Operating temper Hermetic seal Panel leakage	rature -55/+155 ° C NA Atm.cm3/s NA
Dielectric withstanding voltageNAVeff miniInsulation resistanceNAMΩ mini		OTHER CHARACTERISTICS	
MECHANICAL CHARACTE	RISTICS	Assembly instruc Others : Interface leakage I	
Axial force – Opposite end NA	N mini N mini N.cm mini		
0	N.cm N.cm		
Mating life 500 Weight 0,0000	Cycles mini g		
Jame 4 1128 - A			
Issue : 1138 A In the effort to improve our products, we reserve the right to make changes judged to be necessary.			

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Connector Accessories category:

Click to view products by Radiall manufacturer:

Other Similar products are found below :

 89674-0712
 F702RX24
 FERRULE-174
 R141802000
 R141805000
 R161862000
 R161862000W
 R280752000
 R280907000

 R694261906
 RFI21-13
 RFI75-13-D2
 RFI75-4-D2
 AX102906
 AX102907
 18097-0013
 HP-375
 HP-500
 2098-0294-00
 2098-3251-94
 KA

 81-05
 89674-0805
 F1
 FERRULE-223
 202102-11
 213337-1
 220222-2
 24092671A
 24092678A
 R280468000
 R280510000
 R282862060

 RFI155-1
 RFI25-12-D3
 RFI25-5
 RFI75-12-D2
 RFI75-2-D2
 RFI75-4-D3
 RFI77-6
 360HS001M2508M6
 4-1532137-4
 5-21085

 0
 105274-1000
 111062-0490
 112122-SOD-LUG
 112-NUT-KNURL
 IPP-2014
 R280490020