

# TECHNICAL DATA SHEET

### COAXIAL TERMINAISON TNC MALE

4 GHZ 1W Z50

**R404.121.000** Series : **TERMINATION** 

#### **ELECTRICAL CHARACTERISTICS**

Frequency (GHz)	DC - 1	1 - 4
V.S.W.R (≤)	1.08	1.20


	GHz	DC - 4	Operating Frequency Range
	Ω	50	Impedance
	W	100	Peak power at 25°C (1µs, 1%)
Cooled)	W (Free Air Cooled)	1	Average power at 25°C
on Cooled)	W (Conduction Cool		
_	,	1	Average power at 25°C

# MECHANICAL CHARACTERISTICS

Connectors	TNC	MALE	MIL C39012
Weight	16,0500 g		

#### **ENVIRONMENTAL CHARACTERISTICS**

Operating temperature range	-55 /+125 °C
Storage temperature range	-55 /+125 °C



# **SPECIFICATION**

# **OTHER CHARACTERISTICS**



# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Terminators category:

Click to view products by Radiall manufacturer:

Other Similar products are found below :

M390303-02N M39030/3-04S M39030/3-09S M39030/3-11N TNG1-9-78-D3 TNA2-50 TNG1-6-78 TNH1-1-50 R404280000 TNGFL1-1-78 R4042N5000 53S1RR-001N3 142275 56S1RR-001N4 65\_BNC-50-0-7/133\_NE 71S1RR-001N4 02S17R-001D3 R404240120 R404260000 HT-10-2 FL LCX 50-OHM-RSMA M39030/3-04N TNA1-6-50 131-3801-811 TNA1-1-50 65\_N-50-0-51/113\_NE 65\_BNC-50-0-2/133\_NE 65\_N-50-0-1/133\_NE 65002\_N-50-1/122\_NE 65\_MMCX-50-0-31/111\_OE 18K15R-0.5E3 2702702 TRM-2161-M0-35M-02 53S17R-001N3 1100.19.0001 18S24H-40ML5 TRM-2053-M0-NNN-02 R404759000 M39030/6-02N TRM-2080-M0-NNN-07 TRM-2053-MC-NNN-02 M39030/3-03S SF8012-6009 6701.01.A 65\_MCX-50-0-4/111\_NE 65\_716-50-0-2/003\_-E 65\_SMB-50-0-1/111\_NE M39030/3-12N 82-5722-RFX 8018-6174