

TECHNICAL DATA SHEET

SMA ATTENUATOR

8 DB 26.5 GHZ 2W

R413.808.121 Series : ATTENUATOR

ELECTRICAL CHARACTERISTICS

Frequency (GHz)	DC - 4	4 - 8	8 - 12.4	12.4 - 18	18 - 26.5
V.S.W.R (≤)	1.15	1.20	1.25	1.35	1.5
Deviation(±dB)	0.60	0.60	0.60	0.60	0.60

Operating Frequency Range	DC - 26.5	GHz
Impedance	50	Ω
Nominal Attenuation	8	dB
Peak power at 25°C (1µs, 1%)	100	W
Average power at 25°C	2	W (Free Air Cooled)
		W (Conduction Cooled)


MECHANICAL CHARACTERISTICS

Connectors	SMA	Male Female	MIL-C 39012
Weight	5,1470 g		

ENVIRONMENTAL CHARACTERISTICS

Operating temperature range	-55 /+125 °C
Storage temperature range	-55 /+125 °C

Power derating Versus temperature



SPECIFICATION

OTHER CHARACTERISTICS



2/2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Attenuators - Interconnects category:

Click to view products by Radiall manufacturer:

Other Similar products are found below :

 R411803119
 R413806115
 R413808000
 R413810115
 R413850115
 R414510000
 R414701000
 R415303000
 BNC-13
 R41180121

 R411801121
 R412412124
 R412450000
 R41380000
 R413805000
 R413830000
 R413840115
 R414730000
 R415420000
 R415703000

 R416010000
 R420003110
 R411801000
 R411815121
 R413305000
 R413801000
 R414520000
 R411808121
 R412500124
 R412414124

 R412501124
 HMC-C584
 R413802000
 R412400124
 R411700124
 R417310130
 R411801119
 R412419124
 R411703124
 R412401124

 R443131000
 R417130110
 R414700000
 R414505000
 R411802119
 R417720128
 R420706110
 R413811000
 R413803115
 R414501000