

# **SMA ATTENUATOR** 15 DB 4GHZ 2W

R413.815.115

Series : ATTENUATOR







SCALE 1:1

All dimensions are in mm.



COMPONENTS	MATERIALS	PLATING(µm)
BODY MALE CENTER CONTACT FEMALE CENTER CONTACT OUTER CONTACT INSULATOR GASKET SUBSTRATE RESISTOR OTHERS PARTS	STAINLESS STEEL BERYLLIUM COPPER BERYLLIUM COPPER  PTFE SILICONE RUBBER ALUMINA THIN FILM	GOLD 2.5 OVER NICKEL 1 GOLD 2.5 OVER NICKEL 1

Issue: 0838 A

In the effort to improve our products, we reserve the right to make changes judged to be



### SMA ATTENUATOR 15 DB 4GHZ 2W

**R413.815.115**Series: **ATTENUATOR** 

#### **ELECTRICAL CHARACTERISTICS**

Frequency (GHz)	DC - 4	
V.S.W.R (≤)	1.15	
Deviation(±dB)	0.6	

DC - 4	GHz
50	Ω
15	dB
100	W
2	W (Free Air Cooled)
	W (Conduction Cooled)
	50


### **MECHANICAL CHARACTERISTICS**

Connectors	SMA	Male Female	MIL-C 39012
Weight	5,1470 g		

### **ENVIRONMENTAL CHARACTERISTICS**

Operating temperature range	-55 /+125 °C
Storage temperature range	-55 /+125 °C

#### Power derating Versus temperature



# **SPECIFICATION**

### **OTHER CHARACTERISTICS**



## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Attenuators - Interconnects category:

Click to view products by Radiall manufacturer:

Other Similar products are found below:

```
R411803119 R413806115 R413808000 R413810115 R413850115 R414510000 R414701000 R415303000 BNC-13 R411800121
R411801121 R412412124 R412450000 R413800000 R413805000 R413830000 R413840115 R414730000 R415420000 R415703000
R416010000 R420003110 R411801000 R411815121 R413305000 R413801000 R414520000 R411808121 R412500124 R412414124
R412501124 HMC-C584 R413802000 R412400124 R411700124 R417310130 R411801119 R412419124 R411703124 R412401124
R443131000 R417130110 R414700000 R414505000 R411802119 R417720128 R420706110 R413811000 R413803115 R414501000
```