

## **SMA ATTENUATOR**

### 20 DB 18 GHZ 2W

**R413.820.000** Series : ATTENUATOR

#### **ELECTRICAL CHARACTERISTICS**

Frequency (GHz)	DC - 2	2 - 4	4 - 8	8 - 12.4	12.4 - 18
V.S.W.R (≤)	1.10	1.15	1.20	1.25	1.35
Deviation(±dB)	0.60	0.60	0.60	0.60	0.60


Operating Frequency Range	DC - 18	GHz
Impedance	50	Ω
Nominal Attenuation	20	dB
Peak power at 25°C (1µs, 1‰)	100	W
Average power at 25°C	2	W (Free Air Cooled)
		W (Conduction Cooled)

# **MECHANICAL CHARACTERISTICS**

Connectors	SMA	Male Female	MIL-C 39012
Weight	5,1470 g		

#### ENVIRONMENTAL CHARACTERISTICS

Operating temperature range	-55/+125 °C
Storage temperature range	°C



**SPECIFICATION** 

# **OTHER CHARACTERISTICS**

RADIALL

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Attenuators - Interconnects category:

Click to view products by Radiall manufacturer:

Other Similar products are found below :

 R411803119
 R413806115
 R413808000
 R413810115
 R413850115
 R414510000
 R414701000
 BNC-13
 R411800121
 R411801121

 R412412124
 R412450000
 R413800000
 R413805000
 R413830000
 R413840115
 R414730000
 R415420000
 R415703000
 R416010000

 R420003110
 R411801000
 R411815121
 R413305000
 R413801000
 R414520000
 R411808121
 R412500124
 R412414124
 R412501124

 HMC-C584
 R413802000
 R412400124
 R411700124
 R417310130
 R411801119
 R412419124
 R412401124
 R443131000

 R417130110
 R414700000
 R414505000
 R411802119
 R417720128
 R420706110
 R413803115
 R414501000
 R417903128