

# TECHNICAL DATA SHEET

2 W


DC- 8 GHz

**BNC** 

COAXIAL ATTENUATOR

issue 30.aug.95 Page 1/1


DRAWING



General tolerances: +/- 0.5 mm

#### R F CHARACTERISTICS

FREQUENCY RANGE : DC -8 GHz **IMPEDANCE** 50 Ohms ATTENUATION - NOMINAL 13 dB



TEMPERATURE SENSITIVITY

\* 10 dB \* °C

PEAK POWER at 25°C (1µs,1%.) : 100 W AVERAGE POWER at 25°C : 2 W


# MECHANICAL CHARACTERISTICS


**CONNECTORS** : BNC male/female per MIL-C 39012

WEIGHT : < 30 g

### **ENVIRONMENTAL CHARACTERISTICS**

(°C) : -55 OPERATING TEMPERATURE RANGE +125 STORAGE TEMPERATURE RANGE (℃) : -55 +125





#### RAD I ALL®

101. rue P. Hoffmann -Z.I Ouest-93116 ROSNY/BOIS Cedex-FRANCE Phone: 33(1)49353535 Fax :33(1)48546363 Twx RADIA 235220F

as

This information is given

an indication. In the continual goal to improve our products, we reserve the right to make any modifications judged

# **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Attenuators - Interconnects category:

Click to view products by Radiall manufacturer:

Other Similar products are found below:

```
R411803119 R413806115 R413808000 R413810115 R413850115 R414510000 R414701000 R415303000 BNC-13 R411800121
R411801121 R412412124 R412450000 R413800000 R413805000 R413830000 R413840115 R414730000 R415420000 R415703000
R416010000 R420003110 R411801000 R411815121 R413305000 R413801000 R414520000 R411808121 R412500124 R412414124
R412501124 HMC-C584 R413802000 R412400124 R411700124 R417310130 R411801119 R412419124 R411703124 R412401124
R443131000 R417130110 R414700000 R414505000 R411802119 R417720128 R420706110 R413811000 R413803115 R414501000
```