Technical Data Sheet



SPDT Ramses SMA 18GHz Latching 12Vdc TTL Diodes Pins Terminals

PAGE 1/2 ISSUE 06-02-18 SERIE : SPDT PART NUMBER : R570432100

RF CHARACTERISTICS

Frequency range : 0 - 18 GHz Impedance : 50 Ohms

Frequency (GHz)	DC - 3	3 - 8	8 - 12.4	12.4 - 18
VSWR max	1.10	1.20	1.20	1.40
Insertion loss max	0.15 dB	0.20 dB	0.25 dB	0.35 dB
Isolation min	80 dB	75 dB	65 dB	60 dB
Average power (*)	240 W	150 W	120 W	100 W

ELECTRICAL CHARACTERISTICS

Actuator : LATCHING
Nominal current ** : 210 mA

Actuator voltage (Vcc) : 12V (10.2 to 13V)

Terminals : solder pins (250°C max. / 30 sec.)
TTL inputs (E) - High level : 2.2 to 5.5 V / 800µA at 5.5 V

- Low level : 0 to 0.8 V / 20µA at 0.8 V

MECHANICAL CHARACTERISTICS

Connectors : SMA female per MIL-C 39012

Life : 10 million cycles

Switching Time*** : < 10 msConstruction : Splashproof
Weight : < 45 g

ENVIRONMENTAL CHARACTERISTICS

Operating temperature range : -40°C to +85°C Storage temperature range : -55°C to +85°C

(* Average power at 25°C per RF Path)

(** At 25° C ±10%)

(*** Nominal voltage; 25° C)



This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

Technical Data Sheet



SPDT Ramses SMA 18GHz Latching 12Vdc TTL Diodes Pins Terminals


PAGE **2/2** ISSUE 06-02-18 SERIE: SPDT PART NUMBER: **R570432100 DRAWING** [1.343] 34.10 [0.303 max.] 7.70 max. LABEL [0.138 min.] 3.50 min. [1.528 max.] 38.80 max. E2 E1 GND VCC [0.122] 4 x Ø 3.10 **RADIALL®** R570432100 0 - 18 GHz Un: 12V Lot : _ _ _ _ 0.441 $\begin{bmatrix} 0.134 \\ 3.40 \end{bmatrix}$ 11.20 2 C 1 0.880 22.35 1.319 33.50 1.500 38.10

General tolerances: ±0,5 mm [0,02 in]

0000 (3)

SCHEMATIC DIAGRAM

3



TTL input	RF Continuity	
E1=1 / E2=0	$C \leftrightarrow 1$	
E1=0 / E2=1	$C \leftrightarrow 2$	
E1=0 / E2=0	Memory	
E1=1 / E2=1	Forbidden	

This document contains proprietary information and such information shall not be disclosed to any third party for any purpose whatsoever or used for manufacturing purposes without prior written agreement from Radiall. The data defined in this document are given as an indication, in the effort to improve our products; we reserve the right to make any changes judged necessary.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Coaxial Switches category:

Click to view products by Radiall manufacturer:

Other Similar products are found below:

CR-53S10 R599311000 R599906000 R599910000 CCT-38S150-T CR-58S160 MS180LH3-HRMJ-040V300A R599312000 R512F73417
R514F73417 R595333210 R595F53225 R591363400 R595433410 R595333215 R595337220 R595343115 R595343125 R591362440
R593373148 R595343215 CCR-33K40 R595357325 CCS-18N480-TDS R591702640 R591763600 CR-33K10 R599313000 R516431100
R591722605 ARD15105 MS156LH1-HRMJ-088V300A R570412000 R570412100 R570413000 R570422100 R570423000 R570432000
R570433000 R570442000 R570442100 R570412030 R570432010 R570433100 R570443030 R570463100 R570442010
R570413030 R570452000