

● SHORT CIRCUIT U LINKS

The short circuit U link is a complementary component to the 20-way fixed connector and can be used to make shunts. It is fitted with a rear-mounted 2 mm dia. socket.

CHARACTERISTICS

- Current rating max : 7 A (at 20°C)
- Dielectric withstanding voltage : 2 000 V rms 50 Hz
- Operating voltage : 500 V rms 50 Hz
- Insulation resistance : $\geq 5\,000\text{ M}\Omega$
- Mechanical endurance : $> 10\,000$ matings
- Operating temperature : $-40^\circ\text{C} + 70^\circ\text{C}$

► Packaging : 100 pieces of the same part number.

Part number	Dimensions (12 mm between axes)
R 644 543 000 / Blue R 644 543 001 / Red R 644 543 002 / Green R 644 543 003 / Black R 644 543 004 / Yellow	

Part number	Dimensions (6 mm between axes)
R 644 543 020* / Blue R 644 543 021* / Red R 644 543 022* / Green R 644 543 023* / Black R 644 543 024* / Yellow	

* Made to order product, please consult Radiall for price and delivery

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Plugs & Test Jacks](#) category:

Click to view products by [Radiall](#) manufacturer:

Other Similar products are found below :

[01-2601-4-0210](#) [01-2601-4-0212](#) [01-2604-4-0212](#) [01-2604-5-0210](#) [01-2150-1-0312](#) [01-2350-1-02](#) [01-2352-1-02](#) [01-2368-1-02](#) [01-2604-4-0210](#) [01-2604-5-0212](#) [01-2606-4-0210](#) [01-2606-4-0212](#) [01-2606-5-0212](#) [M39024/10-01G](#) [M39024/10-17G](#) [M39024/11-09G](#) [M39024/11-42](#) [M39024/11-43](#) [M39024/12-08](#) [707-5311](#) [707-5402-01-19](#) [707-5410](#) [923739-40-I](#) [R644543000](#) [R948161000](#) [R999351000](#) [1408-4](#) [1499-101](#) [1533-1](#) [1659559](#) [1659567](#) [1663921](#) [1663939](#) [1696-102](#) [174-R825B-EX](#) [NYS508-BU](#) [NYS508-O](#) [211-101](#) [RS100GBL](#) [RS250GBL](#) [251-102](#) [25-2251-2-03](#) [25-2259-2-03](#) [923743-16-I](#) [923743-24-I](#) [923743-28-I](#) [2854-BLU](#) [2970-BLK](#) [30-443G](#) [1680](#)