

4 mm dia. STANDARD SERIES

PATCH CORDS

This series comprises :

- **BM/BM patch cords** moulded extension patch cords
- **BDM/BDM patch cords** moulded, stackable patch cords
- **PTM/BM patch cords** moulded, test probe patch cords
- **PTS/BM patch cords** moulded, test probe patch cords with security flange

The plug is soldered to the cable in order to assure an excellent electrical connection with very stable transfer resistance.

The unit is then moulded in pliable thermoplastic to form a very sturdy connector.

NOTE : Silicone cables are highly flexible and withstand contact with a hot soldering iron without damage.

CHARACTERISTICS

– Current rating max	1 mm ² cable	: 15 A (at 20°C)
	2 and 2.5 mm ² cable	: 30 A (at 20°C)
– Dielectric withstanding voltage		: 2 500 V
– Operating voltage		: 750 V rms 50 Hz
– Insulation resistance		: > 5 000 MΩ
– Contact resistance		: ≤ 0,5 mΩ
– Mechanical endurance		: > 10 000 matings
– Average insertion force		: 25 N
– Operating temperature		: – 40°C + 70°C

► **Packaging : 10 identical patch cords.**

● **BM/BM EXTENSION PATCH CORDS**

Cord length 1 : 10 cm 2 : 20 cm 4 : 50 cm 5 : 100 cm 6 : 150 cm 7 : 200 cm	Colour 0 : Black 1 : Red 2 : Green 3 : Blue 4 : Yellow	Type of cable 00 : PVC 1 mm ² 3,5 dia. 02 : PVC 2 mm ² 3,5 dia. 19 : Silicone 1 mm ² 2,9 dia. 29 : Silicone 2.5 mm ² 4 dia.
---	--	--

R 948 0xx 0xx



X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Test Leads](#) category:

Click to view products by [Radiall](#) manufacturer:

Other Similar products are found below :

[795-2384-10-25](#) [1301430020](#) [1510-24-105](#) [15308](#) [15408](#) [15302](#) [15409](#) [BU-1149-A-36-0](#) [BU-1481-E-12-0](#) [BU-1481-E-24-0](#) [1927617](#) [2450](#)
[2524-A-60](#) [LB1F-2R-RED](#) [LB1F-2R-YLW](#) [2500](#) [2524-A-48](#) [2977-J-48](#) [R948131000](#) [380200](#) [BU-1449-E-12-2](#) [BU-1480-E-24-0](#) [BU-1481-](#)
[E-12-2](#) [BU-1481-E-24-2](#) [LB1F-2R-BLK](#) [LB1F-2R-BLUE](#) [LB1F-2R-WHT](#) [6345](#) [6432](#) [6416](#) [EM3782-24-3#](#) [R948161002](#) [R948160002](#)
[R948170002](#) [R948171002](#) [R948163002](#) [973604100](#) [934160101](#) [934160100](#) [R948174000](#) [CT3269](#) [CT3258](#) [CT3158-100](#) [HSPL](#)
[8568/AWG16/200/RT](#) [HSPL 8568/AWG16/200/SW](#) [28.0119-10020](#) [28.0127-05025](#) [28.0127-20025](#) [49.0079-20021](#) [49.0079-20024](#)