

Standard contact blocks have one common contact chamber and one actuator plunger.



Contact blocks with "latching" contact function are used as switches. When combined with pushbuttons and mushroom actuators, the switching position is visible, releasing is effected by actuating again.


| Dimensions                                      |   |       |
|---|---|-------|
| Size not mounted                                | 22.2 x 22.2 x 34.4 mm   |       |
| Mounting depth (with actuator / indicator)      | 44.7 mm   |       |
| Mechanical design                               |   |       |
| Mounting  | snap on actuator  |       |
| Contact system                                  | bridge-contact self cleaning  |       |
| Contact materials                               | Au  |       |
| Contact arrangement                             | 1 NC + 1 NO   |       |
| Contact function                                | latching  |       |
| Lamp socket                                     | W 2 x 4.6d  |       |
| Terminals                                       | quick connector 2.8 x 0.8 mm  |       |
| Terminal marking                                | according to DIN 50013, NC: 11/12 resp. 21/22, NO: resp 23/24, lamp: X1 +, X2 - | 13/14 |
| Operating travel                                | 3 mm  |       |
| Robustness                                      | 100 N   |       |
| Mechanical characteristics                      |   |       |
| Robustness                                      | acc. to IEC 60947-5-5   |       |
| Electrical characteristics                      |   |       |
| Rated voltage min.                              | 0.02 V  |       |
| Rated voltage AC/DC max.                        | 35 V  |       |
| Rated current min.                              | 0.001 A   |       |
| Rated current max.                              | 0.25 A  |       |
| Operating life switching element (momentary)    | 2,000,000   |       |
| Contact resistance when new max.                | 50 mΩ   |       |
| Other specifications                            |   |       |
| Protection class                                | 11  |       |
| Shock resistance acc. to IEC 60068-2-27         | amplitude < 50g, 11ms, half sinusoidal  |       |
| Operation temperature min.                      | -25 °C  |       |
| Ambient temp. operating max. without lamp / LED | +70 °C  |       |
| Ambient temp. operating max. with lamp /LED     | +55 °C  |       |
|   |   |       |


Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.





| Storage temperature min.                        | -40 °C                                   |
|---|--|
| Storage temperature max.                        | +85 °C                                   |
| Color code                                      | white bottom                             |
| Environmental restistance                       | acc. to IEC 60068-2-14, -30, -33 and -78 |
| Mechanical operating life latching (operations) | 2,000,000                                |
| Resistance to vibrations acc. to IEC 60068-2-6  | 10 g at 20 500 Hz                        |
|   | yes                                      |
| ROHS compliant                                  | yes                                      |
| REACH compliant                                 | yes                                      |

with contact block / lamp socket










Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.





Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by RAFI manufacturer:

Other Similar products are found below :

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8512.2320 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 84-8511.6320 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment