RAFIX FS - Universal contact block, 1 NC + 1 NO, gold contacts 1.20.126.003/9000


Caution: Not suitable for emergency stop functions.




General information	
Lamp optional	SMT LED
Mechanical design	
Mounting	soldering in PCB
Contact system	bridge-contact self cleaning
Contact materials	Au
Contact arrangement	1 NC + 1 NO
NC contact forcibly actuated acc. to IEC	yes
Terminals	THT solder terminals with locating lug
Electrical characteristics	
Operating voltage AC / DC min.	<u>1 V</u>
Operating voltage AC / DC max.	35 V
Operating current AC / DC min.	1 mA
Operating current AC / DC max.	100 mA
Rated power max.	250 mW
Other specifications	
Operating life at 10 mA / 24 V DC	1,000,000
B10	1,300,000
Switching reliability at 24V / 5mA DC	<u>10 x 10⁻⁶</u>
Storage temperature min.	-40 °C
Ambient temp. operating min.	-40 °C
Ambient temp. operating max.	+85 °C
Storage temperature max.	+85
Color of plunger	red and green
Robustness	acc. to IEC 60947-5-5 (TÜV)
Shock resistance acc. to IEC 60068-2-27	15 g at 11 ms, amplitude half sinusoidal
Resistance to vibrations acc. to IEC 60068-2-6	5 g at 10 500 Hz
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Solderability / solder heat resistance	DIN EN 60068-2-20
Solder techniques	wave solder bath / manual soldering
Color of housing	grey
ROHS compliant	yes
REACH compliant	yes

Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by RAFI manufacturer:

Other Similar products are found below :

61-8770.17 M2SA-7010 704.905.2 704.915.5 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added GLZ336