

RAFIX FS - Universal contact block, 2 NC, gold contacts


1.20.126.004/9000


Caution: Not suitable for emergency stop functions.



Lamp optional SMT LED Mechanical design Mounting soldering in PCB Contact system bridge-contact self cleaning Contact arrangement 2 NC NC contact forcibly actuated acc. to IEC 60947-5-1 yes Terminals THT solder terminals with locating lug Electrical characteristics THT solder terminals with locating lug Operating voltage AC / DC min. 1 V Operating voltage AC / DC min. 1 mA Operating current AC / DC max. 35 V Operating current AC / DC max. 100 mA Rated power max. 250 mW Otter specifications Operating life at 10 mA / 24 V DC 1,000,000 B10 1,300,000 Switching reliability at 24V / 5mA DC 10 x 10-6 Ambient temp. operating max. +85 °C Ambient temp. operating min. +00 °C Storage temperature min. 40 °C Storage temperature max. +85 Color of plunger red Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 15 g at 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to	General information	
Mounting soldering in PCB Contact system bridge-contact self cleaning Contact materials Au Contact materials 2 NC NC contact forcibly actuated acc. to IEC 60947-5-1 yes Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. 1 V Operating voltage AC / DC max. 35 V Operating current AC / DC min. 1 mA Operating current AC / DC max. 100 mA Rated power max. 250 mW Other specifications Operating life at 10 mA / 24 V DC 1,000,000 B10 1,300,000 Switching reliability at 24V / 5mA DC 10 x 10 ⁻⁶ Ambient temp. operating min. 40 °C Storage temperature min. 40 °C Storage temperature max. +85 Color of plunger Resistance to vibrations acc. to IEC 60068-2-27 15 g at 11 ms, amplitude half sinusoidal Environmental resistance acc. to IEC 60068-2-20 Solder techniques wave solder bath / manual soldering Color of housing Golder techniques Color of housing Golder bath / manual soldering Golder both / manual soldering Golder bethive manual soldering Golder follows in process and solder in process and solde	Lamp optional	SMT LED
Mounting soldering in PCB Contact system bridge-contact self cleaning Contact materials Au Contact materials 2 NC NC contact forcibly actuated acc. to IEC 60947-5-1 yes Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. 1 V Operating voltage AC / DC max. 35 V Operating current AC / DC min. 1 mA Operating current AC / DC max. 100 mA Rated power max. 250 mW Other specifications Operating life at 10 mA / 24 V DC 1,000,000 B10 1,300,000 Switching reliability at 24V / 5mA DC 10 x 10 ⁻⁶ Ambient temp. operating min. 40 °C Storage temperature min. 40 °C Storage temperature max. +85 Color of plunger Resistance to vibrations acc. to IEC 60068-2-27 15 g at 11 ms, amplitude half sinusoidal Environmental resistance acc. to IEC 60068-2-20 Solder techniques wave solder bath / manual soldering Color of housing Golder techniques Color of housing Golder bath / manual soldering Golder both / manual soldering Golder bethive manual soldering Golder follows in process and solder in process and solde		
Contact system bridge-contact self cleaning Contact materials Au Contact arrangement 2 NC NC contact forcibly actuated acc. to IEC 60947-5-1 yes Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. 1 V Operating voltage AC / DC max. 35 V Operating current AC / DC min. 1 mA Operating current AC / DC max. 100 mA Rated power max. 250 mW Other specifications Operating life at 10 mA / 24 V DC 1,000,000 B10 1,300,000 Switching reliability at 24V / 5mA DC 10 x 10 ⁶ Ambient temp. operating min. 40 °C Storage temperature min. 40 °C Storage temperature max. +85 Color of plunger Resistance acc. to IEC 60068-2-27 15 g at 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to IEC 60068-2-6 Solder ability / solder heat resistance DIN EN 60068-2-20 Solder techniques wave solder bath / manual soldering Color of housing grey		
Contact materials Contact arrangement 2 NC NC contact forcibly actuated acc. to IEC 60947-5-1 Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. Operating voltage AC / DC max. Operating current AC / DC min. Operating current AC / DC max. Operating life at 10 mA Other specifications Operating life at 10 mA / 24 V DC J,000,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. 40 °C Storage temperature min. Storage temperature max. Color of plunger Robustness Color of plunger Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing Geretal Au THT solder terminals with locating lug TH ST	Mounting	
Contact arrangement NC contact forcibly actuated acc. to IEC 60947-5-1 Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. Operating voltage AC / DC min. Operating current AC / DC min. Operating current AC / DC min. Operating current AC / DC max. Operating current AC / DC max. Operating current AC / DC max. 100 mA Rated power max. Operating life at 10 mA / 24 V DC 1,000,000 B10 1,300,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. 40 °C Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 The gat 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing grey	Contact system	bridge-contact self cleaning
NC contact forcibly actuated acc. to IEC 60947-5-1 Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. Operating voltage AC / DC max. Operating current AC / DC min. Operating current AC / DC max. 100 mA Rated power max. Operating life at 10 mA / 24 V DC 1,000,000 B10 1,300,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. 485 °C Ambient temp. operating min. 40 °C Storage temperature min. Storage temperature max. Color of plunger Rebustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Is g at 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to IEC 60068-2-14, -30, -33 and -78 Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing Gere	Contact materials	Au
Terminals THT solder terminals with locating lug Electrical characteristics Operating voltage AC / DC min. Operating voltage AC / DC max. Operating current AC / DC min. Operating current AC / DC max. Too mA Rated power max. Operating life at 10 mA / 24 V DC B10 T1,000,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. As5 °C Ambient temp. operating min. 40 °C Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-66 Solder ability / solder heat resistance Color of housing Geovernmental restistance DIN EN 60068-2-20 Solder techniques Color of housing Geovernmental restistance DIN EN 60068-2-20 Solder bath / manual soldering Geovernmental restistance Color of housing Geovernmental restistance DIN EN 60068-2-20 Solder bath / manual soldering Geovernmental restistance Color of housing	Contact arrangement	2 NC
Electrical characteristics Operating voltage AC / DC min. Operating voltage AC / DC max. Operating current AC / DC min. Operating current AC / DC min. Operating current AC / DC max. 100 mA Rated power max. Operating life at 10 mA / 24 V DC B10 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. 40 °C Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solder ability / solder heat resistance May Color of housing DIN EN 60068-2-20 Solder techniques Wave solder bath / manual soldering Golor of housing Grey	NC contact forcibly actuated acc. to IEC 60947-5-1	yes
Operating voltage AC / DC min. Operating voltage AC / DC max. Operating current AC / DC min. Operating current AC / DC max. Rated power max. Other specifications Operating life at 10 mA / 24 V DC B10 Switching reliability at 24V / 5mA DC Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness Acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Solder ability / solder heat resistance Solder techniques Color of housing DIN EN 60068-2-20 Solder techniques Color of housing DIN EN 60068-2-14, -30, -33 and -78 Solder bath / manual soldering Grey	Terminals	THT solder terminals with locating lug
Operating voltage AC / DC max. Operating current AC / DC min. Operating current AC / DC max. Rated power max. Operating life at 10 mA / 24 V DC B10 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 B1 g at 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solder techniques Operating voltage AC / DC max. 1 mA 100 mA 1,000,000 1,000,000 1,000,000 10 x 10 ⁻⁶ Anounce 10 x 10 ⁻⁶ 40 °C Storage temperature max. 485 Color of plunger 240 °C 5 g at 11 ms, amplitude half sinusoidal Fervironmental restistance 3 cc. to IEC 60068-2-14, -30, -33 and -78 Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing Grey	Electrical characteristics	
Operating current AC / DC min. Operating current AC / DC max. Rated power max. Operating life at 10 mA / 24 V DC B10 Switching reliability at 24V / 5mA DC Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness Acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solder abelian in the max and a soldering Color of housing DIN EN 60068-2-20 Solder techniques Wave solder bath / manual soldering Golor of housing Toughton 100 mA 100 mA 250 mW 1,000,000 1,300,000 1,300,000 10 x 10°6 40°C 40°C 40°C 50 C 50	Operating voltage AC / DC min.	1 V
Operating current AC / DC max. Rated power max. 250 mW Other specifications Operating life at 10 mA / 24 V DC B10 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness Color of plunger Robustness Color of plunger Resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solder ability / solder heat resistance Color of housing DIN EN 60068-2-20 Solder techniques Golor of housing 1,000,000 1,000,000 1,300,000 1	Operating voltage AC / DC max.	35 V
Rated power max.Other specificationsOperating life at 10 mA / 24 V DC1,000,000B101,300,000Switching reliability at 24V / 5mA DC10 x 10-6Ambient temp. operating max.+85 °CAmbient temp. operating min40 °CStorage temperature min40 °CStorage temperature max.+85Color of plungerredRobustnessacc. to IEC 60947-5-5 (TÜV)Shock resistance acc. to IEC 60068-2-2715 g at 11 ms, amplitude half sinusoidalResistance to vibrations acc. to IEC 60068-2-65 g at 10 500 HzEnvironmental restistanceacc. to IEC 60068-2-14, -30, -33 and -78Solderability / solder heat resistanceDIN EN 60068-2-20Solder techniqueswave solder bath / manual solderingColor of housinggrey	Operating current AC / DC min.	1 mA
Other specifications Operating life at 10 mA / 24 V DC B10 1,300,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. +85 °C Ambient temp. operating min40 °C Storage temperature min40 °C Storage temperature max. +85 Color of plunger Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing grey	Operating current AC / DC max.	100 mA
Operating life at 10 mA / 24 V DC B10 1,300,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 Resistance acc. to IEC 60068-2-6 Environmental restistance Solder ability / solder heat resistance Color of housing Color of housing Color of housing 1,000,000 1,300,000 1,300,000 10 x 10 ⁻⁶ Ambient temp. operating max. +85 °C -40 °C Storage temperature max. +85 Color of plunger red Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-7 5 g at 11 ms, amplitude half sinusoidal Environmental restistance DIN EN 60068-2-14, -30, -33 and -78 Solder bath / manual soldering Golor of housing grey	Rated power max.	250 mW
Operating life at 10 mA / 24 V DC B10 1,300,000 Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 Resistance acc. to IEC 60068-2-6 Environmental restistance Solder ability / solder heat resistance Color of housing Color of housing Color of housing 1,000,000 1,300,000 1,300,000 10 x 10 ⁻⁶ Ambient temp. operating max. +85 °C -40 °C Storage temperature max. +85 Color of plunger red Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-7 5 g at 11 ms, amplitude half sinusoidal Environmental restistance DIN EN 60068-2-14, -30, -33 and -78 Solder bath / manual soldering Golor of housing grey		
Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60068-2-27 Shock resistance acc. to IEC 60068-2-6 Environmental restistance Solder ability / solder heat resistance Color of housing 1,300,000 10 x 10 ⁻⁶ +85 °C -40 °C -40 °C -40 °C -40 °C 15 g at 11 ms, amplitude half sinusoidal 5 g at 11 ms, amplitude half sinusoidal Color of blunger Bolderability / solder heat resistance DIN EN 60068-2-14, -30, -33 and -78 Solder techniques Color of housing grey		
Switching reliability at 24V / 5mA DC Ambient temp. operating max. Ambient temp. operating min. -40 °C Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Environmental restistance Solderability / solder heat resistance Color of housing DIN EN 60068-2-20 wave solder bath / manual soldering Grey		
Ambient temp. operating max. Ambient temp. operating min. -40 °C Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance Color of housing -40 °C -40 °		 -
Ambient temp. operating min. Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance Color of housing Color of housing -40 °C -40 °C -40 °C -40 °C -40 °C -40 °C -85 -40 °C -40		
Storage temperature min. Storage temperature max. Color of plunger Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing -40 °C +85 red 3cc. to IEC 60947-5-5 (TÜV) 15 g at 11 ms, amplitude half sinusoidal 5 g at 10 500 Hz acc. to IEC 60068-2-14, -30, -33 and -78 DIN EN 60068-2-20 wave solder bath / manual soldering grey	Ambient temp. operating max.	
Storage temperature max. +85 Color of plunger red Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 15 g at 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to IEC 60068-2-6 5 g at 10 500 Hz Environmental restistance acc. to IEC 60068-2-14, -30, -33 and -78 Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques wave solder bath / manual soldering Color of housing grey	Ambient temp. operating min.	
Color of plunger Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing red acc. to IEC 60947-5-5 (TÜV) 15 g at 11 ms, amplitude half sinusoidal 5 g at 10 500 Hz acc. to IEC 60068-2-14, -30, -33 and -78 DIN EN 60068-2-14, -30, -33 and -78 DIN EN 60068-2-20 grey	Storage temperature min.	-40 °C
Robustness acc. to IEC 60947-5-5 (TÜV) Shock resistance acc. to IEC 60068-2-27 15 g at 11 ms, amplitude half sinusoidal Resistance to vibrations acc. to IEC 60068-2-6 5 g at 10 500 Hz Environmental restistance acc. to IEC 60068-2-14, -30, -33 and -78 Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques wave solder bath / manual soldering Color of housing grey	Storage temperature max.	+85
Shock resistance acc. to IEC 60068-2-27 Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing 25 g at 10 500 Hz acc. to IEC 60068-2-14, -30, -33 and -78 DIN EN 60068-2-20 wave solder bath / manual soldering grey	Color of plunger	red
Resistance to vibrations acc. to IEC 60068-2-6 Environmental restistance Solderability / solder heat resistance DIN EN 60068-2-10 Solder techniques Color of housing Solderability / solder heat resistance grey	Robustness	acc. to IEC 60947-5-5 (TÜV)
Environmental restistance acc. to IEC 60068-2-14, -30, -33 and -78 Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques wave solder bath / manual soldering Color of housing grey	Shock resistance acc. to IEC 60068-2-27	15 g at 11 ms, amplitude half sinusoidal
Solderability / solder heat resistance DIN EN 60068-2-20 Solder techniques Color of housing DIN EN 60068-2-20 grey	Resistance to vibrations acc. to IEC 60068-2-6	5 g at 10 500 Hz
Solder techniques wave solder bath / manual soldering Color of housing grey	Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Color of housing grey	Solderability / solder heat resistance	DIN EN 60068-2-20
	Solder techniques	wave solder bath / manual soldering
ROHS compliant yes	Color of housing	grey
· · · · · · · · · · · · · · · · · · ·	ROHS compliant	yes
REACH compliant yes	REACH compliant	yes









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by RAFI manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8512.2320 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added