

RAFIX 22 FS⁺ - Universal contact block, silver contacts, 1 NO


1.20.126.202/9000





General information	
Lamp optional	SMT LED
Mechanical design	
Mounting	soldering in PCB
Contact system	bridge-contact self cleaning
Contact materials	<u>Ag</u>
Contact arrangement	1 NO
NC contact forcibly actuated acc. to IEC 60947-5-1	yes
Terminals	THT solder terminals with locating lug
Electrical characteristics acc. to IEC 60947, A	C-15 DC-13
Rated insulation voltage AC / DC	250 V
Rated peak voltage	2500 V
Rated operating current I _E , AC15 B300	2300 V
realed operating current ie, ACTO BOOD	3 A / 120 V; 1.5 A / 240 V; I_{the} : 5 A
Rated operating current I _E , DC13 Q300	550 mA / 120 V; 270 mA / 240 V; I _{the} : 2.5 A
Max. fuse protection	microfuse 5 x 20 mm, 6.3 A, inert
Other specifications	
Operating life at 250V / 1A	1,000,000
B10 at 250V / 1A	1,300,000
Operating life at 250V / 2A	100,000
B10 at 250V / 2A	130,000
Operating life at 250V / 4A	30,000
B10 at 250V / 4A	40,000
Switching reliability at 24V / 5mA DC	10 x 10 ⁻⁶
Ambient temp. operating max.	+85 °C
Storage temperature min.	-40 °C
Ambient temp. operating min.	-40 °C
Storage temperature max.	+85 °C
Color of plunger	green
Robustness	acc. to IEC 60947-5-5 (TÜV)
Shock resistance acc. to IEC 60068-2-27	50 g at 11 ms, amplitude half sinusoidal
Resistance to vibrations acc. to IEC 60068-2-6	5 g at 10 500 Hz
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Solderability / solder heat resistance	DIN EN 60068-2-20



Solder techniques	wave solder bath / manual soldering
Hot wire ignition acc. to IEC 60695-2-1	yes
Color of housing	black
ROHS compliant	yes
REACH compliant	yes







X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by RAFI manufacturer:

Other Similar products are found below:

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8512.2320 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304

51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4

5.00.100.105/0000 84-8511.5320 A3CA-7121 84-8511.6320 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment