
RAFIX 22 FS⁺ - Contact block with quick-connect terminals, silver contacts 1.20.126.701/9000



.

| General information | | | | | |
|--|--|--|--|--|--|
| Lamp optional | LED-Clip | | | | |
| | | | | | |
| Mechanical design | | | | | |
| Mounting | snap on actuator | | | | |
| Contact system | bridge-contact self cleaning | | | | |
| Contact materials | Ag | | | | |
| Contact arrangement | <u>1 NC</u> | | | | |
| NC contact forcibly actuated acc. to IEC 60947-5-1 | yes | | | | |
| Terminals | quick connect terminals 2.8 x 0.8 mm | | | | |
| | | | | | |
| Electrical characteristics acc. to IEC 60947, AC | | | | | |
| Rated insulation voltage AC / DC | 250 V | | | | |
| Rated peak voltage | 2500 V | | | | |
| Rated operating current I _E , DC13 Q300 | 550 mA / 120 V; 270 mA / 240 V; I _{the} : 2.5 A | | | | |
| | | | | | |
| Other specifications | 4 000 000 | | | | |
| Operating life at 250V / 1A | 1,000,000 | | | | |
| Operating life at 250V / 2A | 100,000 | | | | |
| Operating life at 250V / 4A | <u>30,000</u> 10 x 10 ⁻⁶ | | | | |
| Switching reliability at 24V / 5mA DC | -40 °C | | | | |
| Storage temperature min. | -40 C +70 °C | | | | |
| Ambient temp. operating max. | | | | | |
| Ambient temp. operating min. Storage temperature max. | -25 C +80 °C | | | | |
| Color of plunger | red | | | | |
| Robustness | acc. to IEC 60947-5-5 (TÜV) | | | | |
| Shock resistance acc. to IEC 60068-2-27 | 15 g at 11 ms, amplitude half sinusoidal | | | | |
| Resistance to vibrations acc. to IEC 60068-2-27 | 5 g at 10 500 Hz | | | | |
| | | | | | |
| Environmental restistance | acc. to IEC 60068-2-14, -30, -33 and -78 | | | | |
| Hot wire ignition acc. to IEC 60695-2-1 | yes | | | | |
| Color of housing | black | | | | |
| ROHS compliant | yes | | | | |
| REACH compliant | yes | | | | |







| Schaltelement mit LED-Clip | | | Schaltelement "Plus 1" | | | |
|---------------------------------------|-------------|---|------------------------|---------|---------|---------|
| (Sicht von unten) | | | (Sicht von unten) | | | |
| Kontakt | takt akt | Kontakt A Kontakt Kontakt Kontakt B Kontakt | | | | |
| a a a a a a a a a a a a a a a a a a a | 1S | 1Ö | 25 | 2Ö | 1Ö + 1S | Plus 1 |
| 000000001002 | 1S | • | 1S | 1Ö | 1S | 1Ö |
| 00500luss0000000000 | 13 - 14 | | 13 - 14 | 11 - 12 | 13 - 14 | 11 - 12 |
| 000000001002 | - | 1Ŏ | 1S | 1Ö | 1Ö | 1Ö |
| 00500uss000000000000 | | 21 - 22 | 23 - 24 | 21 - 22 | 21 - 22 | 21 - 22 |
| *Cu | LED* | LED* | LED* | LED* | LED* | 1S |
| | X1 - X2 | X1 - X2 | X1 - X2 | X1 - X2 | X1 - X2 | 33 - 34 |

Technical data are approximate and intended solely for general orientation in the selection of a product. Subject to modifications and errors. Images and other graphics may only be similar. For more information, refer to www.rafi.de chapter Imprint / Data Protection.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Contact Blocks / Switch Kits category:

Click to view products by RAFI manufacturer:

Other Similar products are found below :

61-8770.17 M2SA-7010 704.905.2 704.915.5 84-8512.2320 A01RTC8 A02504 A02512 A3KJ-7010 BS001 190-17504-003 190-17505-001 190-17508-001 190-17509-002 190-17509-006 A02506 190-17501-001 190-17506-001 190-17509-003 190-17509-005 GLZ304 51401 BS010 BST-D HW-S01 XESP2021 61-8480.22 61-8650.17 704.908.1 704.908.5 704.915.3 HA-C2V S4 704.918.4 5.00.100.105/0000 84-8511.5320 A3CA-7121 704.902.1 A0310Y 51-971.F22 5.05.510.632/0000 190-17502-003 190-17507-002 190-17500-006 190-17510-001 1.20.119.002/0000 2MN6-1PA224 Kit05-Keylocks Kit14-Switch Assortment Kit25-Value Added