


RAFIX 30 FS $^{\scriptscriptstyle +}$ - Selector switch, latching, Rotating angle 1 x 90°, L shape


1.30.292.102/2200



General information	
Actuator	handle
Marking of handle	translucent white
Front ring	stainless steel
Form of collar	round
Dimensions	
Dimensions of collar	ø 34.5 mm
Overall height	17.43 mm
Mounting hole	30.3 mm
Key grid	min. 35 x 35 mm
Mechanical design	
Mounting	threaded ring + adapter
Contact function	latching
Illuminability	
Rotating angle	_ yes 1 x 90°, L shape
Torque for nut ring	1.2 Nm
Torque for flut fling	1.2 INIII
Mechanical characteristics	
Torque max.	1.5 Nm
Other specifications	
Ambient temp. operating min.	25 °C
Ambient temp. operating max.	+70 °C
Operating life (operations)	500,000 momentary / 300,000 latching cycle
Operating life (operations)	650,000 momentary / 400,000 latching cycle
Degree of protection from front side	IP65 (DIN EN 60529)
Storage temperature min.	_40 °C
Storage temperature max.	+80 °C
Environmental restistance	acc. to IEC 60068-2-14, -30, -33 and -78
Salt spray	IEC 600 68-2-11
ROHS compliant	yes
REACH compliant	yes









X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Switch Actuators category:

Click to view products by Rafi manufacturer:

Other Similar products are found below:

LW1B-A0L LW1B-M0 680-4000-00 704.012.618 704.096.0 704.411.018I 704.412.0 704.633.1 704.730.1 704.733.0 84-1221.7 862.8102

G6083 9PA24 A0107X A019307 ADC-418G 12MA7 ASDHHY-B HW1F-3G HW1M-L2222 HW4S-31L 200-.704-00 JS-10008 JS
10083 JS-10118 JS-10133 JS-10277 JS-10389 JS-150 JS-552 JS-555 JS-68 JS-6-B JS-91 JS-94 22-211.011 9001KXSDC 92-458.500

SAPT654133 2PA3 SW53AA2 302561 LW2L-A0 3E-10.4 468-10243-001 51-030.005 JM-13 JS-10120 JS-138-B