

**LED Bi-Pin T 1, red, 3 V****1.90.691.026/0000****Electrical characteristics of LED**

Max. current, $I_F$	10 mA
LED wavelength typ.	635
Forward voltage typ. $U_F$ at $I_F$	2
Light intensity	26-52

**Other specifications**

Socket	Bi-Pin T 1
Color	red
Ambient temp. operating min.	-20 °C
Ambient temp. operating max.	+60 °C
Storage temperature min.	-30 °C
Storage temperature max.	+80 °C
Operating life	100,000 h
ROHS compliant	yes
REACH compliant	yes

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Rafi manufacturer](#):*

Other Similar products are found below :

[1.15.108.481/0000](#) [5.05.510.935/0000](#) [5.00.070.074/0000](#) [1.15.114.936/0000](#) [1.20.126.202/0000](#) [1.30.279.021/0700](#) [5.46.001.127/0200](#)  
[1.74.510.011/2500](#) [1.10.119.967/0000](#) [1.69.508.113/1002](#) [1.30.270.021/2400](#) [1.30.276.601/0000](#) [1.10.011.001/0551](#) [5.00.888.506/1500](#)  
[1.02.157.201/1300](#) [3.13.026.001/0000](#) [1.30.285.221/0100](#) [1.30.270.021/2300](#) [1.66.003.081/1400](#) [1.30.241.001/2207](#) [5.76.204.114/0400](#)  
[5.73.110.000/0000](#) [1.30.295.222/0000](#) [1.30.285.101/0100](#) [1.30.275.221/0800](#) [1.30.273.602/0300](#) [1.30.242.026/2207](#) [1.30.073.601/2000](#)  
[1.30.070.121/1505](#) [1.20.123.035/0000](#) [1.10.010.001/0221](#) [3.13.026.531/0000](#) [1.10.099.201/0011](#) [5.70.090.016/1001](#) [5.70.090.011/1001](#)  
[5.70.090.015/1001](#) [1.20.126.303/9000](#) [5.05.511.747/1500](#) [1.69.507.117/1402](#) [1.90.692.001/0000](#) [1.01.102.001/0104](#) [3.14.002.052/0000](#)  
[1.30.275.321/0100](#) [5.05.511.476/2200](#) [1.30.299.021/0700](#) [1.15.108.632/0100](#) [1.65.111.051/0000](#) [5.00.100.105/0000](#) [5.00.070.078/0000](#)  
[1.30.142.114/0209](#)