

# Raspberry Pi 4 Computer Model B



Published in January 2021 by Raspberry Pi Trading Ltd.



### Overview



Raspberry Pi 4 Model B is the latest product in the popular Raspberry Pi range of computers. It offers ground-breaking increases in processor speed, multimedia performance, memory, and connectivity compared to the prior-generation Raspberry Pi 3 Model B+, while retaining backwards compatibility and similar power consumption. For the end user, Raspberry Pi 4 Model B provides desktop performance comparable to entry-level x86 PC systems.

This product's key features include a high-performance 64-bit quad-core processor, dual-display support at resolutions up to 4K via a pair of micro-HDMI ports, hardware video decode at up to 4Kp60, up to 8GB of RAM, dual-band 2.4/5.0 GHz wireless LAN, Bluetooth 5.0, Gigabit Ethernet, USB 3.0, and PoE capability (via a separate PoE HAT add-on).

The dual-band wireless LAN and Bluetooth have modular compliance certification, allowing the board to be designed into end products with significantly reduced compliance testing, improving both cost and time to market.

## Specification

Processor: Broadcom BCM2711, quad-core Cortex-A72 (ARM v8)

64-bit SoC @ 1.5GHz

Memory: 1GB, 2GB, 4GB or 8GB LPDDR4

(depending on model) with on-die ECC

Connectivity: 2.4 GHz and 5.0 GHz IEEE 802.11b/g/n/ac wireless

LAN, Bluetooth 5.0, BLE

Gigabit Ethernet 2 × USB 3.0 ports 2 × USB 2.0 ports.

GPIO: Standard 40-pin GPIO header

(fully backwards-compatible with previous boards)

Video & sound: 2 × micro HDMI ports (up to 4Kp60 supported)

2-lane MIPI DSI display port 2-lane MIPI CSI camera port

4-pole stereo audio and composite video port

Multimedia: H.265 (4Kp60 decode);

H.264 (1080p60 decode, 1080p30 encode);

OpenGL ES, 3.0 graphics

SD card support: Micro SD card slot for loading operating system

and data storage

**Input power:** 5V DC via USB-C connector (minimum 3A<sup>1</sup>)

5V DC via GPIO header (minimum 3A<sup>1</sup>) Power over Ethernet (PoE)-enabled

(requires separate PoE HAT)

**Environment:** Operating temperature 0–50°C

**Compliance:** For a full list of local and regional product approvals,

please visit


https://www.raspberrypi.org/documentation/

hardware/raspberrypi/conformity.md

**Production lifetime:** The Raspberry Pi 4 Model B will remain in production

until at least January 2026.

# Physical Specifications



#### **WARNINGS**


- This product should only be connected to an external power supply rated at 5V/3A DC or 5.1V/ 3A DC minimum<sup>1</sup>. Any external power supply used with the Raspberry Pi 4 Model B shall comply with relevant regulations and standards applicable in the country of intended use.
- This product should be operated in a well-ventilated environment and, if used inside a case, the case should not be covered.
- This product should be placed on a stable, flat, non-conductive surface in use and should not be contacted by conductive items.
- The connection of incompatible devices to the GPIO connection may affect compliance and result in damage to the unit and invalidate the warranty.
- All peripherals used with this product should comply with relevant standards for the country of use and be marked accordingly to ensure that safety and performance requirements are met. These articles include but are not limited to keyboards, monitors and mice when used in conjunction with the Raspberry Pi.
- Where peripherals are connected that do not include the cable or connector, the cable or connector
  must offer adequate insulation and operation in order that the relevant performance and safety
  requirements are met.

#### SAFETY INSTRUCTIONS

#### To avoid malfunction or damage to this product please observe the following:

- · Do not expose to water, moisture or place on a conductive surface whilst in operation.
- Do not expose it to heat from any source; Raspberry Pi 4 Model B is designed for reliable operation at normal ambient room temperatures.
- Take care whilst handling to avoid mechanical or electrical damage to the printed circuit board and connectors.
- Avoid handling the printed circuit board whilst it is powered and only handle by the edges to minimise the
  risk of electrostatic discharge damage.

<sup>&</sup>lt;sup>1</sup> A good quality 2.5A power supply can be used if downstream USB peripherals consume less than 500mA in total.









### **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Development Boards & Kits - ARM category:

Click to view products by Raspberry Pi manufacturer:

Other Similar products are found below:

CY4541 OM13090UL Raspberry Pi 4 Model B,8GB YR0K77210B000BE B-U585I-IOT02A NUCLEO-C031C6 NUCLEO-U5A5ZJ-Q
NUCLEO-WL55JC1 STM32MP135F-DK ZDSD-Pinboard 081ZYKFB LKS32MC034DOF6Q8-k LKS32MC077MBS8-K
LKS32MC038Y6P8B-K LKS32MC071DOC8T8-K LKS32MC074DOF8Q8-K LKS32MC071CBT8-K LKS32MC038Y6P8-k GD32L233KSTART RTK7F124FPC01000BJ XDS601 RP2040-Tiny M6G2C-256LI YT37 VC-02-Kit\_EN Hi-12FL-Kit PB-03F-Kit Ra-08-Kit Hi07SL-Kit Hi-07S-Kit Ai-WB2-12F-Kit PB-03-Kit Hi-12F-Kit AT-START-F437 AT-START-F407 E104-BT40-TB FT8132Q-3HALLFOC+EMF FU6832L-TGB-DEMO APM32F072VBT6 APM32F091VC MINI APM32F407IG-MINIBOARD APM32F003F6P6MINIBOARD APM32F051R8 MINI GD32EPRTV-START GD32FPRT-START GD32407H-START-1 GD32E503V-EVAL GD32E507RSTART GD32E103R-START GD32403V-START-1