


FEATURES

- High sensitive type
- Dielectric strength AC 5,000V
- 8mm insulation distance
- Using at home appliances, microwave ovens, air conditioners, audio equipment, temperature controller



UL FILE NO. : E131959
CUL FILE NO. : E131959

ORDERING INFORMATION

LM P 1H A — 12 D

1 2 3 4 5 6

- | | |
|---|---|
| 1. Type | 4.Contact Arrangement |
| 2. STYLE:
P: PC COVER | Nil: Form C
A: Form A
B: Form B |
| 3.Cont. Type
1:1 Polt
2:2 Polt
1H:16A(1 Post 2 Feet) | 5.Coil Nominal Voltage
6.Coil Nominal Voltage Type
D:DC |


COIL DATA (at 25°C)

DC 0.53 W				
Coil Nominal Voltage(VDC)	Resistance Tol±10%(Ohms)	Nominal Current (mA)	Maximum Pick Up Voltage (V)	Minimum Drop Out Voltage (V)
5	47	106.4	4	0.5
12	270	44.4	9.6	1.2
24	1,100	21.8	19.2	2.4

CONTACT RATING

LM1	TYPE (1PDT)	Resistive (Cos.θ = 1)	AC 250V / DC 30V	12A
LM2	TYPE (2PDT)	Resistive (Cos.θ = 1)	AC 250V / DC 30V	8A
LM1H	TYPE (1PDT)	Resistive (Cos.θ = 1)	AC 250V / DC 30V	16A

DIMENSIONS(±0.2mm)



GENERAL DATA

Insulation Resistance	1,000 MΩ Min. (DC 500V)
Dielectric Strength	1,000 VAC, 50/60Hz between contact.
	5,000 VAC, 50/60Hz between all elements.
Contact Material	Ag Alloy.
Contact Resistance	100 milliohms max. (initial value)
Shock Resistance	Malfunction: 10G(11ms) ; Destructive: 100G(6ms)
Vibration Resistance	Malfunction: 10 to 55 Hz. at Double Amplitude of 1.5 mm
	Destructive: 10 to 55 Hz. at Double Amplitude of 1.5 mm
Operation Time	15 ms max.
Release Time	10 ms max.
Temperature Range	- 40°C ~ + 80°C
Expected Life	With operation rate 30/min.
	Mechanical - 10,000,000 operations min.
	Electrical - 100,000 operations min. at rated load.
Weight	Standard Type : 17 grams,

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [General Purpose Relays](#) category:

Click to view products by [Rayex](#) manufacturer:

Other Similar products are found below :

[APF30318](#) [JVN1AF-4.5V-F](#) [PCN-105D3MHZ](#) [5JO-10000S-SIL](#) [5JO-1000CD-SIL](#) [5JO-400CD-SIL](#) [LY2S-AC220/240](#) [LYQ20DC12](#)
[6031007G](#) [6131406HQ](#) [6-1393099-3](#) [6-1393099-8](#) [6-1393122-4](#) [6-1393123-2](#) [6-1393767-1](#) [6-1393843-7](#) [6-1415012-1](#) [6-1419102-2](#) [6-](#)
[1423698-4](#) [6-1608051-6](#) [6-1608067-0](#) [6-1616170-6](#) [6-1616248-2](#) [6-1616282-3](#) [6-1616348-2](#) [6-1616350-1](#) [6-1616350-8](#) [6-1616358-7](#) [6-](#)
[1616359-9](#) [6-1616360-9](#) [6-1616931-6](#) [6-1617039-1](#) [6-1617052-1](#) [6-1617090-2](#) [6-1617090-5](#) [6-1617347-5](#) [6-1617353-3](#) [6-1617801-8](#) [6-](#)
[1617802-2](#) [6-1618107-9](#) [6-1618248-4](#) [M83536/1-027M](#) [CX-4014](#) [MAHC-5494](#) [MAVCD-5419-6](#) [703XCX-120A](#) [7-1393100-5](#) [7-1393111-7](#)
[7-1393144-5](#) [7-1393767-8](#)