



General Specification
 Current Rating:1.6A DC /Contact, 20mA DC for LED signals
 Voltage Rating:125V AC /Contact, 2.0 volts DC for LED signals
 Operating Environment
 Standard Derating:
 Industrial Temperature: -40°C~+85°C
 Humidity: 20%~70%
 Contact Resistance: $\le 30m\Omega$
 Insulation Resistance: >5000 $\Omega</math>
 Dielectric Strength:500V AC/(0.02S)/Min
 Mating And Unmating Force:3~20N
 Durability:750 Cycles Min$

Material Specification
 Housing :Thermoplastic, UL94V-0.
 Contact :Alloy Copper
 Shield :Alloy Copper

Please refer to the customer drawing when customer has specified

网络插座外形图



温州瑞川电子有限公司
 WEN ZHOU RUI CHUAN ELECTRONIC CO., LTD.

序号	名称	材料	数量	镀层/颜色	备注
5	LED灯	树脂/PS	2	NT/AG	
4	后盖	PA46	1	BLACK	
3	插针	PHOSPHOR BRONZE	8	FU"	
2	外壳	H62	1	NT	
1	塑座	PA46	1	BLACK	

绘图: 吴鹏飞
 审核: 陈德
 日期: 2022.7.21

品名: RCH-59-01(带灯带弹后脚3.05)
 料号: 5901-8G(Y07410AB30 (R000247))
 型号: RJ45
 图号:

版本	变更履历	变更单号	绘制日期	审核日期	日期
A/0	新出版发行				
1	2	3	该图面	温州瑞川电子	有限公司

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:

Click to view products by [RCH manufacturer](#):

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102277](#) [AX102651](#) [AX102660](#) [AX104024](#)
[203475](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [SM99S01VBNN04G7](#) [17-103540](#) [191587](#) [PDI-](#)
[68-RV](#) [PHP-8P8C-S-5](#)