



**General Specification**  
 Current Rating: 1.6A DC /Contact, 20mA DC for LED signals  
 Voltage Rating: 125V AC /Contact, 2.0 volts DC for LED signals  
 Operating Environment  
 Standard Temperature: -20°C~+70°C  
 Industrial Temperature: -40°C~+85°C  
 Humidity: 20~70%  
 Contact Resistance:  $\leq 30m\Omega$   
 Insulation Resistance:  $\geq 500M\Omega$   
 Dielectric Strength: 500V AC / (50HZ) /Min  
 Mating And Unmating Force: 3~20N  
 Durability: 750 Cycles Min

**Material Specification**  
 Housing : Thermo-plastic, UL94V-0.  
 Contact : Alloy Copper  
 Shield : Alloy Copper

Please refer to the customer drawing when customer has specified

网络插座外形图

PCB LAYOUT  
RECOMMENDED

序号	名称	材料	数量	镀层/颜色	备注
4	插针	PHOSPHOR BRONZE	16	RU <sup>+</sup>	
3	屏蔽	H62	1	NI	
2	后盖	PBT	2	YELLOW	
1	塑座	PBT	1	YELLOW	



**温州瑞川电子有限公司**  
 WEN ZHOU RUI CHUAN ELECTRONIC CO., LTD.

一般公差		品名	
30~	±0.20	料号:	RQH-56-21-12(全塑 黄座) 10P8C
~10	±0.20	型号:	562112-80000010PY26 (RC02614)
~10	±0.15	图号:	RJ45
角度:	±2°	单位:mm	比例: 1:1
页面:	1 of 1	版本:	规格: A4

图例	日期	审核	日期	变更单号	变更履历	版本
网络插座外形图					新出版发行	A/0
					变更履历	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:*

*Click to view products by [RCH manufacturer](#):*

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)  
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)  
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)  
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102277](#) [AX102651](#) [AX102660](#) [AX104024](#)  
[203475](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [SM99S01VBNN04G7](#) [17-103540](#) [191587](#) [PDI-68-RV](#) [PHP-8P8C-S-5](#)