



PCB LAYOUT
(TOP VIEW)

General Specification
 Current Rating: 1.5A DC /Contact, 20A DC for LED signals
 Voltage Rating: 125V AC /Contact, 2.0 volts DC for LED signals
 Operating Environment:
 Standard Temperature: -20°C~+70°C
 Industrial Temperature: -40°C~+65°C
 Humidity: 20~70%
 Contact Resistance: ≤30mΩ
 Insulation Resistance: ≥500MΩ
 Dielectric Strength: 1500V AC/(50Hz)/Min
 Heating and Unheating Forces: 3~20N
 Durability: 750 Cycles Min

Material Specification
 Housing: Thermoplastic, UL94-V-0
 Contact: Alloy Copper
 Shield: Alloy Copper

Please refer to the customer drawing when customer has specified

网络插座外形图



温州瑞川电子有限公司
 WEN ZHOU RUI CHUAN ELECTRONIC CO., LTD.

序号	名称	材料	数量	镀层/颜色	备注
2	插针	PHOSPHOR BRONZE	32	RU ³	
1	塑座	PA46	1	BLACK	

绘图: 吴素飞
 审核: 陈清海
 日期: 20221203

品名: RCH-5366-14 全塑
 料号: 536614-80000010AB22 WR44194

审核: 陈清海
 日期: 20221203

型号: RJ45
 图号: 比例: 1:1 纸张: A4

日期: 20221203

版本: 1 of 1

日期: 20221203

单位: mm

变更单号	变更履历	日期	变更原因
	新出版发行		
	变更履历		

该图面供温州瑞川电子有限公司内部使用, 不得私自复印

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Modular Connectors](#) / [Ethernet Connectors](#) category:

Click to view products by [RCH](#) manufacturer:

Other Similar products are found below :

[8949-H88/06BLKA/SN](#) [74441-0010/BKN](#) [PHP-6P6C-5](#) [GAX-3-66](#) [GDCX-PN-66](#) [GLX-A-44](#) [GLX-N-1010M-BLK](#) [GLX-S-88M-BLK](#)
[GMX-SMT4-N-88](#) [GSGX-N-2-88](#) [GSGX-N-4-88](#) [GSX-NS2-88-3.05](#) [GSX-NS-88-3.68](#) [PT-108A-8C-UL](#) [PTS-J531-8CS-50UL](#) [A-2014-0-4](#)
[GWLX-S9-88-YG](#) [DC-1021-8-WH-6](#) [1300530003](#) [1324640-4](#) [132764-001](#) [1413235](#) [MPS88RX-5000](#) [E5288-S000K3-L](#) [155302-001](#)
[AX101050](#) [AX101063](#) [AX101065](#) [AX101072](#) [AX101307](#) [AX101315](#) [AX101318](#) [AX102271](#) [AX102277](#) [AX102651](#) [AX102660](#) [AX104024](#)
[203475](#) [PC4D0018P](#) [KIT38082NI](#) [8949-B88/6](#) [2-6609208-5](#) [30-8956](#) [30-8964-100](#) [SM85](#) [SM99S01VBNN04G7](#) [17-103540](#) [191587](#) [PDI-68-RV](#) [PHP-8P8C-S-5](#)