

General Description

The HXR5004A Transimpedance Limiting Amplifier array is a member of IDT's family of Optical Receiver Transmitter Array (ORTA) products targeted at the parallel optical links market. Together with a PIN detector array or discrete detectors, high-capacity, high-availability optical links can be designed for telecom and datacom applications.

The 3.3V SiGe device integrates the transimpedance pre-amplifier, the limiting post-amplifier and a versatile CML output stage for four optical channels.

Applications

- IEEE 802.3ba Ethernet transceivers
- InfiniBand QDR & FDR active cables
- · Proprietary multi-channel optical modules

Device Diagram

Features

- 20 μApp receiver sensitivity for 10⁻¹² BER at 10.3 Gbps. Better than 1.5 mApp overload
- 66 mW per channel power consumption with low power setting
- Adjustable output swing size and preemphasis mode and signal detect threshold
- Independent RSSI
- Optimized for isolated and common cathode photo-detector arrays from multiple vendors
- Control lines accessible on both sides of chip
- QSFP MSA compliance

Ordering Information

Part	Temp Range	Pin-Package
HXR5004A-DNT	0°C to +85°C	Bare Die
		2.05mm x 1.67mm
HXR5004A-DNT-F8	0°C to +85°C	Bare Die on Tape
		2.05mm x 1.67mm

For price, delivery schedules, and to place orders, please contact IDT: www.IDT.com/go/sales




Figure 1: Device diagram





Corporate Headquarters

6024 Silver Creek Valley Road San Jose, CA 95138 www.IDT.com

Sales

1-800-345-7015 or 408-284-8200 Fax: 408-284-2775 www.IDT.com/go/sales

Tech Support

www.IDT.com/go/support

DISCLAIMER Integrated Device Technology, Inc. (IDT) and its affiliated companies (herein referred to as "IDT") reserve the right to modify the products and/or specifications described herein at any time, without notice, at IDT's sole discretion. Performance specifications and operating parameters of the described products are determined in an independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of IDT's products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of IDT or any third parties.

IDT's products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of an IDT product can be reasonably expected to significantly affect the health or safety of users. Anyone using an IDT product in such a manner does so at their own risk, absent an express, written agreement by IDT.

Integrated Device Technology, IDT and the IDT logo are trademarks or registered trademarks of IDT and its subsidiaries in the United States and other countries. Other trademarks used herein are the property of IDT or their respective third party owners. For datasheet type definitions and a glossary of common terms, visit www.idt.com/go/glossary. All contents of this document are copyright of Integrated Device Technology, Inc. All rights reserved.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Transimpedance Amplifiers category:

Click to view products by Renesas manufacturer:

Other Similar products are found below:

HMC7590-SX AD8015ARZ AD8015ARZ-REEL7 LTC6560HUD#PBF LTC6560IUD#PBF LTC6561HUF#PBF LTC6561HUF#WPBF LTC6560HUD#WPBF MAX40658ETA+T MAX3806GTC+ MAX40659ETA+ MAX40661ATB/VY+ MAX3665EUA+

OPA380AIDGKTG4 OPA1S2384IDRCR OPA1S2385IDRCR OPA2380AIDGKT OPA2381AIDGKT OPA2381AIDRBT OPA380AIDG4

OPA858IDSGR OPA858IDSGT MAX3654ETE MAX3806GTC+T MAX40658ETA+ ACF2101BU IVC102U/2K5 OPA856IDSGR