

## Description

The XT devices are ultra-low phase noise quartz-based PLL oscillators supporting a large range of frequencies and output interface types.

The XT devices can be programmed to generate an output frequency from 15MHz to 2100MHz with a resolution as low as 1Hz accuracy. The configurability of this family of devices provides fast delivery times for both sample and large production orders.

Parts may be factory programmed for fixed frequency applications, or may be field configured using the I2C interface.

## Features

- Output types: LVDS, LVPECL, CML
  - Frequency range: 15MHz to 2100MHz
- Output type: HCSSL
  - Frequency range: 15MHz to 725MHz
- Supply voltage options: 1.8V, 2.5V, 3.3V
- Phase jitter (12kHz to 20MHz): 135 fs typical
- Package options:
  - 3.2 × 2.5 × 0.85 mm
- Operating temperature and stability:
  - -40°C to +85°C, ±3ppm
- Frequency stability for life:
  - -40°C to +85°C, ±13ppm

## Pin Assignments

Figure 1. 3.2 × 2.5 mm Package – Top View





Table 1. Pin Descriptions

| Pin # | Pin Name         | Description   |
|-------|------------------|---|
| 1     | OE               | Output Enable (0 = output disabled, pulled high internally) |
| 2     | NC               | No connect  |
| 3     | GND              | Connect to ground   |
| 4     | OUT0             | Output  |
| 5     | OUT0b            | Complementary output  |
| 6     | V <sub>DD</sub>  | Supply voltage  |
| 7     | SDA <sup>1</sup> | Serial data   |
| 8     | SCL <sup>1</sup> | Serial clock  |

<sup>1</sup> Pins 7 and 8 are no connect for non-I2C applications.

See [Ordering Information](#) for more details.

# Ordering Information



## Contents

|                                      |    |
|--------------------------------------|----|
| Description .....                    | 1  |
| Features .....                       | 1  |
| Pin Assignments .....                | 1  |
| Ordering Information .....           | 2  |
| Absolute Maximum Ratings .....       | 4  |
| ESD Compliance .....                 | 4  |
| Mechanical Testing .....             | 4  |
| Solder Reflow Profile .....          | 4  |
| DC Electrical Characteristics .....  | 5  |
| AC Electrical Characteristics .....  | 8  |
| Output Phase Noise .....             | 11 |
| Output Waveforms .....               | 12 |
| 3.3V LVPECL Output Termination ..... | 13 |
| 2.5V LVPECL Output Termination ..... | 13 |
| 1.8V LVPECL Output Termination ..... | 13 |
| LVDS Output Termination .....        | 14 |
| HCSL Output Termination .....        | 15 |
| CML Output Termination .....         | 15 |
| Package Outline Drawings .....       | 16 |
| Marking Diagram .....                | 16 |
| Revision History .....               | 16 |

## Absolute Maximum Ratings

Stresses above the ratings listed below can cause permanent damage to the device. These ratings, which are standard values for Renesas commercially rated parts, are stress ratings only. Functional operation of the device at these or any other conditions above those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods can affect product reliability. Electrical parameters are guaranteed only over the recommended operating temperature range. Thermal characteristics, in actual applications, should be assessed case by case to guarantee junction temperature does not exceed 125°C.

**Table 2. Absolute Maximum Ratings**

| Item                              | Rating         |             |
|-----------------------------------|----------------|-------------|
| V <sub>DD</sub>                   | -0.5V to +3.8V |             |
| OE                                | -0.5V to +3.8V |             |
| Storage Temperature               | -55°C to 125°C |             |
| Maximum Junction Temperature      | 125°C          |             |
| Theta J <sub>A</sub> <sup>1</sup> | LNG8           | 131.47 °C/W |
| Theta J <sub>B</sub> <sup>1</sup> |                | 92.89 °C/W  |

<sup>1</sup> Thermal characteristics are based on simulation in standard condition.

## ESD Compliance

**Table 3. ESD Compliance**


|                        |       |
|------------------------|-------|
| Human Body Model (HBM) | 2000V |
|------------------------|-------|

## Mechanical Testing

**Table 4. Mechanical Testing**

| Parameter                       | Test Method  |
|---------------------------------|--|
| Mechanical Shock                | Half-sine wave with 0.3ms 3000G. X, Y, Z each direction 1 time.  |
| Mechanical Vibration            | Frequency: 10 to 55MHz amplitude: 1.5mm.<br>Frequency: 55–2000Hz peak value: 20G.<br>Duration time: 4H for each X, Y, Z axis; total 12hours. |
| High Temp Operating Life (HTOL) | 1000 hours at 125°C (under power).   |
| MSL Level 3                     | J-STD-020E, Moisture/Reflow Sensitivity Classification for Nonhermetic Surface Mount Devices, December 2014.                                 |

## Solder Reflow Profile



## DC Electrical Characteristics

**Table 5. 3.3V IDD DC Electrical Characteristics**

$V_{DD} = 3.3V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ , typical at 156.25MHz.

| Symbol   | Parameter           | Output Type | Conditions          | Minimum | Typical | Maximum | Units |
|----------|---------------------|-------------|---------------------|---------|---------|---------|-------|
| $I_{DD}$ | Current Consumption | LVDS        | 15MHz to 400MHz.    | —       | 59      | 67      | mA    |
|          |                     |             | 400MHz to 2.1GHz.   | —       | —       | 85      |       |
|          |                     | LVPECL      | 15MHz to 212.5MHz.  | —       | 84      | 94      |       |
|          |                     |             | 212.5MHz to 400MHz. | —       | —       | 110     |       |
|          |                     |             | 212.5MHz to 2.1GHz. | —       | —       | 110     |       |
|          |                     | HCSL        | 15MHz to 400MHz.    | —       | —       | 95      |       |
|          |                     |             | 400MHz to 725MHz.   | —       | 74      | 83      |       |
|          |                     | CML         | 15MHz to 2.1GHz.    | —       | 54      | 61      |       |

**Table 6. 2.5V IDD DC Electrical Characteristics**

$V_{DD} = 2.5V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ , typical at 156.25MHz.

| Symbol   | Parameter           | Output Type | Conditions           | Minimum | Typical | Maximum | Units |
|----------|---------------------|-------------|----------------------|---------|---------|---------|-------|
| $I_{DD}$ | Current Consumption | LVDS        | 15MHz to 400MHz.     | —       | 59      | 66      | mA    |
|          |                     |             | 400MHz to 2.1GHz.    | —       | —       | 85      |       |
|          |                     | LVPECL      | 15MHz to 156.25MHz.  | —       | 84      | 94      |       |
|          |                     |             | 156.25MHz to 400MHz. | —       | —       | 110     |       |
|          |                     |             | 400MHz to 2.1GHz.    | —       | —       | 110     |       |
|          |                     | HCSL        | 15MHz to 400MHz.     | —       | —       | 95      |       |
|          |                     |             | 400MHz to 725MHz.    | —       | 74      | 82      |       |
|          |                     | CML         | 15MHz to 2.1GHz.     | —       | 54      | 61      |       |

**Table 7. 1.8V DD DC Electrical Characteristics**

$V_{DD} = 1.8V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ , typical at 156.25MHz.

| Symbol   | Parameter           | Output Type | Conditions        | Minimum | Typical | Maximum | Units |
|----------|---------------------|-------------|-------------------|---------|---------|---------|-------|
| $I_{DD}$ | Current Consumption | LVDS        | 15MHz to 400MHz.  | —       | 59      | 66      | mA    |
|          |                     |             | 400MHz to 2.1GHz. | —       | —       | 85      |       |
|          |                     | LVPECL      | 15MHz to 250MHz.  | —       | 84      | 93      |       |
|          |                     |             | 250MHz to 2.1GHz. | —       | —       | 110     |       |
|          |                     | HCSL        | 15MHz to 400MHz.  | —       | —       | 95      |       |
|          |                     |             | 400MHz to 725MHz. | —       | 74      | 81      |       |
|          |                     | CML         | 15MHz to 2.1GHz.  | —       | 54      | 61      |       |

**Table 8. LVCMOS DC Electrical Characteristics**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ .

| Symbol   | Parameter                        | Conditions                            | Minimum             | Typical | Maximum             | Units |
|----------|----------------------------------|---------------------------------------|---------------------|---------|---------------------|-------|
| $V_{IH}$ | Input High Voltage (OE pin only) | $V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ . | $0.7 \times V_{DD}$ | —       | $V_{DD} + 0.3$      | V     |
| $V_{IL}$ | Input Low Voltage (OE pin only)  | $V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ . | $GND - 0.3$         | —       | $0.3 \times V_{DD}$ | V     |

**Table 9. LVDS DC Electrical Characteristics**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ .

| Symbol   | Parameter                   | Conditions                            | Minimum | Typical | Maximum | Units |
|----------|-----------------------------|---------------------------------------|---------|---------|---------|-------|
| $V_{OD}$ | Differential Output Voltage | $V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ . | 0.30    | 0.44    | 0.60    | V     |
| $V_{OS}$ | Output Offset Voltage       | $V_{DD} = 1.8V \pm 5\%$               | 0.75    | 0.88    | 1.01    |       |
|          |                             | $V_{DD} = 2.5V \pm 5\%$               | 1.08    | 1.25    | 1.41    |       |
|          |                             | $V_{DD} = 3.3V \pm 5\%$               | 1.11    | 1.26    | 1.41    |       |

**Table 10. LVPECL DC Electrical Characteristics**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ .

| Symbol   | Parameter           | Conditions                | Minimum | Typical | Maximum | Units |
|----------|---------------------|---------------------------|---------|---------|---------|-------|
| $V_{OH}$ | Output High Voltage | $V_{DD} = 1.8V \pm 5\%$ . | 0.83    | 0.96    | 1.11    | V     |
|          |                     | $V_{DD} = 2.5V \pm 5\%$ . | 1.52    | 1.69    | 1.87    |       |
|          |                     | $V_{DD} = 3.3V \pm 5\%$ . | 2.28    | 2.49    | 2.72    |       |
| $V_{OL}$ | Output Low Voltage  | $V_{DD} = 1.8V \pm 5\%$ . | 0.19    | 0.30    | 0.42    |       |
|          |                     | $V_{DD} = 2.5V \pm 5\%$ . | 0.92    | 1.04    | 1.17    |       |
|          |                     | $V_{DD} = 3.3V \pm 5\%$ . | 1.68    | 1.84    | 2.01    |       |

**Table 11. HCSL DC Electrical Characteristics**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ .

| Symbol   | Parameter           | Conditions                | Minimum | Typical | Maximum | Units |
|----------|---------------------|---------------------------|---------|---------|---------|-------|
| $V_{OH}$ | Output High Voltage | $V_{DD} = 1.8V \pm 5\%$ . | 0.67    | 0.81    | 0.95    | V     |
|          |                     | $V_{DD} = 2.5V \pm 5\%$ . | 0.74    | 0.88    | 1.03    |       |
|          |                     | $V_{DD} = 3.3V \pm 5\%$ . | 0.78    | 0.92    | 1.07    |       |
| $V_{OL}$ | Output Low Voltage  | —                         | -0.06   | 0.07    | 0.20    |       |

**Table 12. CML DC Electrical Characteristics**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ .

| Symbol   | Parameter           | Conditions                | Minimum | Typical | Maximum | Units |
|----------|---------------------|---------------------------|---------|---------|---------|-------|
| $V_{OH}$ | Output High Voltage | $V_{DD} = 1.8V \pm 5\%$ . | 1.61    | 1.76    | 1.91    | V     |
|          |                     | $V_{DD} = 2.5V \pm 5\%$ . | 2.33    | 2.46    | 2.59    |       |
|          |                     | $V_{DD} = 3.3V \pm 5\%$ . | 3.09    | 3.26    | 3.43    |       |
| $V_{OL}$ | Output Low Voltage  | $V_{DD} = 1.8V \pm 5\%$ . | 1.24    | 1.37    | 1.52    |       |
|          |                     | $V_{DD} = 2.5V \pm 5\%$ . | 1.95    | 2.06    | 2.17    |       |
|          |                     | $V_{DD} = 3.3V \pm 5\%$ . | 2.70    | 2.85    | 3.00    |       |

**Table 13. DC Electrical Characteristics – Leakage Current**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ , typical at 156.25MHz.

| Symbol   | Parameter          | Conditions                | Input | Minimum | Typical | Maximum | Units   |
|----------|--------------------|---------------------------|-------|---------|---------|---------|---------|
| $I_{IH}$ | Input Leakage High | $V_{DD} = 3.3V \pm 5\%$ . | OE    | -5      | 0.8     | 5       | $\mu A$ |
|          |                    |                           | SCLK  | -5      | 1.4     | 5       |         |
|          |                    |                           | SDATA | -5      | 1.4     | 5       |         |
| $I_{IL}$ | Input Leakage Low  | $V_{DD} = 3.3V \pm 5\%$ . | OE    | -20     | -17.4   | -14     | $\mu A$ |
|          |                    |                           | SCLK  | -37     | -33.5   | -30     |         |
|          |                    |                           | SDATA | -20     | -17     | -14     |         |
| $I_{IH}$ | Input Leakage High | $V_{DD} = 1.8V \pm 5\%$ . | OE    | -5      | 0.8     | 5       | $\mu A$ |
|          |                    |                           | SCLK  | -5      | 1.4     | 5       |         |
|          |                    |                           | SDATA | -5      | 1.4     | 5       |         |
| $I_{IL}$ | Input Leakage Low  | $V_{DD} = 1.8V \pm 5\%$ . | OE    | -11.5   | -9.5    | -7.5    | $\mu A$ |
|          |                    |                           | SCLK  | -20.8   | -18.3   | -15.7   |         |
|          |                    |                           | SDATA | -11.5   | -9.3    | -7.5    |         |

## AC Electrical Characteristics

Note for all AC Electrical Characteristics tables:

1. Installation should include a 0.01μF bypass capacitor placed between V<sub>DD</sub> and GND to minimize power supply line noise.

**Table 14. 3.3V AC Electrical Characteristics**

V<sub>DD</sub> = 3.3V ± 5%, T<sub>A</sub> = -40°C to +85°C.

| Symbol          | Parameter                  | Test Condition   |                         | Minimum | Typical | Maximum | Units |
|-----------------|----------------------------|--|-------------------------|---------|---------|---------|-------|
| F               | Output Frequency Range     | LVDS, LVPECL, CML.   |                         | 15      | —       | 2100    | MHz   |
|                 |                            | HCSL.  |                         | 15      | —       | 725     |       |
|                 | Frequency Stability        | Temperature = -40°C to +85°C.  |                         | —       | —       | ±3      | PPM   |
|                 | Frequency Tolerance (25°C) | T <sub>A</sub> = 25°C.   |                         | —       | —       | ±2      |       |
|                 | Aging (1 year)             | T <sub>A</sub> = 25°C.   |                         | —       | —       | ±1      |       |
|                 | Aging (10 years)           | T <sub>A</sub> = 25°C.   |                         | —       | —       | ±7      |       |
|                 | Output Load                | LVDS.  | Differential.           | —       | 100     | —       | Ω     |
|                 |                            | LVPECL.  | Thevenin equivalent.    | —       | 50      | —       |       |
|                 |                            | HCSL.  | To GND.                 | —       | 50      | —       |       |
| T <sub>ST</sub> | Start-up Time              | Output valid time after V <sub>DD</sub> meets minimum specified level. |                         | —       | 5       | —       | ms    |
| t <sub>R</sub>  | Output Rise Time           | LVDS.  | 20% – 80%,<br>156.25MHz | —       | 299     | 400     | ps    |
|                 |                            | LVPECL.  |                         | —       | 287     | 400     |       |
|                 |                            | HCSL.  |                         | —       | 306     | 400     |       |
|                 |                            | CML  |                         | —       | 301     | 400     |       |
| t <sub>F</sub>  | Output Fall Time           | LVDS.  | 80% – 20%,<br>156.25MHz | —       | 279     | 400     | ps    |
|                 |                            | LVPECL.  |                         | —       | 274     | 400     |       |
|                 |                            | HCSL.  |                         | —       | 284     | 400     |       |
|                 |                            | CML  |                         | —       | 279     | 400     |       |
| O <sub>DC</sub> | Output Clock Duty Cycle    | LVDS.  | 156.25MHz               | 45      | —       | 55      | %     |
|                 |                            | LVPECL.  | 156.25MHz               | 45      | —       | 55      |       |
|                 |                            | HCSL.  | 156.25MHz               | 45      | —       | 55      |       |
|                 |                            | CML  | 156.25MHz               | 45      | —       | 55      |       |
| T <sub>OE</sub> | Output Enable/Disable Time | —  | —                       | —       | 1       | —       | ms    |



**Table 15. 2.5V AC Electrical Characteristics**

$V_{DD} = 2.5V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ .

| Symbol   | Parameter                  | Test Condition  |                         | Minimum | Typical | Maximum | Units    |
|----------|----------------------------|---|-------------------------|---------|---------|---------|----------|
| F        | Output Frequency Range     | LVDS, LVPECL, CML.  |                         | 15      | —       | 2100    | MHz      |
|          |                            | HCSL.   |                         | 15      | —       | 725     |          |
|          | Frequency Stability        | Temperature = $-40^\circ C$ to $+85^\circ C$ .                  |                         | —       | —       | $\pm 3$ | ppm      |
|          | Frequency Tolerance (25°C) | $T_A = 25^\circ C$ .  |                         | —       | —       | $\pm 2$ |          |
|          | Aging (1 year)             | $T_A = 25^\circ C$ .  |                         | —       | —       | $\pm 1$ |          |
|          | Aging (10 years)           | $T_A = 25^\circ C$ .  |                         | —       | —       | $\pm 7$ |          |
|          | Output Load                | LVDS.   | Differential.           | —       | 100     | —       | $\Omega$ |
|          |                            | LVPECL.   | Thevenin equivalent.    | —       | 50      | —       |          |
|          |                            | HCSL.   | To GND.                 | —       | 50      | —       |          |
| $T_{ST}$ | Start-up Time              | Output valid time after $V_{DD}$ meets minimum specified level. |                         | —       | 5       | —       | ms       |
| $t_R$    | Output Rise Time           | LVDS.   | 20% – 80%,<br>156.25MHz | —       | 303     | 400     | ps       |
|          |                            | LVPECL.   |                         | —       | 292     | 400     |          |
|          |                            | HCSL.   |                         | —       | 310     | 400     |          |
|          |                            | CML   |                         | —       | 304     | 400     |          |
| $t_F$    | Output Fall Time           | LVDS.   | 80% – 20%,<br>156.25MHz | —       | 282     | 400     | ps       |
|          |                            | LVPECL.   |                         | —       | 278     | 400     |          |
|          |                            | HCSL.   |                         | —       | 288     | 400     |          |
|          |                            | CML   |                         | —       | 281     | 400     |          |
| $O_{DC}$ | Output Clock Duty Cycle    | LVDS.   | 156.25MHz               | 45      | —       | 55      | %        |
|          |                            | LVPECL.   | 156.25MHz               | 45      | —       | 55      |          |
|          |                            | HCSL.   | 156.25MHz               | 45      | —       | 55      |          |
|          |                            | CML   | 156.25MHz               | 45      | —       | 55      |          |
| $T_{OE}$ | Output Enable/Disable Time | —   | —                       | —       | 1       | —       | ms       |

**Table 16. 1.8V AC Electrical Characteristics**

$V_{DD} = 1.8V \pm 5\%$ ,  $T_A = -40^\circ C$  to  $+85^\circ C$ .

| Symbol   | Parameter                  | Test Condition  |                        | Minimum | Typical | Maximum | Units    |
|----------|----------------------------|---|------------------------|---------|---------|---------|----------|
| F        | Output Frequency Range     | LVDS, LVPECL, CML.  |                        | 15      | —       | 2100    | MHz      |
|          |                            | HCSL.   |                        | 15      | —       | 725     |          |
|          | Frequency Stability        | Temperature = $-40^\circ C$ to $+85^\circ C$ .                  |                        | —       | —       | $\pm 3$ | PPM      |
|          | Frequency Tolerance (25°C) | $T_A = 25^\circ C$ .  |                        | —       | —       | $\pm 2$ |          |
|          | Aging (1 year)             | $T_A = 25^\circ C$ .  |                        | —       | —       | $\pm 1$ |          |
|          | Aging (10 years)           | $T_A = 25^\circ C$ .  |                        | —       | —       | $\pm 7$ |          |
|          | Output Load                | LVDS.   | Differential.          | —       | 100     | —       | $\Omega$ |
|          |                            | LVPECL.   | Thevenin equivalent.   | —       | 50      | —       |          |
|          |                            | HCSL.   | To GND.                | —       | 50      | —       |          |
| $T_{ST}$ | Start-up Time              | Output valid time after $V_{DD}$ meets minimum specified level. |                        | —       | 5       | —       | ms       |
| $t_R$    | Output Rise Time           | LVDS.   | 20% – 80%,<br>312.5MHz | —       | 300     | 450     | ps       |
|          |                            | LVPECL.   |                        | —       | 260     | 450     |          |
|          |                            | HCSL.   |                        | —       | 260     | 450     |          |
|          |                            | CML   |                        | —       | 270     | 450     |          |
| $t_F$    | Output Fall Time           | LVDS.   | 80% – 20%,<br>312.5MHz | —       | 280     | 450     | ps       |
|          |                            | LVPECL.   |                        | —       | 250     | 450     |          |
|          |                            | HCSL.   |                        | —       | 250     | 450     |          |
|          |                            | CML   |                        | —       | 270     | 450     |          |
| $O_{DC}$ | Output Clock Duty Cycle    | LVDS.   | 312.5MHz               | 45      | —       | 55      | %        |
|          |                            | LVPECL.   | 312.5MHz               | 45      | —       | 55      |          |
|          |                            | HCSL.   | 312.5MHz               | 45      | —       | 55      |          |
|          |                            | CML   | 312.5MHz               | 45      | —       | 55      |          |
| $T_{OE}$ | Output Enable/Disable Time | —   | —                      | —       | 1       | —       | ms       |


**Table 17. Phase Jitter Characteristics**

$V_{DD} = 1.8V, 2.5V, 3.3V \pm 5\%$ ,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$ .

| Symbol       | Parameter                    | Conditions  | Typical (LVPECL) | Typical (LVDS) | Typical (CML) | Typical (HSCL) | Units |
|--------------|------------------------------|-------------|------------------|----------------|---------------|----------------|-------|
| $f_{JITTER}$ | Phase Jitter (12kHz – 20MHz) | 312.50MHz   | 124              | 159            | 131           | 126            | fsec  |
|              |                              | 625.00MHz   | 130              | 132            | 133           | 131            | fsec  |
|              |                              | 644.53MHz   | 134              | 137            | 133           | 130            | fsec  |
|              |                              | 779.215MHz  | 140              | 140            | 139           | —              | fsec  |
|              |                              | 818.991MHz  | 143              | 144            | 140           | —              | fsec  |
|              |                              | 822.128MHz  | 164              | 167            | 164           | —              | fsec  |
|              |                              | 840.759MHz  | 146              | 152            | 151           | —              | fsec  |
|              |                              | 1588.430MHz | 147              | 144            | 143           | —              | fsec  |
|              |                              | 1681.518MHz | 156              | 153            | 151           | —              | fsec  |
|              |                              | 1644.256MHz | 157              | 154            | 155           | —              | fsec  |
|              |                              | 1637.982MHz | 147              | 148            | 148           | —              | fsec  |


## Output Phase Noise

**Figure 2. 625MHz LVDS Output**



# Output Waveforms


**Figure 3. LVDS/LVPECL/HCSL/CML Output Waveforms**



### 3.3V LVPECL Output Termination

Figure 4 shows an example of termination for 3.3V LVPECL driver.


**Figure 4. 3.3V LVPECL Driver Termination Example**



### 2.5V LVPECL Output Termination

Figure 5 shows an example of termination for 2.5V LVPECL driver.


**Figure 5. 2.5V LVPECL Driver Termination Example**



### 1.8V LVPECL Output Termination

Figure 6 shows an example of termination for 1.8V LVPECL driver.

**Figure 6. 1.8V LVPECL Driver Termination Example**




## LVDS Output Termination


For a general LVDS interface, the recommended value for the termination impedance ( $Z_T$ ) is between  $90\Omega$  and  $132\Omega$ . The actual value should be selected to match the differential impedance ( $Z_0$ ) of your transmission line. A typical point-to-point LVDS design uses a  $100\Omega$  parallel resistor at the receiver and a  $100\Omega$  differential transmission-line environment. In order to avoid any transmission-line reflection issues, the components should be surface mounted and must be placed as close to the receiver as possible. Renesas offers a full line of LVDS compliant devices with two types of output structures: current source and voltage source.

The standard termination schematic as shown in Figure 7 can be used with either type of output structure. Figure 8, which can also be used with both output types, is an optional termination with center tap capacitance to help filter common mode noise. The capacitor value should be approximately  $50\text{pF}$ . If using a non-standard termination, it is recommended to contact Renesas and confirm if the output structure is current source or voltage source type. In addition, since these outputs are LVDS compatible, the input receiver's amplitude and common-mode input range should be verified for compatibility with the output.

**Figure 7. Standard LVDS Termination**




**Figure 8. Optional LVDS Termination**




## HCSL Output Termination

Figure 9 is the recommended source termination for applications where the driver and receiver will be on a separate PCBs. This termination is the standard for PCI Express™ and HCSL output types. All traces should be 50Ω impedance single-ended or 100Ω differential. Figure 10 is the recommended termination for applications where a point-to-point connection can be used. A point-to-point connection contains both the driver and the receiver on the same PCB. With a matched termination at the receiver, transmission-line reflections will be minimized. In addition, a series resistor (Rs) at the driver offers flexibility and can help dampen unwanted reflections. The optional resistor can range from 0Ω to 33Ω. All traces should be 50Ω impedance single-ended or 100Ω differential.

**Figure 9. Recommended Source Termination (where the driver and receiver will be on separate PCBs)**




**Figure 10. Recommended Termination (where a point-to-point connection can be used)**



## CML Output Termination

Figure 11 shows an example of the termination for a CML driver. In this example, the transmission line characteristic impedance is 50Ω. The R1 and R2 50Ω matched load terminations are pulled up to VDDO. The matched loads are located close to the receiver.

**Figure 11. CML Driver Termination Example**




## Package Outline Drawings

The [package outline drawings](#) are located at the end of this document and are accessible from the Renesas website. The package information is the most current data available and is subject to change without revision of this document.

## Marking Diagram

**Figure 12. Marking Configuration for the 3.2 × 2.5 mm (LNG8) Package (example based on XTL312625.000000I)**




- Line 1 denotes the truncated part number as follows:
  - “D” = a combination of the 3rd digit (output type, e.g. “L”) and the 5th digit (voltage supply, e.g. “3”), in accordance with the mapping key as follows:
    - C1 = A, C2 = B, C3 = C, **L1 = D**, L2 = E, L3 = F, N1 = G, N2 = H, N3 = J, P1 = K, P2 = L, P3 = M
  - “xxxxxx” = the first three digits to the left of the decimal point and the last three digits to the left of the decimal point as shown in the above example. This number will vary depending upon the frequency value selected in the orderable part number. (e.g. 625000).
- Line 2 indicates the following:
  - “YWW” denotes the last digit of the year and week when the part was assembled.
  - “\*\*” denotes the sequential lot number.
  - “\$” denotes the mark location.


## Revision History

| Revision Date | Description of Change |
|---------------|-----------------------|
| April 8, 2021 | Initial release.      |






TOP VIEW




SIDE VIEW



BOTTOM VIEW

NOTES:

1. DIMENSIONING AND TOLERANCING CONFORM TO ASME Y14.5-2009
2. ALL DIMENSIONS ARE IN MILLIMETERS



RECOMMENDED LAND PATTERN DIMENSION

NOTES:

1. ALL DIMENSIONS ARE IN MM. ANGLES IN DEGREES
2. TOP DOWN VIEW. AS VIEWED ON PCB
3. LAND PATTERN RECOMMENDATION PER IPC-7351B GENERIC REQUIREMENT FOR SURFACE MOUNT DESIGN AND LAND PATTERN
4. NSMD PATTERN ASSUMED

| Package Revision History |         |                        |
|--------------------------|---------|------------------------|
| Date Created             | Rev No. | Description            |
| Nov. 12, 2019            | 00      | Initial Release        |
| Jun. 21, 2021            | 01      | Update to Renesas Logo |

## IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES (“RENESAS”) PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers skilled in the art designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only for development of an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising out of your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Rev.1.0 Mar 2020)

### Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,  
Koto-ku, Tokyo 135-0061, Japan  
[www.renesas.com](http://www.renesas.com)

### Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit:  
[www.renesas.com/contact/](http://www.renesas.com/contact/)

### Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Standard Clock Oscillators](#) category:*

*Click to view products by [Renesas](#) manufacturer:*

Other Similar products are found below :

[601252](#) [F335-25](#) [F535L-33.333](#) [F535L-50](#) [NBXHBA019LN1TAG](#) [SiT1602BI-22-33E-50.000000E](#) [SIT8918AA-11-33S-50.000000G](#)  
[SM4420TEV-40.0M-T1K](#) [F335-24](#) [F335-40](#) [F535L-10](#) [F535L-12](#) [F535L-24](#) [F535L-27](#) [PE7744DW-100.0M](#) [ASF1-3.686MHZ-N-K-S](#) [ASV-](#)  
[4.000MHZ-LCS-T](#) [XLH735025.000JU4I8](#) [XLP725125.000JU6I8](#) [XO57CTECNA3M6864](#) [601251](#) [SiT8503AI-18-33E-0.200000X](#)  
[SIT8918AA-11-33S-16.000000G](#) [SIT9122AI2C233E300.000000X](#) [9120AC-2D2-33E212.500000](#) [9102AI-243N25E100.00000](#) [8208AC-82-](#)  
[18E-25.00000](#) [8008AI-72-XXE-24.545454E](#) [8004AC-13-33E-133.33000X](#) [AS-4.9152-16-SMD-TR](#) [ASFL1-48.000MHZ-LC-T](#)  
[632L3I004M00000](#) [SIT8920AM-31-33E-25.0000](#) [DSC1028DI2-019.2000](#) [9121AC-2C3-25E100.00000](#) [9102AI-233N33E100.00000X](#)  
[9102AI-233N25E200.00000](#) [9102AI-232H25S125.00000](#) [9102AI-133N25E200.00000](#) [9102AC-283N25E200.00000](#) [9001AC-33-33E1-30.000](#)  
[8103AC-13-33E-12.00000X](#) [3921AI-2CF-33NZ125.000000](#) [5730-1SF](#) [XUN736000.032768I](#) [ASV-25.000MHZ-ECS-50-T](#) [EC3925ETTTS-](#)  
[100.000M TR](#) [SIT1602BC-83-33E-10.000000Y](#) [8003AI-12-33S-40.00000Y](#) [1602BI-13-33S-19.200000E](#)