



SAW Components

SAW Duplexer

WCDMA


Series/type: **B7967**
B39212B7967P810

Date: November 09, 2011
Version: 2.0


Data sheet


Application


- Low-loss SAW duplexer for WCDMA femtocell systems
- Low insertion attenuation
- Low amplitude ripple
- Usable passband 60 MHz
- High power durability


Features

- Package size 3.0 * 2.5 * 1.0 mm³
- RoHS compatible
- Approx. weight 0.035 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**
- Moisture Sensitivity Level 3


Pin configuration

- 3 RX Output
- 1 TX Input
- 6 Antenna
- 2, 4, 5 To be grounded
- 7, 8, 9 To be grounded



Data sheet


Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characteristics TX - ANT		min.	typ. @ 25 °C	max.	
Center frequency	f _C	-	2140.0	-	MHz
Maximum insertion attenuation 2110.0 ... 2170.0 MHz	α _{max}	-	2.0	2.5	dB
Amplitude ripple (p-p) 2110.0 ... 2170.0 MHz	Δα	-	0.6	1.0	dB
Error Vector Magnitude 2112.4 ... 2167.6 MHz	EVM ¹⁾	-	0.4	1.0	%
Input VSWR (TX port) 2110.0 ... 2170.0 MHz		-	1.8	2.2	
Output VSWR (ANT port) 2110.0 ... 2170.0 MHz		-	1.8	2.2	
Attenuation	α				
10.0 ... 1920.0 MHz		35	38	-	dB
1920.0 ... 1960.0 MHz		44	49	-	dB
1960.0 ... 1980.0 MHz		44	50	-	dB
2250.0 ... 2400.0 MHz		35	46	-	dB
2400.0 ... 2500.0 MHz		35	45	-	dB
2500.0 ... 3000.0 MHz		35	45	-	dB
3000.0 ... 3800.0 MHz		30	40	-	dB
3800.0 ... 4220.0 MHz		25	38	-	dB
4220.0 ... 4340.0 MHz		25	37	-	dB
4340.0 ... 5000.0 MHz		20	36	-	dB
5000.0 ... 6330.0 MHz		15	25	-	dB
6330.0 ... 6510.0 MHz		20	30	-	dB

1) Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

Data sheet


Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characterisitcs ANT - RX		min.	typ. @ 25 °C	max.	
Center frequency	f _C	-	1950.0	-	MHz
Maximum insertion attenuation 1920.0 ... 1980.0 MHz	α _{max}	-	2.2	3.0	dB
Amplitude ripple (p-p) 1920.0 ... 1980.0 MHz	Δα	-	1.0	1.8	dB
Error Vector Magnitude 1922.4 ... 1987.6 MHz	EVM ¹⁾	-	1.6	2.0	%
Input VSWR (ANT port) 1920.0 ... 1980.0 MHz		-	1.8	2.2	
Output VSWR (RX port) 1920.0 ... 1980.0 MHz		-	1.9	2.2	
Attenuation	α				
10.0 ... 1800.0 MHz		30	35	-	dB
1800.0 ... 1880.0 MHz		20	30	-	dB
1880.0 ... 1900.0 MHz		8	25	-	dB
2110.0 ... 2170.0 MHz		46	50	-	dB
2400.0 ... 2500.0 MHz		25	28	-	dB
2500.0 ... 3840.0 MHz		15	20	-	dB
3840.0 ... 3960.0 MHz		25	30	-	dB
3960.0 ... 5000.0 MHz		20	32	-	dB
5000.0 ... 5760.0 MHz		10	20	-	dB
5760.0 ... 5940.0 MHz		15	25	-	dB

1) Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

Data sheet


Characteristics

Temperature range for specification:	T = -10 °C to +85 °C
Antenna terminating impedance:	Z _{ANT} = 50 Ω
RX terminating impedance:	Z _{RX} = 50 Ω
TX terminating impedance:	Z _{TX} = 50 Ω

Characterisitcs TX - RX				min.	typ. @ 25 °C	max.	
Isolation	α	1920.0 ... 1980.0 MHz		45	48	-	dB
		2110.0 ... 2170.0 MHz		52	55	-	dB


Maximum ratings

Operable temperature range	T	-35/+85	°C	machine model, 10 pulses source and load impedance 50 Ω
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100	V ¹⁾	
Input power at pin 1	P _{IN}			
2110.0 ... 2170.0 MHz		28	dBm	} LTE 5 MHz downlink (11.7 PAPR) T = 55°C, 50.000 h
elsewhere		10	dBm	


1) acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses



Frequency Response TX-ANT




Frequency Response TX-ANT






Frequency Response ANT-RX




Frequency Response ANT-RX




Data sheet



Frequency Response TX-RX





Frequency Response TX-RX







S11 VSWR (TX)





normal impedance: 50.00 Ω

S22 VSWR (ANT)



normal impedance: 50.00 Ω


S33 VSWR (RX)




normal impedance: 50.00 Ω



EVM Rx



EVM Tx



Type	B7967
Ordering code	B39212B7967P810
Marking and package	C61157-A3-A26
Packaging	F61074-V8211-Z000
Date codes	L_1126
S-parameters	B7967_NB.s3p B7967_WB.s3p See file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	Defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See Inductor pdf-catalog http://www.tdk.co.jp/tefe02/coil.htm#aname1 and Data Library for circuit simulation http://www.tdk.co.jp/etvcl/index.htm

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

Published by EPCOS AG

Systems, Acoustics, Waves Business Group

P.O. Box 80 17 09, 81617 Munich, GERMANY

© EPCOS AG 2011. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the “General Terms of Delivery for Products and Services in the Electrical Industry” published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Signal Conditioning](#) category:

Click to view products by [RF360](#) manufacturer:

Other Similar products are found below :

[MAPDCC0001](#) [MAPDCC0004](#) [PD0409J5050S2HF](#) [880157](#) [HHS-109-PIN](#) [DC1417J5005AHF](#) [AFS14A30-2185.00-T3](#) [AFS14A35-1591.50-T3](#) [DS-323-PIN](#) [B39321R801H210](#) [1A0220-3](#) [JP510S](#) [LFB212G45SG8C341](#) [LFB322G45SN1A504](#) [LFL182G45TC3B746](#) [SF2159E](#) [30057](#)
[FM-104-PIN](#) [CER0813B](#) [MAPDCC0005](#) [3A325](#) [40287](#) [41180](#) [ATB3225-75032NCT](#) [BD0810N50100AHF](#) [BD2425J50200AHF](#)
[C5060J5003AHF](#) [JHS-115-PIN](#) [JP503AS](#) [DC0710J5005AHF](#) [DC2327J5005AHF](#) [DC3338J5005AHF](#) [43020](#) [LFB2H2G60BB1C106](#)
[LFL15869MTC1B787](#) [X3C19F1-20S](#) [XC3500P-20S](#) [10013-20](#) [SF2194E](#) [CDBLB455KCAX39-B0](#) [TGL2208-SM, EVAL](#) [RF1353C](#)
[PD0922J5050D2HF](#) [1E1305-3](#) [1G1304-30](#) [B0922J7575AHF](#) [2020-6622-20](#) [TP-102-PIN](#) [TP-103-PIN](#) [BD1222J50200AHF](#)