	F	PART NO.	MAXIMUM PANEL THICKNESS	HOLE DIAMETER	"A"±.020	"B" REF
		PGM-1	.062 [1.57]	.250±.003 [6.35±0.08]	.312 [7.9]	.312 [7.9]
		PGM-2		.312±.003 [7.9±0.08]	.375 [9.5]	
	F	PGM-3		.468±.002 [11.9±0.05]	.531 [13.5]	.250 [6.35]
		PGM-4	.067 [1.7]	.189±.004 [4.8±0.1]	.236 [6]	.205 [5.2]
	F	PGM-5	.062 [1.57]	.500±.002 [12.7±0.05]	.562 [14.3]	.250 [6.35]
	F	PGM-6	.067 [1.7]	.252 [6.4±0.1]	.299 [7.6]	.221 [5.6]
		PGM-7	PGM-8 .063 [1.6]	.278±.002 [7.05±0.05]	.433 [11]	.276 [7]
		PGM-8		.307±.008 [7.8±0.2]	.375 [9.5]	.236 [6]
		PGM-9		.376±.002[9.55±0.05]	544 [40]	.256 [6.5]
		PGM-10	.055 [1.4]	.386±.008 [9.8±0.2]	.511 [13]	.236 [6]
		PGM-11	.062 [1.57]	.531±.002 [13.48±0.05]	.593 [15.1]	
		PGM-12		.625±.002 [15.9±0.05]	.718 [180.2]	.250 [6.35]
		PGM-13	.083 [2.1]	.506±.006 [12.85±0.15]	.669 [17]	.315 [8]
		PGM-14	.062 [1.57]	.750±.002 [19.05±0.05]	.843 [21.4]	
│ "₿" 《│ │》 │   ⊨	=	PGM-15		.781±.002 [19.84±0.05	.890 [22.6]	.250 [6.35]
	—U   F	PGM-16	.079 [2]	.628±.002[15.95±0.05]	.787 [20]	.315 [8]
		PGM-17	.062 [1.57]	.875±.002 [22.22±0.05]	.968 [24.6]	.250 [6.35]
	Γ	PGM-18	.125 [3.2]	1.250±.002 [31.75±0.05]	1.375 [34.9]	.465 [11.8]
		PGM-19		.746±.002 [18.95±0.05]	.925 [23.5]	.413 [10.5]
	Γ	PGM-20		1.375±.002 [34.93±0.05]	1.500 [38.1]	.465 [11.8]
		PGM-21		1.750±.002 [44.45±0.05]	1.906 [48.4]	.405 [11.0]
		PGM-22	.118 [3]	.864±.002 [21.95±0.05]	1.024 [26]	.378 [9.6]
		PGM-23		2.000±.002 [50.8±0.05]	2.170 [55.1]	.470 [11.9]
		PGM-24		.500±.002 [12.7±0.05]	.578 [14.7]	.406 [10.3]
		PGM-25		1.004±.004 [25.5±0.1]	1.102 [28]	.500 [12.7]
		PGM-26 PGM-27		.562±.002 [14.27±0.05]	.656 [16.7]	
				.625±.002 [15.88±.0.05]	.718 [18.2]	
		PGM-28	.125 [3.2] GM-30 GM-31 GM-32 GM-33	.687±.002 [17.45±0.05]	.781 [19.8]	
		PGM-29		.875±.002 [22.22±0.05]	1.125 [28.6]	.453 [11.5]
		PGM-30		1.203±.002 [30.55±0.05]	1.339 [34]	.512 [13]
		PGM-31		1.500±.002 [38.1±0.05]	1.671 [42.4]	.465 [11.8]
		PGM-32		1.097±.004 [27.86±0.1]	1.218 [30.9]	. 100 [ 1 1.0]
		PGM-33		.375±.002 [9.5±0.05]	.468 [11.9]	.406 [10.3]
NOTES	L	PGM-34		.437±.002 [11.1±0.05]	.531 [13.5]	[]
1. MATERIAL: NYLON 6/6 UL 94 V-2 (RMS-01) 2. COLOR: BLACK.						
COLOR WHITE AVAILABLE BY SPECIAL ORDER ONLY.						
					DWG	
'''``F				ERIES] 🛛 🕀		
	CREATED USING SOLIDWORKS FILE #: PGM			APP: SK	FINAL	
TOLERANO	TOLERANCES SHEET: 1 OF 1 SHEET SIZE: A			CHKD: D.Z PART		PDINIT
	UNLESS NOTED					PRINT TYPE
1 SEE CO 200321 POR CHAINGES ON 02/03/03 XXX=±.0	02/09/09 .XXX=±.005 RICHCO, INC.					
SEE ENGINEERING FOR REV A-E FRAC.=±1/64 DESCRIPTION ENGR. DATE ANG.=±1°						
REV. DESCRIPTION ENGR. DATE ANG.=±			( , .			

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Conduit Fittings & Accessories category:

Click to view products by Richco manufacturer:

Other Similar products are found below :

 \$53.35A
 260-416
 DM0240-1/2A
 817.612.0
 55506625
 1.511.2001.50
 1.533.1601.50
 1.533.2001.50
 52005810
 817.716.0
 712.015.0
 216 

 420
 2276
 2663-P
 C2070-P
 3582V
 2643-P
 4975
 2644-P
 90480
 2404-P
 1047561
 2723-P
 55506355
 1.513.1101.14
 55502461
 55502462

 55502463
 55502464
 55502473
 166-22214
 166-22215
 166-24800
 166-25801
 166-30318
 SHR-C1
 2037
 12-20 LGR
 2037
 16-24 LGR

 HP50SS
 55502470
 SH PA6 BL ND10
 5308 946
 295.012.0
 2955
 M25
 2955
 M40
 297.212.0
 297.240.0
 298.012.0