

## SAFETY DATA SHEET

HX628HP/NC

Page: 1  
Compilation date: 25/04/2012  
Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: HX628HP/NC

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company name: Robnor Resins Ltd  
31 Athena Avenue  
Elgin Industrial Estate  
Swindon  
Wiltshire  
SN2 8EJ  
United Kingdom  
Tel: +44(0)1793 823741  
Fax: +44(0)1793 827033  
Email: [support@robnor.co.uk](mailto:support@robnor.co.uk)

#### 1.4. Emergency telephone number

Emergency tel: +44(0)1793 823741  
(office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Repr. 2: H361f; Skin Corr. 1B: H314; Skin Sens. 1: H317

Most important adverse effects: Causes severe skin burns and eye damage. May cause an allergic skin reaction.  
Suspected of damaging fertility. Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements:

Hazard statements: H314: Causes severe skin burns and eye damage.  
H317: May cause an allergic skin reaction.  
H361f: Suspected of damaging fertility.  
H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion  
GHS07: Exclamation mark  
GHS08: Health hazard  
GHS09: Environmental



Precautionary statements: P202: Do not handle until all safety precautions have been read and understood.

# SAFETY DATA SHEET

HX628HP/NC

Page: 2

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+313: IF exposed or concerned: Get medical advice.

P321: Specific treatment (see instructions on this label).

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

#### FATTY ACIDS, VEGETABLE-OIL, REACTION PRODUCTS WITH, TETRAETHYLENEMPENTAMINE

FINECS	CAS	PBT / WEL	CLP Classification	Percent
273-652-9	68991-84-4	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 2: H411	30-50%

#### 2-PIPERAZIN-1-YLETHYLAMINE

205-411-0	140-31-8	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	10-30%
-----------	----------	---	--	--------

#### 3,6-DIAZAOCETANETHYLENEDIAMINE

203-950-6	112-24-3	-	Acute Tox. 4: H312; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 3: H412	1-10%
-----------	----------	---	--	-------

#### 2,2'-IMINODIETHYLAMINE

203-865-4	111-40-0	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317	1-10%
-----------	----------	---	---	-------

#### 4,4'-ISOPROPYLIDENEDIPHENOL

201-245-8	80-05-7	-	Repr. 2: H361f; STOT SE 3: H335; Eye Dam. 1: H318; Skin Sens. 1: H317	1-10%
-----------	---------	---	---	-------

#### 1,3-BENZENEDIOL

203-585-2	108-46-3	-	Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Aquatic Acute 1: H400	1-10%
-----------	----------	---	--	-------

#### 3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE

203-986-2	112-57-2	-	Acute Tox. 4: H312; Acute Tox. 4: H302; Skin Corr. 1B: H314; Skin Sens. 1: H317; Aquatic Chronic 2: H411	1-10%
-----------	----------	---	--	-------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

[cont...]

# SAFETY DATA SHEET

HX628HP/NC

Page: 3

**Ingestion:** If conscious, give half a litre of water to drink immediately. Do not induce vomiting. Transfer to hospital as soon as possible.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** Irritation or pain may occur at the site of contact. Progressive ulceration will occur if treatment is not immediate. Absorption through the skin may occur causing symptoms similar to those of ingestion.

**Eye contact:** There may be irritation and redness. The eyes may water profusely. There may be severe pain. Corneal burns may occur.

**Ingestion:** Corrosive burns may appear around the lips. There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting. There may be mental confusion. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** Exposure may cause coughing or wheezing. There may be shortness of breath with a burning sensation in the throat. Nausea and stomach pain may occur. There may be vomiting.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

## 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Immediate medical attention is required. Show this safety data sheet to the doctor in attendance. Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** Corrosive. In combustion emits toxic fumes. In combustion emits toxic fumes of nitrogen oxides.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. If outside do not approach from downwind. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

[cont...]

# SAFETY DATA SHEET

HX628HP/NC

Page: 4

## 6.4. Reference to other sections

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. Avoid incompatible materials and conditions - see section 10 of SDS.

**Suitable packaging:** Must only be kept in original packaging.

### 7.3. Specific end use(s)

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

**2,2'-IMINODIETHYLAMINE**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	4.3 mg/m <sup>3</sup>	-	-	-

**4,4'-ISOPROPYLIDENEDIPHENOL**

UK	5 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	-	-
----	---------------------	---------------------	---	---

**1,3-BENZENEDIOL**

UK	46 mg/m <sup>3</sup>	92 mg/m <sup>3</sup>	-	-
----	----------------------	----------------------	---	---

### DNEL/PNEC Values

DNEL / PNEC No data available.

### 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Butyl gloves. Neoprene gloves.

**Eye protection:** Safety goggles. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**Environmental:** Ensure emissions from ventilation or equipment comply with environmental protection legislation.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Pale yellow

**Odour:** Characteristic odour

**Solubility in water:** Soluble

**Flash point°C:** 148-154

**Relative density:** 0.98

[cont...]

# SAFETY DATA SHEET

HX628HP/NC

Page: 5

## 9.2. Other information

Other information: No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.  
Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces.

### 10.5. Incompatible materials

Materials to avoid: Acids. Oxidising agents.

### 10.6. Hazardous decomposition products

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Toxicity values:

Route	Species	Test	Value	Units
ORL	RAT	LD50	2500	mg/kg
ORL	MUS	LD50	1600	mg/kg
IVN	MUS	LD50	350	mg/kg

#### Hazardous ingredients:

##### 2-PIPERAZIN-1-YLETHYLAMINE

IPR	MUS	LD50	250	mg/kg
ORL	RAT	LD50	2140	µl/kg

##### 3,6-DIAZAOCTANETHYLENEDIAMINE

IVN	MUS	LD50	350	mg/kg
ORL	MUS	LD50	1600	mg/kg
ORL	RAT	LD50	2500	mg/kg

##### 2,2'-IMINODIETHYLAMINE

IPR	RAT	LD50	74	mg/kg
ORL	MUS	LD50	970	mg/kg
ORL	RAT	LD50	970	mg/kg

[cont...]

# SAFETY DATA SHEET

HX628HP/NC

Page: 6

## 4,4'-ISOPROPYLIDENEDIPHENOL

ORL	MUS	LD50	2400	mg/kg
ORL	RAT	LD50	3250	mg/kg

## 1,3-BENZENEDIOL

ORL	MUS	LD50	200	mg/kg
ORL	RAT	LD50	301	mg/kg
SCU	MUS	LD50	213	mg/kg

## 3,6,9-TRIAZAUNDECAMETHYLENEDIAMINE

IPR	RAT	LD50	205	mg/kg
IVN	MUS	LD50	320	mg/kg
ORL	RAT	LD50	3990	mg/kg

### Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
Reproductive toxicity	--	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** Irritation or pain may occur at the site of contact. Progressive ulceration will occur if treatment is not immediate. Absorption through the skin may occur causing symptoms similar to those of ingestion.

**Eye contact:** There may be irritation and redness. The eyes may water profusely. There may be severe pain. Corneal burns may occur.

**Ingestion:** Corrosive burns may appear around the lips. There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting. There may be mental confusion. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

**Inhalation:** Exposure may cause coughing or wheezing. There may be shortness of breath with a burning sensation in the throat. Nausea and stomach pain may occur. There may be vomiting.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Only slightly biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** No data available.

### 12.4. Mobility in soil

**Mobility:** No data available.

[cont...]

# SAFETY DATA SHEET

HX628HP/NC

Page: 7

## 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

## 12.6. Other adverse effects

**Other adverse effects:** Harmful to soil organisms. Harmful to aquatic organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN2735

### 14.2. UN proper shipping name

**Shipping name:** AMINES, LIQUID, CORROSIVE, N.O.S.  
(2-PIPERAZIN-1-YLETHYLAMINE, TRIETHYLENTETRAMINE, DIETHYLENETRIAMINE)

### 14.3. Transport hazard class(es)

**Transport class:** 8

### 14.4. Packing group

**Packing group:** II

### 14.5. Environmental hazards

**Environmentally hazardous:** Yes

**Marine pollutant:** No

### 14.6. Special precautions for user

**Tunnel code:** E

**Transport category:** 2

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H302: Harmful if swallowed.  
H312: Harmful in contact with skin.  
H314: Causes severe skin burns and eye damage.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.

[cont...]

# SAFETY DATA SHEET

HX628HP/NC

Page: 8

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

H361f: Suspected of damaging fertility.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



## SAFETY DATA SHEET

RX628HP/NC

Page: 1  
Compilation date: 25/04/2012  
Revision No: 1

### Section 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name: RX628HP/NC

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

Company name: Robnor Resins Ltd  
31 Athena Avenue  
Elgin Industrial Estate  
Swindon  
Wiltshire  
SN2 8EJ  
United Kingdom  
Tel: +44(0)1793 823741  
Fax: +44(0)1793 827033  
Email: [support@robnor.co.uk](mailto:support@robnor.co.uk)

#### 1.4. Emergency telephone number

Emergency tel: +44(0)1793 823741  
(office hours only)

### Section 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317

Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.  
Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Label elements:

Hazard statements: H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H411: Toxic to aquatic life with long lasting effects.

Signal words: Warning

Hazard pictograms: GHS07: Exclamation mark  
GHS09: Environmental



Precautionary statements: P264: Wash hands thoroughly after handling.  
P302+352: IF ON SKIN: Wash with plenty of water/.  
P273: Avoid release to the environment.

# SAFETY DATA SHEET

RX628HP/NC

Page: 2

P280: Wear protective gloves.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321: Specific treatment (see instructions on this label).  
P332+313: If skin irritation occurs: Get medical attention.  
P363: Wash contaminated clothing before reuse.

## 2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

## Section 3: Composition/information on ingredients

### 3.2. Mixtures

#### Hazardous ingredients:

#### ORTHO CRESOL NOVALAC EPOXY RESIN

FINECS	CAS	PBT / WEL	CLP Classification	Percent
-	94362-50-2	-	Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411; Eye Irrit. 2: H319	30-50%

#### CHALK

-	471-34-1	Substance with a Community workplace exposure limit.	-	30-50%
---	----------	--	---	--------

#### 1,4-BIS(2,3-EPOXYPROPOXY) BUTANE

219-371-7	2425-79-8	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317	10-30%
-----------	-----------	---	---	--------

## Section 4: First aid measures

### 4.1. Description of first aid measures

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.  
**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.  
**Ingestion:** Wash out mouth with water. Do not induce vomiting. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be irritation and redness at the site of contact.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
**Ingestion:** There may be soreness and redness of the mouth and throat.  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Immediate / special treatment:** Eye bathing equipment should be available on the premises.

## Section 5: Fire-fighting measures

[cont...]

# SAFETY DATA SHEET

RX628HP/NC

Page: 3

## 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

## 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

## 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed. The floor of the storage room must be impermeable to prevent the escape of liquids.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**Hazardous ingredients:**

[cont...]

# SAFETY DATA SHEET

RX628HP/NC

Page: 4

CHALK

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	mg/m <sup>3</sup>	-

## DNEL/PNEC Values

DNEL / PNEC No data available.

## 8.2. Exposure controls

**Engineering measures:** Ensure there is sufficient ventilation of the area. The floor of the storage room must be impermeable to prevent the escape of liquids.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Safety glasses. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Environmental:** Prevent from entering in public sewers or the immediate environment.

## Section 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

**State:** Liquid

**Colour:** Various

### 9.2. Other information

**Other information:** No data available.

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

**Conditions to avoid:** Heat.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

[cont...]

# SAFETY DATA SHEET

RX628HP/NC

Page: 5

Hazardous ingredients:

## 1,4-BIS(2,3-EPOXYPROPOXY) BUTANE

ORL	MUS	LD50	1100	µg/kg
ORL	RAT	LD50	1134	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

**Delayed / immediate effects:** Delayed effects can be expected after long-term exposure.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

### 12.2. Persistence and degradability

**Persistence and degradability:** Not biodegradable.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential:** Bioaccumulation potential.

### 12.4. Mobility in soil

**Mobility:** Readily absorbed into soil.

### 12.5. Results of PBT and vPvB assessment

**PBT identification:** This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

**Other adverse effects:** Toxic to aquatic organisms. Toxic to soil organisms.

## Section 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## Section 14: Transport information

### 14.1. UN number

**UN number:** UN3082

[cont...]

# SAFETY DATA SHEET

RX628HP/NC

Page: 6

## 14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.  
(ORTHO CRESOL NOVALAC EPOXY RESIN)

## 14.3. Transport hazard class(es)

Transport class: 9

## 14.4. Packing group

Packing group: III

## 14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

## 14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

## Section 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### 15.2. Chemical Safety Assessment

## Section 16: Other information

### Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H312: Harmful in contact with skin.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

## **X-ON Electronics**

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [robnor](#) manufacturer:*

Other Similar products are found below :

[EL171LF/BK/500](#) [EL420LV/WW/050TC](#) [EL583C/NC/500](#) [EL227CL/NC/500](#) [PX439NL-1/BK/250](#) [TS106/NC/1LT](#) [EL110H/BK/250](#)  
[TS109/NC/1LT](#) [EL217C/BK/250](#) [PX900D/NC/250](#) [PX439XS/BK/500](#) [EL171C/566](#) [PX439XS/BK/250](#) [PX439XS/BK/100](#)