



项目 Project	规格 Specification
额定电负荷: Rated electric load	DC5V 50mA
绝缘电阻: Insulation resistance	≥100MΩ
耐压强度: Compressive strength	AC250V 50Hz/1min
电气寿命: Electrical life	10000 cycles Min
环境温度: Ambient temperature	-25℃~+70℃
相对湿度: Relative humidity	(40 ) ≤95%
接触电阻: Contact resistance	≤100mΩ
操作力: Operating force	150gf±50gf

D	盖子 Shell	1	不锈钢 Stainless steel	银白色 silver white
C	接触簧片 Contact spring	2	复银铜 Compound silver copper	银白色镶银 Silver-white inlaid with silver
B	底座 Base	1	LCP与黄铜 LCP&Brass	黑色与镀银 Black and silver
A	手柄 Handle	1	增强尼龙 Reinforced nylon	黑色 Black
No.	名称 Name	Quantity	Material	Plating color

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	
DRAWN BY	FUYUAN	CHECKED BY	COCO
DATE	2019	APPROVAL	B ALEN

PRODUCT NAME:

MODEL NO: TP-33005

Https: www.rocpcu.tw

**ROCPCU TECHNOLOGY CO.,LTD**

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Slide Switches](#) category:*

*Click to view products by [ROCPU Technology](#) manufacturer:*

Other Similar products are found below :

[6-1437581-1](#) [M43R](#) [MHS123K15D](#) [MHS133K](#) [MMD](#) [MSS12A](#) [1825074-1](#) [1825160-3](#) [1825167-2](#) [1825289-7](#) [K232CB](#) [25139NLDB](#)  
[25449NAH](#) [SLB1240R45](#) [1825078-1](#) [1825080-4](#) [1825269-1](#) [1825270-2](#) [STS141RA04](#) [T2215BEN506](#) [GH46P000001](#) [GH49P010001](#)  
[25339NA](#) [25436NLDH](#) [M42A](#) [AYZ0202AG](#) [L203091MS02Q](#) [4-1437581-7](#) [48BFSP3M2QT](#) [1101M1S3ZB8E2](#) [1-1437581-1](#)  
[EG1218REDACTUATOR](#) [MSS2225G04](#) [MSS42G](#) [T105S1CWZBE](#) [SLB124145](#) [SLB1280R5](#) [TG39W000050](#) [25149NAH](#) [25439NAH](#)  
[25436NAH6](#) [TG36Y000050](#) [SL-1211C1B8](#) [46204LRX](#) [1977143-4](#) [1977144-4](#) [HASS0194](#) [JS0001](#) [SSJ12R04](#) [GR5-1323-0800](#)