



Reference technical requirements:

参考技术要求:

1. Contact impedance: 100M ohm Max
- 1.接触阻抗: 100m ohm max
2. Insulation impedance: 1000m ohm min
- 2.绝缘阻抗: 1000M ohm min
3. Withstand voltage: AC250V (50Hz or 60Hz) /60 sec
- 3.耐电压: AC250V(50Hz or 60Hz)/60 sec
4. Heat resistance: 85 °C ± 2 °C, 96h
- 4.耐热性: 85 °C ± 2 °C, 96H
5. Cold and hot shock: -40 °C /30 minutes -- > 85 °C /30 minutes
- 5.冷热冲击: -40 °C /30分钟 -- > 85 °C /30分钟
6. Humidity resistance: 40 °C ± 2 °C, humidity 90%~95%, 504h
- 6.抗湿性: 40 °C ± 2 °C, 湿度90%~95%, 504H
7. Salt spray test: 35 °C, 5%, 48H
- 7.盐雾测试: 35 °C, 5%, 48H
8. Conduction stroke: 0.15mm~0.25mm
- 8.导通行程: 0.15mm~0.25mm
9. Reflow soldering: 260 °C ± 5 °C, 5sec min, twice
- 9.回流焊接: 260 °C ± 5 °C, 5sec Min, 两次
10. Service life: 1,000,000 times
- 10.寿命: 1,000,000次
11. Action force: 100±30gf
- 11.动作力: 100±30gf

4	Dust proof glue 防尘胶	Polyimide 聚酰亚胺	
3	Base 基座	PA6T	Black 黑色
2	Terminal 端子	Phosphor bronze 磷青铜	Ag plating/0.5um Min 镀银/0.5um Min
1	Contact 弹片	SUS	Ag plating/0.5um Min 镀银/0.5um Min
NO 序号	Part name 部件名	Material 材料	Remark 备注

A4				 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP40423210	
A2						DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
A1						ROCPCU TECHNOLOGY CO., LTD					
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				
	A		B		C	D	E	F	G		

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Tactile Switches](#) category:

Click to view products by [ROCPU Technology](#) manufacturer:

Other Similar products are found below :

[6407-250V-25273P](#) [ADTSA62NV](#) [B3F-3123](#) [1977177-8](#) [1977266-1](#) [ADTSA63NV](#) [ADTSM21NSVTR](#) [ADTSM25RVTR](#) [ADTSM32NVTR](#)
[ADTSMW64RV](#) [1977120-6](#) [FSMRA4JHA04](#) [GS4.70F300QP](#) [KSC241J SP DELTA LFS](#) [3FTL600RAS](#) [3FTL640RAS](#) [6407-250V-25343P](#)
[ADTSM31NVTR](#) [2-1977120-7](#) [TSJW-5.2-260-TR](#) [Y651050400P](#) [KMT011MNGJLHS](#) [70-201.0](#) [ADTSG648NV](#) [ADTSM62KSVTR](#)
[ADTSM648NV](#) [95C06E3RAT](#) [3ATH9Q](#) [FSMRA8JHA04](#) [HARS0073](#) [Y33R411N9FPLFT](#) [Y33R51139FPLFT](#) [Y31C01402FPLFS](#)
[PTS645SK50SMTR92](#) [ADTSM32NVB](#) [KMS233GPWTLFG](#) [Y78B64124FP](#) [Y31CJ244KFP LFS](#) [Y96D113G0FP LFS](#) [Y33A812C5FP LFT](#)
[Y56B2D120FP LFS](#) [Y31C5144KFP LFS](#) [PTS645 DVM83-BN125-2 LFS](#) [B3W 1000G](#) [KSC621G OL LFS](#) [B3F 1002C](#) [B3F 0047H](#) [B3W](#)
[1002C](#) [B3F 5001G](#) [B3W 1100C](#)