





A4				 台普 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3			DRAWN BY			FUYUAN	CHECKED BY	COCO	MODEL NO:	TP91602G2A	
A2			DATE			2019	APPROVAL	B	ALLEN	Https:	www.rocpcu.tw
A1			ROCPCU TECHNOLOGY CO.,LTD								
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

A	B	C	D	E	F	G					
1	性能参数		13. Electrical life: 500000 cycles 电气寿命: 500000 cycles								
	1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A		14. mechanical: 500000cycles 机械寿命: 500000cycles								
2	2. Rated current:3A/DC36V 额定电流:3A/DC36V		15. Operation method:Self repeating form 操作方式: 自复式								
	3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min		16. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N								
	4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ										
	5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ										
3	6. Pressing stroke:2.80mm ± 0.10 按压行程:2.80mm ± 0.10										
	7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10										
	8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N										
	9. Protection level:IP67 防护等级:IP67										
	10. Explosion prevention level: IK09 防暴等级: IK09										
	11. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C										
4	12. Compression torque: ≤ 3.5N 按压扭力: ≤3.5N										
	连接形式										
	1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下										
	2. Can be used with dedicated connectors: 可配专用接插件使用:										
	2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)										
5	A4		 台普 ROCPCU	COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:		
	A3			X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91602G2A	
	A2			X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw	
	A1			X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD					
	REV	DATE		REVISION	DESCRIPTION						ISSUE
		A		B		C		D	E	F	G

A	B	C	D	E	F	G			
材质参数									
1									
2	7	Base 底座	PA46	1					
3	6	Pin 引脚	Brass 黄铜	1	gold-plating 镀金				
4	5	Contact material 接触材质	silver alloy 银合金	1					
5	4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍				
6	3	Oring O型圈	Silica gel 硅胶	1					
7	2	Housing 外壳	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色				
8	1	Key 按键	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色				
	NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注				
A4				UNIT	MM	PROJECTED		PRODUCT NAME:	
A3				DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91602G2A	
A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw	
A1				ROCPU TECHNOLOGY CO.,LTD					
REV	DATE	REVISION	DESCRIPTION	ISSUE	ANGULAR			Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission	



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [ROCPU Technology](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)