





A4				 <b>台普</b> <b>ROCPCU</b>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91642G224RA
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	<b>ROCPCU TECHNOLOGY CO.,LTD</b>				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					

性能参数



1. Heating current: Ui: AC250V, Ith: 3A  
发热电流: Ui: AC250V, Ith: 3A
2. Rated current: 2A/DC36V  
额定电流: 2A/DC36V
3. Insulation resistance:  $\geq 1000M\Omega$   
绝缘电阻:  $\geq 1000M\Omega$
4. Contact resistance:  $\leq 50m\Omega$   
接触电阻:  $\leq 50m\Omega$
5. Pressing stroke:  $2.80mm \pm 0.10$   
按压行程:  $2.80mm \pm 0.10$
6. Contact stroke:  $1.10mm \pm 0.10$   
接触行程:  $1.10mm \pm 0.10$
7. Nut assembly torque: 5-14N  
螺帽装配力矩: 5-14N
8. Protection level: IP67  
防护等级: IP67
9. Explosion prevention level: IK09  
防暴等级: IK09
10. Working environment temperature:  $-20^\circ C \sim +55^\circ C$   
工作环境温度:  $-20^\circ C \sim +55^\circ C$
11. Compression torque:  $\leq 3N$   
按压扭力:  $\leq 3N$
12. Electrical life: 500000 cycles  
电气寿命: 500000 cycles

13. mechanical: 500000cycles  
机械寿命: 500000cycles
14. Operation method: Self repeating form  
操作方式: 自复式
15. NO reverse thrust foot torque:  $\leq 30N$   
NO反推脚扭力:  $\leq 30N$
16. LED lamp power consumption: 20m以下  
LED灯功耗: 20m以下
17. LED lamp lifespan: 40000h  
LED寿命: 40000h
18. LED color: Red  
LED颜色: 红色

A4				 <b>台普</b> <b>ROCPCU</b>	COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91642G224RA	
A2					X.XX	$\pm 0.10$	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X.X	$\pm 0.15$	<h1 style="text-align: center;">ROCPCU TECHNOLOGY CO.,LTD</h1>				
REV	DATE	REVISION	DESCRIPTION		ISSUE	X					
					ANGULAR	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission					

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
1	Key 按键	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色
2	Housing 外壳	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色
3	Oring O型圈	Silica gel 硅胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
5	Base 基座	PA66	1	Black 黑色
6	Contact material 接触材质	Silvering 镀银	1	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
8	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银
9	luminous zone 发光区	PC 塑料	1	

### 材质参数

A4				 <b>ROCPCU</b>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91642G224RA
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					
	A		B		C		D	E	F	G	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [ROCPU Technology](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)