






A4				 台普 ROC PU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3							DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91652P124RA
A2					X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
A1					X.X	± 0.15	ROC PU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION	ISSUE	X	± 0.25					
					ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				



	A	B	C	D	E	F	G
1	性能参数						
2	1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A			13. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C			
3	2. Rated current:3A/DC36V 额定电流:3A/DC36V			14. Compression torque: ≤ 3.5N 按压扭力: ≤3.5N			
4	3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min			15. Electrical life: 500000 cycles 电气寿命: 500000 cycles			
5	4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ			16. mechanical: 500000cycles 机械寿命: 500000cycles			
6	5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ			17. Operation method:Self-locking type 操作方式: 自锁式			
7	6. Pressing stroke:2.80mm ± 0.10 按压行程:2.80mm ± 0.10			18. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N			
8	7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10			19. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下			
9	8. welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C			20. LED lamp lifespan: 40000h LED寿命: 40000h			
10	9. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration			21. LED color: Red LED颜色: 红色			
11	10. Nut assembly torque:5-14N 螺帽装配力矩:5-14N						
12	11. Protection level:IP67 防护等级:IP67						
13	12. Explosion prevention level: IK09 防暴等级: IK09						
14	连接形式						
15	1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下						
16	2. Can be used with dedicated connectors: 可配专用接插件使用:						
17	2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)						
18	2.2 LED functional wire: red wire positive pole, black wire negative pole, LED without distinction between positive and negative poles LED功能线材: 红线正极, 黑线负极, LED不分正负极						
19	A4						
20	A3						
21	A2						
22	A1						
23	REV	DATE	REVISION DESCRIPTION ISSUE				
24	A						
25	B						
26	C						
27	D						
28	E						
29	F						
30	G						



	A	B	C	D	E	F	G																																																															
1	<div>材质参数</div> <table border="1"> <tr> <td>10</td><td>luminous zone 发光区</td><td>PC 塑料</td><td>1</td><td></td></tr> <tr> <td>9</td><td>LEDpin LED脚</td><td>Brass 黄铜</td><td>1</td><td>Silvering 镀银</td></tr> <tr> <td>8</td><td>Base 底座</td><td>PA46</td><td>1</td><td></td></tr> <tr> <td>7</td><td>Pin 引脚</td><td>Brass 黄铜</td><td>1</td><td>gold-plating 镀金</td></tr> <tr> <td>6</td><td>Contact material 接触材质</td><td>silver alloy 银合金</td><td>1</td><td>Silvering 镀银</td></tr> <tr> <td>5</td><td>LED Base LED基座</td><td>PBT</td><td>1</td><td></td></tr> <tr> <td>4</td><td>Arm nut 固定螺帽</td><td>Brass 黄铜</td><td>1</td><td>nickeling 镀镍</td></tr> <tr> <td>3</td><td>Oring O型圈</td><td>Silica gel 硅胶</td><td>1</td><td></td></tr> <tr> <td>2</td><td>Housing 外壳</td><td>Aluminum alloy 铝合金</td><td>1</td><td>Oxidized/Black 氧化/黑色</td></tr> <tr> <td>1</td><td>Key 按键</td><td>Aluminum alloy 铝合金</td><td>1</td><td>Oxidized/Black 氧化/黑色</td></tr> <tr> <td>NO 序号</td><td>Part name 部件名</td><td>Material 材料</td><td>QTY 数量</td><td>Remark 备注</td></tr> </table>						10	luminous zone 发光区	PC 塑料	1		9	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银	8	Base 底座	PA46	1		7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金	6	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银	5	LED Base LED基座	PBT	1		4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍	3	Oring O型圈	Silica gel 硅胶	1		2	Housing 外壳	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色	1	Key 按键	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色	NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注	1								
10	luminous zone 发光区	PC 塑料	1																																																																			
9	LEDpin LED脚	Brass 黄铜	1	Silvering 镀银																																																																		
8	Base 底座	PA46	1																																																																			
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金																																																																		
6	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银																																																																		
5	LED Base LED基座	PBT	1																																																																			
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍																																																																		
3	Oring O型圈	Silica gel 硅胶	1																																																																			
2	Housing 外壳	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色																																																																		
1	Key 按键	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色																																																																		
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注																																																																		
2							2																																																															
3							3																																																															
4							4																																																															
5	<table border="1"> <tr> <td>A4</td><td></td><td></td><td></td><td rowspan="5">  <div>台普 ROCPCU</div> </td> <td colspan="2">COMMON TOLERANCE</td> <td>UNIT</td><td>MM</td><td>PROJECTED</td><td></td><td>PRODUCT NAME:</td></tr> <tr> <td>A3</td><td></td><td></td><td></td><td>DRAWN BY</td><td>FUYUAN</td><td>CHECKED BY</td><td>COCO</td><td colspan="3">MODEL NO: TP91652P124RA</td></tr> <tr> <td>A2</td><td></td><td></td><td></td><td>DATE</td><td>2019</td><td>APPROVAL B</td><td>ALEN</td><td colspan="3">Https: www.rocpcu.tw</td></tr> <tr> <td>A1</td><td></td><td></td><td></td><td colspan="7" rowspan="2"> <div>ROCPCU TECHNOLOGY CO.,LTD</div> </td></tr> <tr> <td>REV</td><td>DATE</td><td>REVISION</td><td>DESCRIPTION</td><td>ISSUE</td></tr> <tr> <td></td><td></td><td></td><td></td><td></td><td>ANGULAR</td><td>—</td><td colspan="6">Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission</td></tr> </table>						A4				 <div>台普 ROCPCU</div>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:	A3				DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91652P124RA			A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw			A1				<div>ROCPCU TECHNOLOGY CO.,LTD</div>							REV	DATE	REVISION	DESCRIPTION	ISSUE						ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission						5
A4				 <div>台普 ROCPCU</div>	COMMON TOLERANCE		UNIT	MM	PROJECTED			PRODUCT NAME:																																																										
A3					DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP91652P124RA																																																													
A2					DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw																																																													
A1					<div>ROCPCU TECHNOLOGY CO.,LTD</div>																																																																	
REV	DATE	REVISION	DESCRIPTION									ISSUE																																																										
					ANGULAR	—	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission																																																															
	A	B	C	D	E	F	G																																																															



## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [ROCPU Technology](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)