





| | | | | | | | | | | | |
|-----|------|----------|-------------|---|------------------|---------|------------------------------------|--------|------------|---|-------------------------|
| A4 | | | |  台普 ROCPCU | COMMON TOLERANCE | | UNIT | MM | PROJECTED |  | PRODUCT NAME: |
| A3 | | | | | X.XX | ± 0.10 | DRAWN BY | FUYUAN | CHECKED BY | COCO | MODEL NO: TP92213P124RA |
| A2 | | | | | X.X | ± 0.15 | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | X | ± 0.25 | <h1>ROCPCU TECHNOLOGY CO.,LTD</h1> | | | | |
| REV | DATE | REVISION | DESCRIPTION | | ISSUE | ANGULAR | | | | | |


性能参数

- | | | | |
|---|---|---|---|
| 1 | 1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A 2. Rated current:3A/DC36V 额定电流:3A/DC36V 3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min 4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ 5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ 6. Pressing stroke:3.00mm ± 0.10 按压行程:3.00mm ± 0.10 7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10 8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N 9. Protection level:IP67 防护等级:IP67 10. Explosion prevention level: IK10 防暴等级: IK10 11. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C 12. Compression torque: ≤ 6N 按压扭力: ≤ 6N | 13. Electrical life: 100000 cycles 电气寿命: 100000 cycles 14. mechanical: 500000cycles 机械寿命: 500000cycles 15. Operation method:Self-locking type 操作方式: 自锁式 16. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下 17. LED lamp lifespan: 40000h LED寿命: 40000h 18. LED color: Red LED颜色: 红色 19. LED Lamp Voltage: 24V LED灯电压: 24V 20. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N | 1 |
| 2 | | | 2 |
| 3 | | | 3 |

连接形式

- | | | |
|---|---|---|
| 4 | 1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下 2. Can be used with dedicated connectors: 可配专用接插件使用: 2.1 1NO1NCswitch function wire: green (C) blue wire (NO) yellow wire (NC) 1NO1NC开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC) 2.2 2NO2NC switch function wire: green black wire C, blue black wire NO, yellow white wire NC 2NO2NC开关功能线材: 绿黑线C、蓝黑线NO、黄白线NC 2.3 LED functional wire: red wire positive pole black wire negative pole LED without distinguishing positive and negative poles LED功能线材: 红线正极 黑线负极 LED不分正负极 | 4 |
|---|---|---|

| | | | | | | | | | | | |
|-----|------|----------|-------------|--|------------------|---------|---|--------|------------|---|-------------------------|
| A4 | | | |  <p>台普 ROCPCU</p> | COMMON TOLERANCE | | UNIT | MM | PROJECTED |  | PRODUCT NAME: |
| A3 | | | | | X.XX | ± 0.10 | DRAWN BY | FUYUAN | CHECKED BY | COCO | MODEL NO: TP92213P124RA |
| A2 | | | | | X.X | ± 0.15 | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | | X | ± 0.25 | ROCPCU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | | ISSUE | ANGULAR | Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission | | | | |

| A | B | C | D | E | F | G | | |
|-------------|--------------------------|-----------------------|-------------|---------------------------------|--|------------|---|-------------------------|
| 材质参数 | | | | | | | | |
| 10 | luminous zone 发光区 | PC 塑胶 | 1 | | | | | |
| 9 | LEDpin LED引脚 | Brass 黄铜 | 1 | | Silvering 镀银 | | | |
| 8 | Base 底座 | PA46 | 1 | | | | | |
| 7 | Pin 引脚 | Brass 黄铜 | 1 | | gold-plating 镀金 | | | |
| 6 | Contact material 接触材质 | silver alloy 银合金 | 1 | | | | | |
| 5 | LED Base LED基座 | PC 塑胶 | 1 | | | | | |
| 4 | Arm nut 固定螺帽 | Brass 黄铜 | 1 | | nickeling 镀镍 | | | |
| 3 | Oring O型圈 | Silica gel 硅胶 | 1 | | | | | |
| 2 | Housing 外壳 | Aluminum alloy 铝合金 | 1 | | Oxidized/Black 氧化/黑色 | | | |
| 1 | Key 按键 | Aluminum alloy 铝合金 | 1 | | Oxidized/Black 氧化/黑色 | | | |
| NO 序号 | Part name 部件名 | Material 材料 | QTY 数量 | | Remark 备注 | | | |
| A4 | | | | UNIT | MM | PROJECTED |  | PRODUCT NAME: |
| A3 | | | | DRAWN BY | FUYUAN | CHECKED BY | COCO | MODEL NO: TP92213P124RA |
| A2 | | | | DATE | 2019 | APPROVAL B | ALEN | Https: www.rocpcu.tw |
| A1 | | | | ROCPU TECHNOLOGY CO.,LTD | | | | |
| REV | DATE | REVISION | DESCRIPTION | ISSUE | <small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission</small> | | | |
| | A | B | C | D | E | F | G | |



COMMON TOLERANCE

| | |
|---------|--------|
| X.XX | ± 0.10 |
| X.X | ± 0.15 |
| X | ± 0.25 |
| ANGULAR | — |

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [ROCPU Technology](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)