



Single color electrical schematic diagram  
单色电气原理图



Installation View  
安装视图



A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP92225P124RA
DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw



**ROCPCU TECHNOLOGY CO.,LTD**

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basis of manufacture or sale of apparatus without permission

	A	B	C	D	E	F	G	
1	性能参数			13. Electrical life: 100000 cycles 电气寿命: 100000 cycles				
	1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A			14. mechanical: 500000cycles 机械寿命: 500000cycles				
2	2. Rated current:3A/DC36V 额定电流:3A/DC36V			15. Operation method:Self-locking type 操作方式: 自锁式				
	3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min			16. Power-frequency withstand voltage: 2000V/1min 工频耐压: 2000V/1min				
	4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ			17. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下				
	5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ			18. LED lamp lifespan: 40000h LED寿命: 40000h				
	6. Pressing stroke:3.50mm ± 0.10 按压行程:3.50mm ± 0.10			19. LED color: Red LED颜色: 红色				
3	7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10			20. LED Lamp Voltage: 24V LED灯电压: 24V				
	8. Nut assembly torque:5-14N 螺帽装配力矩:5-14N			21. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N				
	9. Protection level:IP67 防护等级:IP67							
	10. Explosion prevention level: IK10 防暴等级: IK10							
	11. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C							
	12. Compression torque: ≤ 3.5N 按压扭力: ≤3.5N							
4	连接形式							
	1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下							
	2. Can be used with dedicated connectors: 可配专用接插件使用:							
	2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)							
	2.2 LED functional wire: red wire positive pole black wire negative pole LED without distinguishing positive and negative poles LED功能线材: 红线正极 黑线负极 LED不分正负极							
5	A4							
	A3			COMMON TOLERANCE	UNIT	MM	PROJECTED	PRODUCT NAME:
	A2			X.XX ± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO
	A1			X.X ± 0.15	DATE	2019	APPROVAL B	ALEN
	REV	DATE	REVISION DESCRIPTION	ISSUE	ROCPU TECHNOLOGY CO.,LTD			MODEL NO: TP92225P124RA
					Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission			Https: www.rocpcu.tw
				ANGULAR				
	A	B	C	D	E	F	G	



ROCPU TECHNOLOGY CO.,LTD

A		B		C		D		E		F		G	
<b>材质参数</b>													
10	luminous zone 发光区			PC 塑胶		1							
9	LEDpin LED引脚			Brass 黄铜		1		Silvering 镀银					
8	Base 底座			PA66		1							
7	Pin 引脚			Brass 黄铜		1		gold-plating 镀金					
6	Contact material 接触材质			silver alloy 银合金		1		Silvering 镀银					
5	LED Base LED基座			PA66		1							
4	Arm nut 固定螺帽			Brass 黄铜		1		nickeling 镀镍					
3	Oring O型圈			Silica gel 硅胶		1							
2	Housing 外壳			Aluminum alloy 铝合金		1		Oxidized/Black 氧化/黑色					
1	Key 按键			Aluminum alloy 铝合金		1		Oxidized/Black 氧化/黑色					
NO 序号	Part name 部件名			Material 材料		QTY 数量		Remark 备注					
A4				 <b>台普</b> <b>ROCPCU</b>	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:		
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP92225P124RA		
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw		
A1					X	± 0.25	<b>ROCPCU TECHNOLOGY CO.,LTD</b>						
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR							
A		B		C		D		E		F		G	

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [Pushbutton Switches](#) category:*

*Click to view products by [ROCPU Technology](#) manufacturer:*

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)  
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)  
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)  
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)  
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)  
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)