



性能参数


1. Heating current: Ui: AC250V, Ith: 5A
发热电流: Ui: AC250V, Ith: 5A
2. Rated current:3A/DC36V
额定电流:3A/DC36V
3. Power-frequency withstand voltage:2000V1min
工频耐压:2000V1min
4. Insulation resistance:≥1000MΩ
绝缘电阻 :≥1000MΩ
5. Contact resistance:≤50mΩ
接触电阻 :≤50mΩ
6. Pressing stroke:3.00mm ± 0.10
按压行程:3.00mm ± 0.10
7. Contact stroke:1.50mm±0.10
接触行程 :1.50mm±0.10
8. welding temperature: 320 °C± 20 °C
焊接温度: 320 °C± 20 °C
9. Welding duration: Less than 3 seconds in duration
焊接时长: Less than 3 seconds in duration
10. Nut assembly torque:5-14N
螺帽装配力矩:5-14N
11. Protection level:IP67
防护等级:IP67
12. Explosion prevention level: IK10
防暴等级: IK10

连接形式

1. Welding temperature of wire: 320 ± 20 °C
线材焊接温度: 320±20°C
Wire welding duration: less than 3 seconds
线材焊接时长: 时长3秒以下
2. Can be used with dedicated connectors:
可配专用接插件使用:
 - 2.1 开关功能线材 Switch function wire: green (C) blue wire (NO) yellow wire (NC)
开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)
 - 2.2 LED functional wire: red wire positive pole black wire negative pole LED without distinguishing positive and negative poles
LED功能线材: 红线正极 黑线负极 LED不分正负极

13. Working environment temperature: -20 °C~+55 °C
工作环境温度: -20 °C~+55 °C
14. Compression torque: ≤ 3.00N
按压扭力: ≤3.00N
15. Electrical life: 100000 cycles
电气寿命: 100000 cycles
16. mechanical: 500000cycles
机械寿命: 500000cycles
17. Operation method:Self-locking type
操作方式: 自锁式
18. LED lamp power consumption: 20m以下
LED灯功耗: 20m以下
19. LED lamp lifespan: 40000h
LED寿命: 40000h
20. LED color: Red
LED颜色: 红色
21. LED Lamp Voltage: 24V
LED灯电压: 24V
22. NO reverse thrust foot torque: ≤30N
NO反推脚扭力: ≤30N

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP92509P124RA
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					

A	B	C	D	E	F	G		
材质参数								
10	luminous zone 发光区	PC 塑胶	1					
9	LEDpin LED引脚	Brass 黄铜	1		Silvering 镀银			
8	Base 底座	PA46	1					
7	Pin 引脚	Brass 黄铜	1		gold-plating 镀金			
6	Contact material 接触材质	silver alloy 银合金	1		Silvering 镀银			
5	LED Base LED基座	PC 塑胶	1					
4	Arm nut 固定螺帽	Brass 黄铜	1		nickeling 镀镍			
3	Oring O型圈	Silica gel 硅胶	1					
2	Housing 外壳	Aluminum alloy 铝合金	1		Oxidized/Black 氧化/黑色			
1	Key 按键	Aluminum alloy 铝合金	1		Oxidized/Black 氧化/黑色			
NO 序号	Part name 部件名	Material 材料	QTY 数量		Remark 备注			
A4				UNIT	MM	PROJECTED		PRODUCT NAME:
A3				DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP92509P124RA
A2				DATE	2019	APPROVAL B	ALEN	Https: www.rocpu.tw
A1				ROCPU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION	ISSUE	<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>			



COMMON TOLERANCE

X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [ROCPU Technology](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)