







A4				 ROCPCU	COMMON TOLERANCE X.XX ± 0.10 X.X ± 0.15 X ± 0.25 ANGULAR —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3			DRAWN BY			FUYUAN	CHECKED BY	COCO	MODEL NO:	TP93009P124RA	
A2			DATE			2019	APPROVAL	B	ALLEN	Https:	www.rocpcu.tw
A1			ROCPCU TECHNOLOGY CO.,LTD								
REV	DATE	REVISION	DESCRIPTION			ISSUE	Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission				

A	B	C	D	E	F	G				
1	性能参数		<p>13. Working environment temperature: -20 °C~+55 °C 工作环境温度: -20 °C~+55 °C</p> <p>14. Compression torque: ≤ 2.5N 按压扭力: ≤2.5N</p> <p>15. Electrical life: 100000 cycles 电气寿命: 100000 cycles</p> <p>16. mechanical: 500000cycles 机械寿命: 500000cycles</p> <p>17. Operation method:Self-locking type 操作方式: 自锁式</p> <p>18. LED lamp power consumption: 20m以下 LED灯功耗: 20m以下</p> <p>19. LED lamp lifespan: 40000h LED寿命: 40000h</p> <p>20. LED color: Red LED颜色: 红色</p> <p>21. LED Lamp Voltage: 24V LED灯电压: 24V</p> <p>22. NO reverse thrust foot torque: ≤30N NO反推脚扭力: ≤30N</p>							
2	<p>1. Heating current: Ui: AC250V, Ith: 5A 发热电流: Ui: AC250V, Ith: 5A</p> <p>2. Rated current:3A/DC36V 额定电流:3A/DC36V</p> <p>3. Power-frequency withstand voltage:2000V1min 工频耐压:2000V1min</p> <p>4. Insulation resistance:≥1000MΩ 绝缘电阻 :≥1000MΩ</p> <p>5. Contact resistance:≤50mΩ 接触电阻 :≤50mΩ</p> <p>6. Pressing stroke:3.00mm ± 0.10 按压行程:3.00mm ± 0.10</p> <p>7. Contact stroke:1.50mm±0.10 接触行程 :1.50mm±0.10</p> <p>8. welding temperature: 320 °C± 20 °C 焊接温度: 320 °C± 20 °C</p> <p>9. Welding duration: Less than 3 seconds in duration 焊接时长: Less than 3 seconds in duration</p> <p>10. Nut assembly torque:5-14N 螺帽装配力矩:5-14N</p> <p>11. Protection level:IP67 防护等级:IP67</p> <p>12. Explosion prevention level: IK10 防暴等级: IK10</p>									
3	连接形式		<p>1. Welding temperature of wire: 320 ± 20 °C 线材焊接温度: 320±20°C Wire welding duration: less than 3 seconds 线材焊接时长: 时长3秒以下</p> <p>2. Can be used with dedicated connectors: 可配专用接插件使用:</p> <p>2.1 Switch function wire: green (C) blue wire (NO) yellow wire (NC) 开关功能线材: 绿色(C) 蓝线 (NO) 黄线 (NC)</p> <p>2.2 LED functional wire: red wire positive pole black wire negative pole LED without distinguishing positive and negative poles LED功能线材: 红线正极 黑线负极 LED不分正负极</p>							
4										
5	A4		 台普 ROCPCU	COMMON TOLERANCE	UNIT	MM	PROJECTED		PRODUCT NAME:	
	A3				DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP93009P124RA	
	A2			X.XX	± 0.10	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
	A1			X.X	± 0.15	ROCPCU TECHNOLOGY CO.,LTD				
	REV	DATE		X	± 0.25					
		REVISION DESCRIPTION	ISSUE	ANGULAR	Copies are issued in strict confidence and shall not be reproduced or copied,or used as the basic of manufacture or sale of apparatus without permission					
	A	B	C	D	E	F	G			

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
10	luminous zone 发光区	PC 塑胶	1	
9	LEDpin LED引脚	Brass 黄铜	1	Silvering 镀银
8	Base 底座	PA46	1	
7	Pin 引脚	Brass 黄铜	1	gold-plating 镀金
6	Contact material 接触材质	silver alloy 银合金	1	Silvering 镀银
5	LED Base LED基座	PC 塑胶	1	
4	Arm nut 固定螺帽	Brass 黄铜	1	nickeling 镀镍
3	Oring O型圈	Silica gel 硅胶	1	
2	Housing 外壳	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色
1	Key 按键	Aluminum alloy 铝合金	1	Oxidized/Black 氧化/黑色

A4				 台普 ROCPCU	COMMON TOLERANCE		UNIT	MM	PROJECTED		PRODUCT NAME:
A3					X.XX	± 0.10	DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP93009P124RA
A2					X.X	± 0.15	DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw
A1					X	± 0.25	ROCPCU TECHNOLOGY CO.,LTD				
REV	DATE	REVISION	DESCRIPTION		ISSUE	ANGULAR					
	A		B		C		D	E	F	G	

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Pushbutton Switches](#) category:

Click to view products by [ROCPU Technology](#) manufacturer:

Other Similar products are found below :

[8971K1133](#) [LW2L-M1C20M-A](#) [01-153.025](#) [M22-D-R-GB0/K11](#) [67021K512](#) [701PB580](#) [7199K101](#) [810K12910](#) [810KSV30B](#) [FLT 2U EE](#)
[01A](#) [MML21EA2ADK](#) [MML21KA3ABK](#) [MML23KW3AA01W](#) [8418K2](#) [8442K3](#) [8450K1](#) [860K11911T01A](#) [861901](#) [861K11911T01A07](#)
[861K13810T00A14](#) [861K13911](#) [8646AB6X718UL](#) [9533CD4+U574+U4922](#) [99-450.837](#) [99-453.837](#) [A2PMA1X03EC56](#) [A3A-7310](#) [A3A-](#)
[7340](#) [12037A2ULCSA](#) [1203A2UL](#) [ABGW410-R](#) [1211390004](#) [ABN400-R](#) [121382](#) [1213C3](#) [HE3B-M2](#) [1211500044](#) [121194](#) [1212MRA](#)
[1232A6NF](#) [121489](#) [1223A2ULCSA](#) [D5P-MT4](#) [13435AG](#) [13445AD29GX768](#) [AG23-L2](#) [AH165-2SGLG1TE3](#) [AH165-TGFY22](#) [AH165-](#)
[TGL5Y11E3](#) [AH165-TGLR11AA3](#)