SLR-342 series


LED, flat disk type, direct mount

Dimensions (Units : mm)

The SLR-342 series LEDs are small, reflecting, high brightness single color LEDs.

Features

- single LED per package
- diameter of lens = 3.1 mm
- height as low as 5.2 mm
- mounting pitch as small as 2.5 mm
- available in red, orange, yellow and green with choice of tinted diffused or tinted non-diffused lens
- available on tape for mounting by an automatic machine



Selection guide

| Part no. | SLR-342VR | SLR-342DU | SLR-342YY | SLR-342MG |
|--------------------|---------------------|---------------------|---------------------|---------------------|
| Color & wavelength | Red, 650 nm | Orange, 610 nm | Yellow, 585 nm | Green, 563 nm |
| Lens | Tinted diffused | Tinted diffused | Tinted diffused | Tinted diffused |
| Availability | standard | standard | standard | standard |
| Part no. | SLR-342VC | SLR-342DC | SLR-342YC | SLR-342MC |
| Color & wavelength | Red, 650 nm | Orange, 610 nm | Yellow, 585 nm | Green, 563 nm |
| Lens | Tinted non-diffused | Tinted non-diffused | Tinted non-diffused | Tinted non-diffused |
| Availability | standard | standard | standard | standard |

Absolute maximum ratings ($T_a = 25^{\circ}C$)

| Parameter | | Symbol | Limits | Unit | Conditions |
|-----------------------|--------------|------------------|------------|------|----------------------------|
| Danna dia sia stisa | MG & MC type | | 75 | mW | |
| Power dissipation | All others | P _d – | 60 | mW | |
| Forward current | MG & MC type | l _F | 25 | mA | |
| | All others | | 20 | mA | |
| Peak forward current | | I _{FP} | 60 | mA | Pulse width 1 ms, duty 20% |
| Reverse voltage | | V _R | 3 | V | |
| Operating temperature | | T _{opr} | -25 ~ +85 | °C | |
| Storage temperature | | T _{stg} | -30 ~ +100 | °C | |

166




Light Emitting Diodes

| • | | | | • | | | |
|---------------------------------|-----------------|-------------------|-----|--|-----|------|------------------------|
| Par | ameter | Symbol | Min | Typical | Max | Unit | Conditions |
| Forward | Red Orange | V | | 2.0 | 3.0 | v | I _F = 10 mA |
| voltage | Yellow Green | V _F | | 2.1 | 5.0 | | |
| Reverse cu | irrent | I _R | | | 10 | μΑ | V _R = 3 V |
| Peak wave | length | λ _p | | Red 650 Orange 610 Yellow 585 Green 563 | | nm | I _F = 10 mA |
| Spectral ha | lf-width | Δλ | | 40 | | nm | $l_F = 10 \text{ mA}$ |
| Emission power half angle | Non-diffused | | | 40 | | deg | |
| | Diffused | 2θ _{1/2} | | 40 | | | |
| | | | | | | | <u> </u> |

Electro-optical characteristics ($T_a = 25^{\circ}C$)


Figure 1 Luminous intensity vs wavelength



Luminous intensity

| Part no. | Color | λρ | Min | Typical | Max | Unit | Conditions |
|-----------|--------|---------|-----|---------|-----|------|----------------------------|
| SLR-342VR | Red | 650 | 3.6 | 10.0 | | mcd | |
| SLR-342VC | | 050 | 6.6 | 16.0 | | mcd | |
| SLR-342DU | Orange | ge 610 | 3.6 | 10.0 | | mcd | - |
| SLR-342DC | | | 5.6 | 16.0 | | mcd | For I _F = 10 mA |
| SLR-342YY | Yellow | 585 | 2.2 | 6.3 | | mcd | |
| SLR-342YC | | | 5.6 | 16.0 | | mcd | |
| SLR-342MG | Green | een 563 | 5.6 | 16.0 | | mcd | |
| SLR-342MC | | | 9.0 | 25.0 | | mcd | |


Light Emitting Diodes




ROHM

L

Light Emitting Diodes









Light Emitting Diodes

ROHM




SLR-342 series Direct-mount LED lamps, flat disk and reflector type






ROHM



Light Emitting Diodes

rohm

SLR-342 series Direct-mount LED lamps, flat disk and reflector type



172

rohm




Figure 29 Directional pattern (green)

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Standard LEDs - Through Hole category:

Click to view products by ROHM manufacturer:

Other Similar products are found below :

LTL-10254W LTL-1214A LTL-3251A LTL-4262N LTL-433P LTL-5234 LTL87HTBK LTW-87HD4B HLMP-EL30-PS0DD 1L0532V23G0TD001 NSPW500CS NTE30036 NTE30044 NTE30059 NTE3020 LD CQDP-1U3U-W5-1-K LO566UHR3-70G-A3 LP379PPG1C0G0300001 SLX-LX3044GD SLX-LX3044ID SLX-LX3044YD 1.90690.3330000 SSS-LX4673ID-410B 1L0532Y24I0TD001 264-7SYGD/S530-E2 HLMP-1301-G00FG HLMP1385 LTL-10224W LTL-1224A LTL-1234A LTL-2251AT LTL-403HR LTL-4222 LU7-E-B 4380H1 TLHY44K1L2 HLMP-3962-F0002 HLMP-GG15-R0000 323-2SURD/S530-A3 L53SRC/E-Z L-7679C1ZGC 4302T1-5V 4306D23 4363D1/5 WP1503SRC/J4 WP153GDT WP153YDT WP1543SGC WP1543SURC WP53MGD