



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to Longwipe SMP, Rosenberger 17S000-000

Documents

N/A

Material and plating

Connector parts

Center contact
Outer contact
Dielectric

Material

CuBe
CuBe
PTFE

Plating

AuroDur®, gold plated
AuroDur®, gold plated

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/05.10/6.0

Technical Data Sheet

Rosenberger

ADAPTOR

Longwipe SMP Jack - Longwipe SMP Jack

17K117-K18L5

Electrical data

| | |
|---------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 6 GHz |
| Return loss | ≥ 26 dB, DC to 4 GHz |
| Insertion loss | $\leq 0.05 \times \sqrt{f(\text{GHz})}$ dB, DC to 18 GHz |
| Insulation resistance | ≥ 5 G Ω |
| Center contact resistance | ≤ 6.0 m Ω |
| Outer contact resistance | ≤ 2.0 m Ω |
| Test voltage | 500 V rms |
| Working voltage | 335 V rms |
| Contact Current | 1.2A DC max. |

Mechanical data

| | |
|----------------------------------|-------------|
| Mating cycles | |
| if mating part is smooth bore | ≥ 1000 |
| if mating part is limited detent | ≥ 500 |
| if mating part is full detent | ≥ 100 |
| Center contact captivation | ≥ 5 N |
| Engagement force | |
| - smooth bore | 9 N max. |
| - limited detent | 45 N max. |
| - full detent | 68 N max. |
| Disengagement force | |
| - smooth bore | 2.2 N min. |
| - limited detent | 9 N min. |
| - full detent | 22 N min. |

Environmental data

| | |
|---------------------|--------------------------------------|
| Temperature range | -65°C to +155°C |
| Thermal shock | MIL-STD-202, Method 107, Condition B |
| Vibration | MIL-STD-202, Method 204, Condition B |
| Shock | MIL-STD-202, Method 213, Condition A |
| Moisture resistance | MIL-STD-202, Method 106 |
| RoHS | compliant |

Tooling

N/A

Suitable cables

N/A

Weight

0.41 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-----------|----------|------|---------------------------|--|---------------|
| A. Barbet | 17.03.16 | A. Barbet | 12.04.18 | a00 | 18-s152 | R. Kumar | 12.04.18 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | | Tel. : +49 8684 18-0 Email : info@rosenberger.de | |
| | | | | | | | Page 2 / 2 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Adapters - In Series](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[5918-1103-000](#) [5919-9503-000](#) [651A505](#) [R114703000W](#) [R142720000W](#) [R222M40050](#) [R223703180](#) [HRM-513S](#) [KC-79-179](#) [KN-99-14](#)
[252169-75](#) [252186](#) [R142710000](#) [R142723000](#) [R161703000](#) [R161715000W](#) [R405005000](#) [KA-99-56](#) [KC-59-270](#) [KC-59-284](#) [KC-79-131](#)
[KC-99-35](#) [KC-99-40](#) [756-18-9](#) [84004734](#) [R164705000](#) [R222M40080](#) [R124720003W](#) [R142723000W](#) [R222M40060](#) [755-93-7](#) [3094317](#)
[5917-9103-000](#) [920-56](#) [R125704001](#) [R143753000W](#) [R143720000](#) [9176-9113-000](#) [R222M40107](#) [R114009000](#) [R124720003](#) [AD48](#) [ADP-](#)
[NF-NF](#) [R142562290](#) [ADAPT/SMAM/SMAM/RP](#) [CT3388](#) [CT2765](#) [2477400-1](#) [142-0901-431](#) [53BK501-K00N1](#)