

RF_35/09.14/6.2

Technica	al Data Sheet		Rosenberger		
Mini-SMP	Adaptor Jack - Jack		18K118-K04L5		
Electrical data Impedance Frequency Return loss Insertion loss Insulation resistance Center contact resistance Outer contact resistance Working voltage (at sea level) (at 70000 feet) Mating cycles if mating part is smooth bore if mating part is full detent Center contact captivation Engagement force - smooth bore - full detent Disengagement force - smooth bore - full detent		50 Ω DC to 65 GHz ≥ 23 dB, DC to 18 GHz ≥ 15 dB, 18 to 50 GHz ≤ 0.05 x $\sqrt{f(GHz)} dB$ ≥ 5 GΩ ≤ 6.0 mΩ ≤ 2.0 mΩ 325 V rms 125 V rms 2 500 ≥ 100 ≥ 7 N 11 N typical 19 N typical 11 N typical 29 N typical			
Environmental data Temperature range Thermal shock Vibration Shock Moisture resistance Climatic Category RoHS Tooling		-55°C to +155°C MIL-STD-202, Method 107, Condition B MIL-STD-202, Method 204, Condition A MIL-STD-202, Method 213, Condition A MIL-STD-202, Method 106 IEC 60068 55/155/21 compliant			

Suitable cables

N/A

Weight Weight

0.16 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



	Draft	Date	Approved	Date		Rev.	Engineering change number	Name	Date
	Rong Fang	19.07.06	Chr. Janßen	20.10.20		e00	20-1927	S. Huber-Siegl	20.10.20
	Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel. : +49 8684 18-0			Page	
					Email : <u>info@rosenberger.de</u>			2/2	

RF_35/09.14/6.2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for RF Adapters - In Series category:

Click to view products by Rosenberger manufacturer:

Other Similar products are found below :

 5916-1103-603
 5919-1503-000
 651A505
 82-5552
 9030-9523-502
 PN2C
 A0407000
 R114703000W
 R125771001
 R141710000W

 R141723161
 R141730000
 R143730700
 R143770000
 R161703000W
 R161791530W
 R201705000
 R222705200

 R222M40010W
 R223703180
 R316754000
 R405006000
 R443162000
 AD78TL
 HRM-513S
 1996352-2
 2157155-1
 252169-75
 AD158

 2101130-1
 252186
 R114704000W
 R114720000W
 R125705001
 R125705701
 R125771000
 R127704001
 R127.870.001

 R127872001
 R141717000
 R142710000
 R142723000
 R143703000
 R143704000
 R143705700
 R161715000W
 R161771000W
 R176754000