



All dimensions are in mm; tolerances according to ISO 2768 m-H

**Interface**

According to MIL-STD-348

**Documents**

PCB layout B 30

**Material and plating**

**Connector parts**

|                |       |
|----------------|-------|
| Center contact | Brass |
| Outer contact  | Brass |
| Body           | Brass |
| Dielectric     | PTFE  |

**Plating**

AuroDur®, gold plated  
AuroDur®, gold plated  
AuroDur®, gold plated

Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09.14/6.2

**Electrical data**

|                           |                                  |
|---------------------------|----------------------------------|
| Impedance                 | 50 Ω                             |
| Frequency                 | DC to 26.5 GHz                   |
| Return loss               | ≥ 21 dB, DC to 6 GHz             |
| Insertion loss            | ≤ 0.05 x √f(GHz) dB, Dc to 6 GHz |
| Insulation resistance     | ≥ 5 GΩ                           |
| Center contact resistance | ≤ 6.0 mΩ                         |
| Outer contact resistance  | ≤ 2.0 mΩ                         |
| Test voltage              | 500 V rms                        |
| Working voltage           | 335 V rms                        |
| Contact Current           | 1.2A DC max.                     |

- VSWR in application depends decisive on PCB layout -

**Mechanical data**

|                             |           |
|-----------------------------|-----------|
| Mating cycles               | ≥ 500     |
| Center contact captivation: | ≥ 7 N     |
| Engagement force            |           |
| - limited detent            | 45 N max. |
| Disengagement force         |           |
| - limited detent            | 9 N min.  |

**Environmental data**

|                            |                                      |
|----------------------------|--------------------------------------|
| Temperature range          | -65°C to +155°C                      |
| Thermal shock              | MIL-STD-202, Method 107, Condition B |
| Vibration                  | MIL-STD-202, Method 204, Condition B |
| Shock                      | MIL-STD-202, Method 213, Condition A |
| Moisture resistance        | MIL-STD-202, Method 106              |
| Max. soldering temperature | IEC 61760-1, +260°C for 10 sec.      |
| RoHS                       | compliant                            |

**Tooling**

N/A

**Suitable cables**

N/A

**Weight**

|        |            |
|--------|------------|
| Weight | 1.85 g/pce |
|--------|------------|

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF\_35/09.14/6.2

|               |          |             |          |      |                           |                |          |
|---------------|----------|-------------|----------|------|---------------------------|----------------|----------|
| Draft         | Date     | Approved    | Date     | Rev. | Engineering change number | Name           | Date     |
| Inge Mühlauer | 24.08.04 | Chr. Janßen | 29.10.20 | h00  | 20-1927                   | S. Huber-Siegl | 29.10.20 |

|  |  |  |  |  |  |               |  |
|--|--|--|--|--|--|---------------|--|
| Rosenberger Hochfrequenztechnik GmbH & Co. KG<br>P.O.Box 1260 D-84526 Tittmoning Germany<br><a href="http://www.rosenberger.de">www.rosenberger.de</a> |  |  |  | Tel. : +49 8684 18-0<br>Email : <a href="mailto:info@rosenberger.de">info@rosenberger.de</a> |  | Page<br>2 / 2 |  |
|--|--|--|--|--|--|---------------|--|

## X-ON Electronics

Largest Supplier of Electrical and Electronic Components

*Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:*

*Click to view products by [Rosenberger](#) manufacturer:*

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)