



1:1

All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to CECC 22220, IEC 61169-36

Documents

Assembly instruction 29 B

Material and plating

Connector parts

| | | |
|----------------|-----------------|-------|
| Center contact | Material | Brass |
| Outer contact | | CuBe |
| Dielectric | | PTFE |

Plating

AuroDur®, gold plated
AuroDur®, gold plated

Electrical data

| | |
|---------------------------|--|
| Impedance | 50 Ω |
| Frequency | DC to 6 GHz |
| Return loss | ≥ 30 dB, DC to 1 GHz ≥ 22 dB, 1 to 3 GHz ≥ 20 dB, 3 to 5 GHz |
| Insertion loss | ≤ 0.05 x √f(GHz) dB |
| Insulation resistance | ≥ 1 GΩ |
| Center contact resistance | ≤ 5.0 mΩ |
| Outer contact resistance | ≤ 2.5 mΩ |
| Test voltage | 750 V rms |
| Working voltage | 335 V rms |
| Contact Current | 1.5A DC max. |

- Limitations are possible due to the used cable type -

Mechanical data

| | |
|----------------------------|-----------------------|
| Mating cycles | ≥ 500 |
| Center contact captivation | ≥ 10 N |
| Engagement force | ≤ 25 N |
| Disengagement force | 8 N min. to 20 N max. |

Environmental data

| | |
|---------------------|-----------------------------|
| Temperature range | -55°C to +155°C |
| Thermal shock | CECC 22 220, Chapter 4.6.7 |
| Vibration | CECC 22 220, Chapter 4.6.3 |
| Corrosion | CECC 22 220, Chapter 4.6.10 |
| Moisture resistance | CECC 22 220, Chapter 4.6.6 |
| RoHS | compliant |

Tooling

N/A

Suitable cables

UT 85-M17, RTK-FS-085

Weight

Weight 0.74 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



Dieses Dokument ist urheberrechtlich geschützt • This document is protected by copyright • Rosenberger Hochfrequenztechnik GmbH & Co. KG

RF_35/09.14/6.2

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|--|----------|-------------|----------|------|---------------------------|--|---------------|
| König A. | 12.01.08 | Chr. Janßen | 04.11.20 | c00 | 20-1927 | S. Huber-Siegl | 04.11.20 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de | | | | | | Tel. : +49 8684 18-0 Email : info@rosenberger.de | |
| | | | | | | | Page 2 / 2 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)