
TECHNICAL DATA SHEET

Rosenberger®

N 50 Ω ATTENUATOR PLUG/JACK

53AS120-K10N3



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

IEC 60169-16, MIL-PRF-39012, CECC 22210

Documents

N/A

PTFE

ALN

Material and plating

Connector parts

Center contact - plug Center contact - jack Outer contact

Coupling nut Heatsinks

Dielectric Substrate

Material

Plating

Brass Gold, min. 1.27 µm, over nickel Beryllium copper Gold, min. 1.27 μ m, over nickel

Flash white bronze over silver(e.g. Optargen®) Brass Flash white bronze over silver(e.g. Optargen®) Brass Αl

Black anodized

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de

Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de Page

TECHNICAL DATA SHEET



2/2

N 50 Ω ATTENUATOR PLUG/JACK

53AS120-K10N3

Electrical data

Impedance 50 Ω

Frequency DC to 10 GHz

Return loss \geq 26.4 dB, DC to 2 GHz \geq 21.2 dB, 2 GHz to 5 GHz

≥ 14.0 dB, 5 GHz to 10 GHz

Attenuation 10 dB

Tolerances $\leq \pm 0.3$ dB, DC to 2 GHz

 \leq \pm 0.5 dB, 2 GHz to 4 GHz \leq \pm 1.0 dB, 4 GHz to 10 GHz

 $\begin{array}{ll} \text{Center contact resistance} & \leq 1 \text{ m}\Omega \\ \text{Outer contact resistance} & \leq 0.25 \text{ m}\Omega \\ \text{Power handling} & 20 \text{ W at } 25^{\circ}\text{C} \\ \end{array}$

derated linearity to 0 Watts at 125°C

Mechanical data

 $\begin{array}{lll} \text{Mating cycles} & \text{min. 500} \\ \text{Coupling nut retention} & \geq 450 \text{ N} \\ \text{Center contact captivation} & \geq 28 \text{ N} \\ \text{Coupling test torque} & \text{max. 1.7 Nm} \\ \text{Recommended torque} & 0.7 \text{ Nm to 1.1 Nm} \\ \end{array}$

Environmental data

Temperature range -65°C to +125°C

2002/95/EC (RoHS) compliant

Tooling

N/A

Suitable cables

www.rosenberger.de

N/A

Packing

Standard 1 pce in air cushion bag

Weight 270 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date		Rev.	Engineering change number	Name	Date
Kerstin Herzog	05/08/05	Frank Weiß	11/12/07		b00	07-0838	Kerstin Hobrak	11/12/07
Rosenberger Hochfrequenztechnik GmbH & Co. KG P. O. Box 1260								Page

email: <u>info@rosenberger.de</u>

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Attenuators - Interconnects category:

Click to view products by Rosenberger manufacturer:

Other Similar products are found below:

```
R411803119 R413806115 R413808000 R413810115 R413850115 R414510000 R414701000 BNC-13 R411800121 R411801121 R412412124 R412450000 R413800000 R413805000 R413830000 R413840115 R414730000 R415420000 R415703000 R416010000 R420003110 R411801000 R411815121 R413305000 R413801000 R414520000 R411808121 R412500124 R412414124 R412501124 HMC-C584 R413802000 R412400124 R411700124 R417310130 R411801119 R412419124 R411703124 R412401124 R443131000 R417130110 R414700000 R414505000 R411802119 R417720128 R420706110 R413811000 R413803115 R414501000 R417903128
```