



All dimensions are in mm; tolerances according to ISO 2768 m-H

Interface

According to

IEC 60169-10, CECC 22130, MIL-PRF-39012

Documents

PCB layout

B 30

Material and plating

Connector parts

Center contact
Outer contact
Dielectric

Material

Brass
Brass
PTFE

Plating

AuroDur®, gold plated
AuroDur®, gold plated

Electrical data

| | |
|---------------------------|---|
| Impedance | 50 Ω |
| Frequency | DC to 4 GHz |
| Return loss | ≥ 25 dB, DC to 1 GHz ≥ 18 dB, 1 to 4 GHz |
| Insertion loss | ≤ 0.1 x √f(GHz) dB |
| Insulation resistance | ≥ 1x10 ³ MΩ |
| Center contact resistance | ≤ 5 mΩ |
| Outer contact resistance | ≤ 2.5 mΩ |
| Test voltage | 750 V rms, 50 Hz, at sea level |
| Working voltage | ≤ 250 V rms, 50 Hz, at sea level |
| Contact current | 1.5 A DC typ. |
| RF-leakage | ≥ 55 dB up to 1 GHz |

- Connector only, VSWR in application depends decisive on PCB layout -

Mechanical data

| | |
|-----------------------------------|-----------------------|
| Mating cycles | ≥ 500 |
| Center contact captivation: axial | ≥ 10 N |
| Engagement force | ≤ 63 N |
| Disengagement force | 8 N min. to 63 N max. |

Environmental data

| | |
|----------------------------|---------------------------------|
| Temperature range | -55°C to +155°C |
| Thermal shock | MIL-STD-202, Meth. 107, Cond. B |
| Vibration | MIL-STD-202, Meth. 204, Cond. B |
| Corrosion | MIL-STD-202, Meth. 101, Cond. B |
| Moisture resistance | MIL-STD-202, Meth. 106 |
| Max. soldering temperature | IEC 61760-1, +260°C for 10 sec. |
| RoHS | compliant |

Tooling

N/A

Suitable cables

N/A

Weight

Weight 0.7 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

For the installation of the electrotechnical equipment, particular electrotechnical expertise is required.



| | | | | | | | |
|--|----------|-------------|----------|------|--|----------------|---------------|
| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
| König A. | 25.10.06 | Chr. Janßen | 08.02.21 | e00 | 20-1927 | S. Huber-Siegl | 08.02.21 |
| Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.com | | | | | Tel. : +49 8684 18-0 Email : info@rosenberger.com | | Page 2 / 2 |

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [980-8666-005](#) [1200690078](#) [1-201144-1](#) [R107003010W](#) [R110A172100](#)