Technical Data Sheet

Rosenberger

7/16

Calibration Kit Industrial Version

60CK010-150



Picture may differ from original product

Contents

Device	Part number	Quantity	Calibration Option ^a	
Open circuit plug	60S12L-000S3	1	FC / AC	
Open circuit jack	60K12L-000S3	1	FC / AC	
Short circuit plug	60S12S-000S3	1	FC / AC	
Short circuit jack	60K12S-000S3	1	FC / AC	
Calibration load plug	60S150-C10S3	1	FC / AC	
Calibration load jack	60K150-C10S3	1	FC / AC	
Calibration adaptor plug/plug	60S121-S20S3	1	FC / AC	
Calibration adaptor jack/jack	60K121-K20S3	1	FC / AC	
Combi wrench	60W013-000	1	-	
Torque wrench	60W000-003	1	FC	

a. See "Declaration of calibration options" for explanation.

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de

Page

1/3

Documentation

This kit is delivered with

USB-Stick

Standard Definitions as data files for Vector Network Anaylzer Families PNA (Keysight/Agilent) and ZVA (Rohde&Schwarz). Calibration Certificate as PDF-file.

Standard Definitions Cards

Printed Standard Definitions that can be used on nearly all Vector Network Analyzers.

Kit Info Card

Handling precautions and information for installing Standard Definitions on a Vector Network Analyzer.

Calibration Certificate

Details see "Declaration of calibration options"

• Operating Manual

Electrical specifications

This specification covers electrical key values for the main calibration standards of the calibration kit. Specific datasheets are available for each component among the part number.

Calibration standard	Frequency	Parameter	Specification	
Opens ^b	DC to ≤ 4 GHz	Error from	≤ 1.0°	
(plug and jack)	> 4 GHz to ≤ 8 GHz	Nominal Phase	≤ 1.5°	
Shorts ^b (plug and jack)	DC to ≤ 4 GHz	Error from	≤ 1.0°	
	> 4 GHz to ≤ 8 GHz	Nominal Phase	≤ 1.5°	
Calibration loads (plug and jack)	DC to ≤ 4 GHz > 4 GHz to ≤ 8 GHz	Return Loss	≥ 40 dB ≥ 38 dB	
Calibration adaptors (plug/plug)	DC to ≤ 4 GHz > 4 GHz to ≤ 8 GHz	Return Loss	≥ 40 dB ≥ 36 dB	
Calibration adaptors	DC to ≤ 4 GHz	Return Loss	≥ 38 dB	
(jack/jack)	> 4 GHz to ≤ 8 GHz		≥ 34 dB	

b. The specifications for opens and shorts are given as allowed deviation from nominal model as defined in calibration certificate included with your kit.

Rosenberger Hochfrequenztechnik GmbH & Co. KG
P.O.Box 1260 D-84526 Tittmoning Germany
www.rosenberger.de

Tel. : +49 8684 18-0
Fax : +49 8684 18-499
Email : info@rosenberger.de

Page

2/3

Technical Data Sheet Rosenberger 7/16 Calibration Kit Industrial Version Calibration Kit 60CK010-150

Declaration of calibration options

Factory Calibration

Standard delivery for this kit includes a Factory Calibration. All devices marked with "FC" in the Content table above are reported in a Calibration Certificate with their individual calibration results, traceable to national / international standards. Model based definitions of the calibration standards are reported in Agilent/Keysight, Rohde & Schwarz and Anritsu compatible VNA format.

Accredited Calibration

Optional this kit can be delivered with an Accredited Calibration (DAkkS) having the highest confidence in the traceability. All devices marked with "AC" in the Content table above are reported in a DAkkS Calibration Certificate with their individual calibration results in a complex format, traceable to national / international standards. Model based definitions of the calibration standards are reported in Agilent/Keysight, Rohde & Schwarz and Anritsu VNA format as well as in dense data sets needed for data based calibration kits. The uncertainties are a little bit smaller than in a Factory Calibration.

All devices marked with "FC" only cannot be calibrated under accreditation. They are factory calibrated as described above.

For further, more detailed information see application note AN001 on the Rosenberger homepage.

Calibration interval

Recommendation

12 months

Recommended accessories

- Rosenberger Test Port Adaptor
- Rosenberger VNA Test cable kit and Microwave Cable Assemblies
- Rosenberger Gauge Kit 60GK0KS-010

For further, more detailed information please visit our homepage www.rosenberger.com.

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Martin Moder	12.10.15	H.Babinger	01.08.16	b00	16-1267	M. Knoll	01.08.16

Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de Tel. : +49 8684 18-0 Fax : +49 8684 18-499 Email : info@rosenberger.de Page 3/3

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for Calibration Equipment category:

Click to view products by Rosenberger manufacturer:

Other Similar products are found below:

700P27 AX-C830 AKT8R112100 AKT4R1121001 AKT4R1122001 AR604/P FLUKE-700G08 461750 AX-C850 RT-820 FLUKE 709
FLUKE-805 AKT4R111100 AKT4R111200 AKT7111100J AKT7212100J AKT8R111100 REF2510R K39-LCRR 412355A 461831
461895 461920 480400 480403 PRC15 PRC20 PRC30 700P02 700P27EX 700P29 FLUKE-714B/EN FLUKE-789 FLUKE BP7235
U086 U087 03K30R-MSOTS3 18CK010-150 19CK010-150 P5514-70M P5515-140M 12890 TACH-10 461950 461825 461830 461891
350456 CAL73 DCS025