

All dimensions are in mm; tolerances according to ISO 2768 m-H
 EMC-screening must be assured by chassis compartment. Control box manufacturer is responsible for EMC-screening.

Interface

According to RN 059-01

Documents

| | |
|----------------------|----------------------------|
| Assembly instruction | acc. D4V016 |
| PCB layout | acc. MB_285 |
| Pinning instruction | RN 053-01 |
| Test specification | RN 061-01 |
| Blister packaging | Pick&Placeable (shape tbd) |

Material and plating

Connector parts

| | |
|---------------------------|------------|
| Center contacts | Brass |
| Outer contact (Interface) | Brass |
| Outer contact (PCB) | Zinc Alloy |
| Dielectric | LCP |
| Housing | PA 6T/66 |

Plating

Gold, 0.15 µm
 Nickel, 2.5-5 µm
 Tin, 2-5 µm

HSD STRAIGHT PLUG FOR
PCB**D4S12H-40MA5-Y****Electrical data**

| | |
|--|--|
| Impedance, differential mode | 100 Ω differential signalling, for one pair or quad cable shielded |
| Frequency | DC to 2.0 GHz |
| Return loss | ≥ 20 dB to 1.0 GHz ≥ 17 dB to 2.0 GHz |
| Insertion loss | ≤ 0.1 dB @ 1.0 GHz |
| Skew (between signal contacts) | ≤ 5 psec. |
| Nearend-Crosstalk | ≤ 30 dB |
| Farend-Crosstalk | ≤ 35 dB |
| Insulation resistance | $\geq 1 \times 10^3$ M Ω |
| Signal contact resistance | ≤ 10 m Ω |
| Outer contact resistance | ≤ 7.5 m Ω |
| Test voltage | 250 V rms |
| Working voltage | 100 V rms |
| Power current | ≤ 1.5 A DC |
| RF-leakage (shielding effectiveness) | ≥ 75 dB up to 1 GHz (IEC 62153-4-7) ≥ 65 dB up to 2 GHz (IEC 62153-4-7) |

Mechanical data

| | |
|-----------------------|--------------|
| Mating cycles | ≥ 25 |
| Engagement force | ≤ 30 N |
| Disengagement force | ≥ 5 N |
| Retention force latch | ≥ 110 N |
| Coding efficiency | ≥ 80 N |

Environmental data

| | |
|--------------------------|-----------------------------------|
| Temperature range | -40°C to +105°C |
| Thermal shock | DIN IEC 60068-2-14 Test NA |
| Temperature and humidity | USCar 2 – 4 5.6.2 |
| Vibration (Random) | DIN IEC 60068-2-64 |
| Mechanical Shock | DIN IEC 60068-2-27 |
| High-Temp. Exposure | DIN IEC 60068-2-2 |
| Soldering profile | acc. to IEC 60068-2-58; Group 3&4 |
| 2002/95/EC (RoHS) | compliant |

Tooling

N/A

Suitable cables








N/A

Packing

| | |
|----------|----------------------|
| Standard | 150 pcs on tape&reel |
| Weight | 2.7 g/ |

Coding

Part Number has to be accomplished by codification

| Coding | Plug | Colour | RAL | Part-Number |
|--------|---|-----------|-----------|----------------|
| A |  | black | sim. 9005 | D4S12H-40MA5-A |
| B |  | white | sim. 9001 | D4S12H-40MA5-B |
| C |  | blue | sim. 5005 | D4S12H-40MA5-C |
| D |  | bordeaux | sim. 4004 | D4S12H-40MA5-D |
| E |  | green | sim. 6002 | D4S12H-40MA5-E |
| F |  | brown | sim. 8011 | D4S12H-40MA5-F |
| Z |  | waterblue | sim. 5021 | D4S12H-40MA5-Z |

| Draft | Date | Approved | Date | Rev. | Engineering change number | Name | Date |
|----------------|----------|----------------|----------|------|---------------------------|--------|----------|
| Thomas Höfling | 20/04/11 | Thomas Höfling | 11/08/11 | a00 | 11-s358 | A.Kott | 11/08/11 |

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Connectors / Coaxial Connectors](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[8915-1511-000](#) [89674-0827](#) [6001-7071-019](#) [6002-7051-003](#) [6002-7551-202](#) [6059674-1](#) [619550-1](#) [630059-000](#) [M39030/3-01N](#) [6500-7071-046](#) [6769](#) [CX050L2AQ](#) [7002-1541-010](#) [7002-1542-011](#) [7004-1512-000](#) [7009-1511-004](#) [7010-1511-000](#) [7029-1511-060](#) [7101-1541-010](#) [7101-1571-002](#) [7145-1521-002](#) [7203-1571-003](#) [7209-1511-011](#) [7210-1511-015](#) [7210-1511-019](#) [73137-5015](#) [73216-2241](#) [73404-2300](#) [7405-1521-005](#) [7405-1521-802](#) [8527](#) [8547](#) [FS11V](#) [877931](#) [8808-1511-001](#) [9049-9513-000](#) [9074-9513-000](#) [9101-9573-002](#) [910A205F](#) [9130-9573-002](#) [PL11SC-026](#) [PL375-33](#) [PL40-5](#) [PL74C-221](#) [PL75MC-217](#) [PL803-7](#) [980-8666-005](#) [1200690078](#) [1-201144-1](#) [R107003010W](#)