



All dimensions are in mm; tolerances acc. to ISO 2768 m-H

Interface

According to

Rosenberger EBC™

Documents

Application note

EBC

Material and plating

Connector parts

Center contact
Outer contact
Dielectric

Material

Cu
Brass
PTFE

Plating

Silver ≥ 1,5 µm
Flash white bronze over silver(e.g. Optargen®)

Electrical data

Impedance	50 Ω
Frequency	DC to 8 GHz
Return loss	≥ 26 dB @ DC to 6 GHz ¹⁾
Insertion loss	≤ 0.05 x √f [GHz] dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≤ 10 mΩ
Outer contact resistance	≤ 5 mΩ
Test voltage (at sea level)	500 V rms
Working voltage (at sea level)	335 V rms
Power handling (sea level, VSWR 1.0)	100 W @ 3.5 GHz @ 105°C ²⁾
Contact Current	≤ 2A DC
Screening attenuation - Interface	≥ 50 dB up to 4 GHz
Intermodulation (3 rd order)	≥ 160 dBc (2 x 43 dBm)

1) Dependent on axial misalignment

2) Power value is dominated by the application

Mechanical data

Mating cycles	≥ 50
Center contact captivation	≥ 5 N
Engagement force	
-Limited detent	≤ 35N (typ.30N)
-smooth bore	≤ 12N
Disengagement force	
-Limited detent	≤ 12N
-smooth bore	≤ 5N
Working range	1.6 mm (± 0.8 mm)
Radial misalignment	max. 4°
Pitch	≥ 6.9 mm

Environmental data

Temperature range	-55 °C to +105 °C
Thermal shock	MIL-STD-202, Method 107, Condition B
Climatic category	IEC 61169-1, Sub-clause 9.4.5
Moisture resistance	MIL-STD-202, Method 106
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition A
RoHS	compliant

Weight

Weight	0,8 g/pc
--------	----------

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
C_Schmidinger	28.03.19	B_Aicher	01.09.20	C00	20-1267	T_Stadler	01.09.20
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de						Tel. : +49 8684 18-0 Email : info@rosenberger.de	
							Page 2 / 2

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Adapters - In Series](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[5918-1103-000](#) [5919-9503-000](#) [651A505](#) [9030-9523-502](#) [R114703000W](#) [R143770000](#) [R161730000](#) [R161753000W](#) [R222M40050](#) [1996352-2](#) [2157155-1](#) [252169-75](#) [AD158](#) [2101130-1](#) [252186](#) [R114704000W](#) [R114720000W](#) [R125771001W](#) [R127703001](#) [R127704001](#) [R127753000](#) [R127.870.001](#) [R127872001](#) [R141717000](#) [R142710000](#) [R142723000](#) [R143703000](#) [R161715000W](#) [R161771000W](#) [R176754000](#) [R405005000](#) [BJ38](#) [5928-9503-000](#) [7222-1501-600](#) [5919-9503-003](#) [R125753001](#) [R125753001W](#) [56K101-K00N5](#) [R164705000](#) [56S201-K00N5](#) [R222M40080](#) [R125513001](#) [R124720003W](#) [R222970000W](#) [R142723000W](#) [19K119-K38L5](#) [53K502-K00N5](#) [CT3393](#) [R222M40060](#) [05S121-S00S3](#)