

Cable Assembly Specification

Rosenberger NA P/N: L71-404-XXX



Description

Rosenberger: Cable: RTK-Flex-405-SPC-FEP
 Connector Combination: SMA+ (m) straight / SMA+ (m) straight
 Length in millimeters: (XXX mm)

General Electrical Specifications

Impedance: 50 ± 2 Ohms
 Operating Frequency: DC to 36 GHz
 Return Loss: 18 dB minimum up to 36 GHz
 Cable Insertion Loss: 5.2 dB/m @ 36 GHz (typical)
 Velocity of Propagation (%): 69.5 % nominal
 Shielding Effectiveness: >100 dB @ 1GHz
 Working Voltage: 850 Vrms

Mechanical Specification

Cable Diameter: 2.64 mm nominal
 Minimum Bend Radius: 6.35 mm
 Mating Torque: 0.8 Nm to 1.1Nm
 Mating Cycles: > 500
 Temperature Range: -65°C to +155°C

MATERIALS AND FINISHES

Cable: RTK-FS-085-FEP; SCPW Center Conductor,
 Connector Interface Per MIL-STD-348A
 Connector Types, Material & Plating
 Coupling nut: passivated stainless steel
 Outer contact: gold plated beryllium copper or equivalent
 Center conductor: gold plated brass

Part Number	Length (End to End, mm)
L71-404-305	305
L71-404-457	457
L71-404-610	610
L71-404-915	915
L71-404-1220	1220
L71-404-1830	1830

* For pair matching requirements, please contact the factory

Cable Assembly Specification

Rosenberger NA P/N: L71-404-XXX



Phone: 717.859.8900
Fax: 717.859.7044

Rosenberger of North America, LLC
PO Box 309
Akron PA 17501

www.rosenbergerna.com
info@rosenbergerna.com

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Cable Assemblies](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[73-6352-10](#) [73-6353-3](#) [73-6364-6](#) [R285001001](#) [R288940004](#) [145111-05-12.00](#) [1661-C-24](#) [1801171170914KE](#) [24P104C24J1-012](#)
[24P104C24P1-006](#) [24P104C24P1-018](#) [24P204C24J1-003](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-](#)
[50](#) [24P103C24P2-003](#) [25P203C25P2-003](#) [R284008001](#) [R285001021](#) [R285426000](#) [R288940003](#) [4814-BB-24](#) [5260-72](#) [JT2N1-CL1-1F](#) [DLP-](#)
[COAX1](#) [4814-K-48](#) [115101-09-06.00](#) [MXHT83QE3000](#) [CCNTN2-MM-LL335-26](#) [73-6351-25](#) [73-6352-3](#) [73-6353-25](#) [1800920920610PJ](#)
[GD0BQ0BQ024.0](#) [1-3636-600-5210](#) [TL8A-11SMA-11SMA-01500-51](#) [R284C0351060](#) [R288940009](#) [R284C0351028](#) [R288940002](#) [9702-](#)
[1SL-1](#) [PT82NSMA](#) [73-6353-10](#) [R285020301W](#) [PCX-18-50](#) [Minibend-9](#) [Minibend-4](#)