


Cable Assembly Specification
Rosenberger NA p/n: L71-800-XXX

RoHS Compliant



Description

Rosenberger: Cable: RTK-FS 085-FEP/SPCW
Connector Combination: SMP female right angle / SMA+ male straight
Length in millimeters: XXX

General Electrical Specifications

Impedance: 50 ± 2 Ohms
Operating Frequency: DC to 26 GHz
Return Loss: 14 dB min up to 26 GHz
Cable Insertion Loss: 4.8 dB/m @ 26 GHz (typical)
Velocity of Propagation: 70% nominal
Shielding Effectiveness: >100 dB @ 1GHz
Working Voltage: 850 Vrms

Mechanical Specification

Cable Diameter: 2.64 mm nominal
Minimum Bend Radius: 6 mm
Mating Torque: SMA+ 8.1 Nm to 13 Nm
Engagement/Disengagement Force: 45 N max / 9 N min – Limited Detent Mating
SMP Connector
Mating Cycles: SMP / SMA+ > 500
Temperature Range: -55°C to +125°C

MATERIALS AND FINISHES

Cable: RTK-FS 085-FEP; SCPW Center Conductor,
Per MIL-STD-348 Hybrid
Connector Interface: SMA+
Connector Types, Material & Plating: **Coupling nut:** passivated stainless steel
Outer contact: gold plated beryllium copper or equivalent
Dielectric: PTFE
Center contact: gold plated brass
SMP: Outer & center contact: gold plated beryllium copper or equivalent
Dielectric: PTFE

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [RF Cable Assemblies](#) category:

Click to view products by [Rosenberger](#) manufacturer:

Other Similar products are found below :

[73-6352-10](#) [73-6353-3](#) [73-6364-6](#) [R285001001](#) [R288940004](#) [145111-05-12.00](#) [1661-C-24](#) [1801171170914KE](#) [24P104C24J1-012](#)
[24P104C24P1-006](#) [24P104C24P1-018](#) [24P204C24J1-003](#) [172-2150-EX](#) [1800920920914PJ](#) [FCB-3030-ALT](#) [21117-046](#) [21117-050](#) [PCX-24-](#)
[50](#) [24P103C24P2-003](#) [25P203C25P2-003](#) [R284008001](#) [R285001021](#) [R285426000](#) [R288940003](#) [4814-BB-24](#) [5260-72](#) [JT2N1-CL1-1F](#) [DLP-](#)
[COAX1](#) [4814-K-48](#) [115101-09-06.00](#) [MXHT83QE3000](#) [CCNTN2-MM-LL335-26](#) [73-6351-25](#) [73-6352-3](#) [73-6353-25](#) [1800920920610PJ](#)
[GD0BQ0BQ024.0](#) [1-3636-600-5210](#) [TL8A-11SMA-11SMA-01500-51](#) [R284C0351060](#) [R288940009](#) [R284C0351028](#) [R288940002](#) [9702-](#)
[1SL-1](#) [PT82NSMA](#) [73-6353-10](#) [R285020301W](#) [PCX-18-50](#) [Minibend-9](#) [Minibend-4](#)