


PJV / PZJ series

125°C 4000 時間品 (ハイブリッドタイプ)
Load life : 125°C 4000 hours (Hybrid Type)
高温対応, 高リップル品
High Temperature, High Ripple Current

AEC-Q200



◆規格表/SPECIFICATION

| 項目 Item | 特性 Characteristics | | | | | | | | | | | |
|--|--|-------------------------------|---|------------------------------|--|---------------|--|-------------------------|---|------|------|------|
| カテゴリ温度範囲 Category Temperature Range | -55~+125°C | | | | | | | | | | | |
| 定格電圧範囲 Rated Voltage Range | 25~63Vdc | | | | | | | | | | | |
| 静電容量許容差 Capacitance Tolerance | ±20% (20°C, 120Hz) | | | | | | | | | | | |
| 漏れ電流 Leakage Current (MAX) | I=0.01CV又は3μAのいずれか大なる値以下 (定格電圧印加2分後) I=0.01CV or 3μA whichever is greater. (After 2 minutes) I=漏れ電流(μA) C=静電容量(μF) V=定格電圧(Vdc) Leakage Current Capacitance Rated Voltage | | | | | | | | | | | |
| 損失角の正接(tan δ) Dissipation Factor(MAX) | <table border="1"> <tr> <td>定格電圧 (Vdc) Rated Voltage</td> <td>25</td> <td>35</td> <td>50</td> <td>63</td> <td rowspan="2">(20°C, 120Hz)</td> </tr> <tr> <td>tan δ</td> <td>0.14</td> <td>0.12</td> <td>0.10</td> <td>0.08</td> </tr> </table> | 定格電圧 (Vdc) Rated Voltage | 25 | 35 | 50 | 63 | (20°C, 120Hz) | tan δ | 0.14 | 0.12 | 0.10 | 0.08 |
| 定格電圧 (Vdc) Rated Voltage | 25 | 35 | 50 | 63 | (20°C, 120Hz) | | | | | | | |
| tan δ | 0.14 | 0.12 | 0.10 | 0.08 | | | | | | | | |
| 耐久性 Endurance | 125°C中で4000時間定格電圧(定格リップル重畳)印加後、下記規格を満足すること。 After applying rated voltage with rated ripple current for 4000 hours at 125°C, the capacitors shall meet the following Criteria. | | | | | | | | | | | |
| 高温高湿負荷 Biased Humidity | 85°C,85%RH中で2000時間定格電圧印加後、下記規格を満足すること。 After applying rated voltage for 2000 hours at 85°C and humidity of 85%, the capacitors shall meet the following Criteria. | | | | | | | | | | | |
| 規格 Criteria | <table border="1"> <tr> <td>静電容量変化率 Capacitance Change</td> <td>初期値の ±30% 以内 Within ±30% of the initial value.</td> </tr> <tr> <td>損失角の正接 Dissipation Factor</td> <td>規格値の 200% 以下 Not more than 200% of the specified value.</td> </tr> <tr> <td>等価直列抵抗 ESR</td> <td>規格値の 200% 以下 Not more than 200% of the specified value.</td> </tr> <tr> <td>漏れ電流 Leakage Current</td> <td>規格値以下 Not more than the specified value.</td> </tr> </table> | 静電容量変化率 Capacitance Change | 初期値の ±30% 以内 Within ±30% of the initial value. | 損失角の正接 Dissipation Factor | 規格値の 200% 以下 Not more than 200% of the specified value. | 等価直列抵抗 ESR | 規格値の 200% 以下 Not more than 200% of the specified value. | 漏れ電流 Leakage Current | 規格値以下 Not more than the specified value. | | | |
| 静電容量変化率 Capacitance Change | 初期値の ±30% 以内 Within ±30% of the initial value. | | | | | | | | | | | |
| 損失角の正接 Dissipation Factor | 規格値の 200% 以下 Not more than 200% of the specified value. | | | | | | | | | | | |
| 等価直列抵抗 ESR | 規格値の 200% 以下 Not more than 200% of the specified value. | | | | | | | | | | | |
| 漏れ電流 Leakage Current | 規格値以下 Not more than the specified value. | | | | | | | | | | | |
| 低温特性 Low Temperature Stability (インピーダンス比) Impedance Ratio (MAX) | $Z(-55^{\circ}\text{C})/Z(+20^{\circ}\text{C}) \leq 2.0$ (100kHz) $Z(-25^{\circ}\text{C})/Z(+20^{\circ}\text{C}) \leq 1.5$ | | | | | | | | | | | |


◆呼称方法/PART NUMBER

□□□
PJV/PZJ
□□□□□
M
□□□
□□
D x L
 定格電圧 シリーズ名 静電容量 静電容量許容差 副記号 リード加工記号 ケースサイズ
 Rated Voltage Series Capacitance Capacitance Tolerance Option Lead Forming Case Size

◆リップル電流補正係数/
MULTIPLIER FOR RIPPLE CURRENT

| 周波数 (Hz) Frequency | 100 ≤ f < 1k | 1k ≤ f < 10k | 10k ≤ f < 20k |
|-----------------------|---------------|----------------|---------------|
| 係数 Coefficient | 0.05 | 0.30 | 0.70 |
| 周波数 (Hz) Frequency | 20k ≤ f < 50k | 50k ≤ f < 100k | 100k ≤ |
| 係数 Coefficient | 0.80 | 0.90 | 1.00 |


◆表示/MARKING




※電圧記号 Voltage code

| 定格電圧 (Vdc) Rated Voltage | 25 | 35 | 50 | 63 |
|-----------------------------|----|----|----|----|
| 電圧記号 Voltage code | E | V | H | J |

◆寸法図/DIMENSIONS



| φD | L | A1 | B1 | C | W1 | P | α |
|-----|------|------|------|-----|---------|-----|-----|
| 6.3 | 6.1 | 6.6 | 6.6 | 2.7 | 0.5~0.8 | 1.8 | 0 |
| 6.3 | 8 | 6.6 | 6.6 | 2.7 | 0.5~0.8 | 1.8 | 0 |
| 8 | 10.5 | 8.3 | 8.3 | 2.9 | 0.8~1.1 | 3.1 | 0 |
| 10 | 10.5 | 10.3 | 10.3 | 3.2 | 0.8~1.1 | 4.5 | 0 |
| 10 | 12.5 | 10.3 | 10.3 | 3.2 | 0.8~1.1 | 4.5 | 0.3 |
| 10 | 16.5 | 10.3 | 10.3 | 3.2 | 0.8~1.1 | 4.5 | 0.3 |




| φD | L | F | φd | α |
|----|----|-----|-----|-----|
| 8 | 9 | 3.5 | 0.6 | 1.5 |
| 10 | 9 | 5.0 | 0.6 | 1.5 |
| 10 | 11 | 5.0 | 0.6 | 1.5 |
| 10 | 15 | 5.0 | 0.6 | 1.5 |

◆標準品一覧表/STANDARD SIZE

| 定格電圧 Rated Voltage (Vdc) | 静電容量 Capacitance (μF) | 外形寸法 Size φD×L (mm) | | 等価直列抵抗 E.S.R (mΩ MAX, 100kHz) | | 定格リプル電流 Rated Ripple Current (mA rms/125°C, 100kHz) | 許容リプル電流 Permissible Ripple Current (mA) | |
|--------------------------------|-----------------------------|------------------------|----------------|----------------------------------|-------|---|--|--------------|
| | | PJV (SMD) | PZJ (LeadWire) | 20°C | -40°C | | 125°C, 100kHz | 90°C, 100kHz |
| 25 | 68 | 6.3×6.1 | - | 50 | | 1080 | 1080 | 1960 |
| | 150 | 6.3×8 | - | 30 | | 1680 | 1680 | 3220 |
| | 270 | 8×10.5 | 8×9 | 25 | | 1920 | 1920 | 3490 |
| | 470 | 10×10.5 | 10×9 | 20 | | 2800 | 2800 | 5090 |
| | 560 | 10×12.5 | 10×11 | 14 | | 3500 | 3500 | 6370 |
| | 820 | 10×16.5 | 10×15 | 11 | | 4000 | 4000 | 7280 |
| 35 | 56 | 6.3×6.1 | - | 50 | | 1080 | 1080 | 1960 |
| | 100 | 6.3×8 | - | 30 | | 1680 | 1680 | 3220 |
| | 180 | 8×10.5 | 8×9 | 25 | | 1920 | 1920 | 3490 |
| | 330 | 10×10.5 | 10×9 | 20 | | 2800 | 2800 | 5090 |
| | 390 | 10×12.5 | 10×11 | 14 | | 3500 | 3500 | 6370 |
| | 560 | 10×16.5 | 10×15 | 11 | | 4000 | 4000 | 7280 |
| 50 | 82 | 8×10.5 | 8×9 | 30 | | 1700 | 1700 | 3090 |
| | 150 | 10×10.5 | 10×9 | 28 | | 2200 | 2200 | 4000 |
| | 180 | 10×12.5 | 10×11 | 18 | | 3000 | 3000 | 5460 |
| | 220 | 10×16.5 | 10×15 | 13 | | 3600 | 3600 | 6550 |
| 63 | 47 | 8×10.5 | 8×9 | 40 | | 1500 | 1500 | 2730 |
| | 82 | 10×10.5 | 10×9 | 30 | | 1900 | 1900 | 3450 |
| | 100 | 10×12.5 | 10×11 | 19 | | 2700 | 2700 | 4910 |
| | 150 | 10×16.5 | 10×15 | 15 | | 3300 | 3300 | 6000 |

◆温度係数/TEMPERATURE COEFFICIENT FOR RIPPLE CURRENT



| 温度 Temperature T(°C) | ≤90 | 95 | 100 | 105 | 110 | 115 | 125 |
|---|------|------|------|------|------|------|------|
| 係数 Coefficient (IMAX/I _r) | 1.82 | 1.73 | 1.63 | 1.52 | 1.41 | 1.29 | 1.00 |

温度係数 IMAX/I₀: 定格リプル電流(I₀)を超えて連続印加可能なリプル電流最大値(IMAX)を示す係数。寿命推定時間は寿命計算式に従う。

Temperature coefficient IMAX/I₀: Coefficient indicating the maximum permissible ripple current (IMAX) that can be continuously applied beyond the rated current (I₀). Estimated lifetime complies with our lifetime calculation formula.

X-ON Electronics

Largest Supplier of Electrical and Electronic Components

Click to view similar products for [Aluminium Organic Polymer Capacitors](#) category:

Click to view products by [Rubycon](#) manufacturer:

Other Similar products are found below :

[750-1809](#) [SEAU0A0102G](#) [MAL218497801E3](#) [MAL218297003E3](#) [MAL218497803E3](#) [MAL218397603E3](#) [MAL218297802E3](#)

[MAL218497701E3](#) [MAL218397102E3](#) [MAL218297804E3](#) [MAL218497804E3](#) [MAL218697005E3](#) [MAL218697509E3](#) [MAL218297603E3](#)

[MAL218397604E3](#) [MAL218697106E3](#) [MAL218297005E3](#) [MAL218397106E3](#) [MAL218297103E3](#) [MAL218397104E3](#) [MAL218297604E3](#)

[MAL218697601E3](#) [MAL218697554E3](#) [MAL218697607E3](#) [MAL218397702E3](#) [MAL218497901E3](#) [MAL218497806E3](#) [MAL218697001E3](#)

[PCZ1V181MCL1GS](#) [PCZ1E331MCL1GS](#) [35PZF270MT810X9](#) [HHXD500ARA470MHA0G](#) [APD1012271M035R](#) [APD1012331M035R](#)

[APA0609471M006R](#) [APA0609561M004R](#) [APA0609561M006R](#) [APD0811271M035R](#) [APA0807561M004R](#) [APA0809331M016R](#)

[APA0809561M010R](#) [APA0809821M004R](#) [APA0809821M006R](#) [APA0812471M016R](#) [APA0812561M016R](#) [APA1010122M006R](#)

[APA1012122M010R](#) [APA1012821M016R](#) [SPT1EM101D11OR](#) [SPT0JM101D08ORVZC](#)